N75-13311

NASA CR-132553

VIBRATION AND STRESS ANALYSIS OF SOFT-BONDED SHUTTLE INSULATION TILES

Modal Analysis With Compact Widely-Spaced Stringers

GRUMMAN

NASA CR-132553

VIBRATION AND STRESS ANALYSIS OF SOFT-BONDED SHUTTLE INSULATION TILES

Modal Analysis With Compact Widely-Spaced Stringers

by

I. U. Ojalvo
F. Austin
A. Levy

September 1974

Prepared by

Grumman Aerospace Corporation
Bethpage, N.Y. 11714

for

Langley Research Center
Under Contract NAS 1-10635-17

FOREWORD

The work reported herein was performed by the Grumman Aerospace Corporation under the NASA/Langley Master Agreement and Contract No. NAS 1-10635 for the Development and Implementation of Space Shuttle Structural Dynamics Modeling Technology. The Work Statement of Task Order No. 17, "Development of an Analytical Program to Analyze Reusable Surface Insulation for Shuttle", authorized and specified the tasks to be performed in this study. The period of performance was for 15 months starting in June of 1973.

The overall supervision of programs under the Master Agreement is provided by Mr. E.F. Baird, Master Agreement Program Manager. The Task Order No. 17 Project Manager was Dr. I. U. Ojalvo. Many individuals at Grumman contributed to the work reported here. However, the authors wish to specifically acknowledge the efforts of Mrs. Patricia Ogilvie for greatly assisting in the development of the associated computer program.

ABSTRACT

This report describes an efficient iterative procedure for the vibration and modal stress analysis of Reusable Surface Insulation (RSI) of multi-tiled Space Shuttle panels. The method, which is quite general, is rapidly convergent and highly useful for this application. A user-oriented computer program based upon this procedure and titled RESIST (REusable Surface Insulation Stresses) has been prepared for the analysis of compact, widely spaced, stringer-stiffened panels. RESIST, which uses finite element methods, obtains three diemensional tile stresses in the isolator, arrestor (if any), and RSI materials. Two-dimensional stresses are obtained in the tile coating and the stringer-stiffened primary-structure plate. A special feature of the program is that all the usual detailed finite element grid data is generated internally from a minimum of input data. The program can accommodate tile idealizations with up to 850 nodes (2550 degrees-of-freedom) and primary structure idealizations with a maximum of 10,000 degrees-of-freedom. The primary structure vibration capability is achieved through the development of a new rapid eigenvalue program named ALARM (Automatic LArge Reduction of Matrices to tridiagonal form).

CONTENTS

ILLUSTRATIONS

TABLES

I. INTRODUCTION

The integrity of a reusable space shuttle system is strongly dependent upon protecting the orbiting vehicle from reentry heating in a manner which does not require significant refurbishment between missions. The thermal protection system (TPS) selected to fulfill this need is a non-structural reusable surface insulation (RSI) material shaped into individual tiles which cover almost all of the orbiter surface area. Most of the tiles are square in planform and measure 15.3 or 20.4 cm (6 or 8 inches) on a side, with thicknesses which vary roughly between 1.3 and 7.6 cm (0.5 and 3 inches). Since loss of a single tile could be catastrophic, RSI tile stresses must be accurately determined for the anticipated static, dynamic and thermal environments.

Recognizing that a system's natural vibration modes may serve as basic building blocks for predicting the response to acoustic excitation, this report describes a new iterative procedure for accurately determining tile stresses associated with typical shuttle-panel lower frequency modes. The results of this work must be combined with a dynamic response program, to obtain realistic forced response results.

A user-oriented computer program based upon the present method of analysis was developed. The program, which is titled RESIST (for REusable Surface Insulation STresses), is capable of computing undamped vibration mode shapes and frequencies of elastically supported multi-tiled panels and determining associated normalized RSI stresses. Typical numerical results from this computer program are presented. A user's manual to facilitate its implementation is presented as Appendix B.

Because of the complex geometry, nonuniform anisotropic material properties, and detailed three-dimensional stress states, the TPS was idealized by finite element assemblages with up to 2500 degrees of freedom per tile. Since a number of tiles affixed to a given structural panel will, in general, interact with one another, application of the standard direct stiffness method would require simultaneous equation systems involving excessive numbers of unknowns. The present iteration scheme overcomes this problem by treating each tile separately. An important byproduct of this approach is that it avoids conditioning problems associated with combining low-stiffness tile isolation ele-

ments ($E \approx 50$ psi) with high-stiffness primary structure elements ($E \approx 10 \times 10^6$ psi). Typical results from the associated computer program reveal a rapid rate of convergence. In addition, a related effort for obtaining tile-stresses associated with statically loaded and heated shuttle panels is presented in Reference 1.

II. TECHNICAL APPROACH

A. STRUCTURAL CONFIGURATION

The design configuration for which an analysis procedure is presented is shown in Figure 1. It consists of a stringer-stiffened flat rectangular panel which supports a nonstructural thermal protection system (TPS).

The TPS is composed of a series of rigidized (RSI) tiles. The tiles are undercut on all four sides to accommodate "filler-strips". The purpose of the nonrigidized filler-strip insulation is to prevent severe heat penetration through the gaps between adjacent tiles.

The RSI material is not bonded directly to the primary structure, but to a thin, stiff, strain arrestor plate first, and then, in turn, to a soft strain isolator material. The function of both these items is to help isolate the primary-structure strains from the low-strength RSI tiles, for the wide range of loading environments which the vehicle must sustain.

B. GENERAL SOLUTION PROCEDURE

Because of the detailed complexity of the structural configuration and the dependence of material properties upon temperature, an analysis technique based upon finite element methods was selected. However, direct application of the standard direct stiffness finite element procedure, to obtain accurate three-dimensional tile stresses, would require equation systems involving excessive numbers of unknowns. The reason for this is that many tiles affixed to a given structural panel may interact. Since each one is a three-dimensional body requiring a detailed structural idealization, their simultaneous consideration requires the solution of large systems of equations. To overcome this problem a rapidly convergent iteration scheme, which treats each tile separately, was developed. The logic flow for an efficient computer program which employs this procedure is presented in Figure 2. The basis for the method is that the TPS is nonstructural but its stress levels, which are critical, must be computed. Thus, it becomes possible to neglect the stiffness of the TPS initially, but not its mass, to determine approximate primary structure modal deflections associated with the vibrations of the overall system. In these initial calculations, the tiles are assumed rigid in shear and thickness-stretching for the purpose of computing their kinetic energies.



Figure1. Typical Design Configuration for Shuttle Thermal Protection System



Figure 2. Logic Diagram for Solution Procedure

An interative procedure is then performed where, for each step, the primary structure oscillatory modal deflections are imposed individually upon each tile at the tile/primary-structure interface, and the tile deflections and interface boundary loads are obtained. The frequency is then updated by computing a Rayleigh Quotient, using the latest non-rigid tile displacements in addition to the corresponding primary structure displacements. The individual tile boundary loads obtained are then assembled and their reactions applied to the primary structure. New primary structure deflections are obtained and compared to the previous set. This process is repeated until convergence is obtained. By this method each tile is temporarily assumed uncoupled from all others. Although this is not strictly true, the coupling involved is sufficiently weak so as to ensure accurate approximate results and rapid convergence as well.

It should be noted that an important byproduct of the present tile-by-tile solution procedure is that, unlike the direct stiffness method, it avoids possible numerical precision problems associated with directly combining a low finite element stiffness ($E = 50$ psi) with a high primary structure stiffness element ($E = 10^7$ psi).

C. STRUCTURAL IDEALIZATION

A pictorial representation of the four finite element types incorporated in the RESIST computer program is presented in Appendix C. A brief description of these elements and how each type is used in the overall structural idealization is presented below.

Primary Structure

The primary structure stiffness idealization is based upon two finite elements contained in the Grumman program library described in Ref 2. The panel surface is represented by flat rectangular membrane-bending elements. The elements possess three deflections and two rotations at each node, for a total of 20 independent nodal degrees of freedom per element. The stiffeners are represented by beam elements which bend, stretch and twist. These elements possess 6 degrees of freedom per node, for a total of 12 degrees of freedom per element.

In general, the stiffeners do not attach to the plate nodes at the beam centroids. The stringer attachment points actually used coincide with the plate node which is closest to the centroid of each beam element. The assumption associated with this connection is that the attachment point and beam centroid

move as two points on the same rigid body. Furthermore, the principal axes of the beam cross section may make an arbitrary angle with the plate surface. Refer to Appendix C for further details on the manner of attachment of beam elements to plate nodes.

The translational mass properties of each rectangular plate element are divided equally and lumped at their middle surface node points. The stiffener translation mass properties of each beam element are also divided equally and lumped at their two centroidal nodes. The rotational inertias of the primary structure beam and plate elements are ignored. The assembled structure is rectangular in planform and is assumed to be statically supported with uniform, but different, arbitrary boundary conditions along each edge.

The above idealizations and assumptions appear consistent with the degree of detail required for obtaining accurate dynamic responses of typical aerospace stiffened panel construction.

Thermal Protection System (TPS) Tiles

The basic stiffness element used for the RSI tiles and strain isolator is the anisotropic hexahedron, as defined in References 3 and 4. The version of this element which is being used contains 3 deflection degrees of freedom per node and 8 nodes per element (the more general version which is available permits up to 20 nodes per element). A typical undercut tile with element and node numbering is shown in Figures 3 & 4. The top layer of each tile also has a coating material which is idealized by rectangular membrane elements. The bottom two layers of each tile comprise the strain isolator and strain arrestor, respectively. The undercut regions of each tile are filled with nonrigidized insulation material. This contributes a small amount of mass to the structure but negligible stiffness and negligible effect upon the stresses within the rigidized tile material. Thus, for purposes of computing the tile deflections and stresses, the undercut regions are treated as empty voids.

Mass Matrix Calculations

Two different mass matrices for the TPS must be computed. The first mass matrix required for the TPS "HEX" element and used in Steps 4 and 5 of the logic flow diagram (Figure 2), is based upon lumping 1/8 of each element's mass at each of its 8 corner nodes for x, y and z translational motion. The second type mass matrix, required in Step 2 of Figure 2, is necessary for computing the ap-



Figure 3. Typical Finite Element Idealization of Shuttle RSI Tile



Figure 4. Top View of Lowest Surface of Deck

proximate mode shapes and frequencies (Step 3 of Figure 2) based upon certain assumptions. These assumptions are that the TPS behaves as a series of rigidly attached masses which contribute inertia, but afford no structural stiffness to the primary structure. Analytical details associated with the latter procedure are described as follows.

Let u, v and w be the displacements of a generic TPS point above a corresponding point on the primary structure plate (p) with displacements u_p, v_p and w_p. Then under the assumption of a rigid-in-shear and thickness-stretch TPS we obtain

$$u = u_p - z \frac{\partial w_p}{\partial x}$$

$$v = v_p - z \frac{\partial w_p}{\partial y}$$

$$w = w_p$$

(i.e., normals to the plate middle surface remain normal).

For a section of TPS above a typical plate element, the kinetic energy is given by

$$T = 1/2 \int_A \int_z \rho(\dot{u}^2 + \dot{v}^2 + \dot{w}^2) \, dz \, dA$$

$$= 1/2 \int_A \int_z \rho \left\{ \dot{u}_p^2 - z\dot{u}_p \frac{\partial \dot{w}_p}{\partial x} + z^2 \left(\frac{\partial \dot{w}_p}{\partial x} \right)^2 + \dot{v}_p^2 - 2z\dot{v}_p \frac{\partial \dot{w}_p}{\partial y} + z^2 \left(\frac{\partial \dot{w}_p}{\partial y} \right)^2 + \dot{w}_p^2 \right\} dz \, dA$$

where A is the planform area surrounding a node.

Defining the integrals in the kinetic energy equation as follows (refer to Figure 5):

$$\int_z \rho dz = \sum_{i=1}^{3} \rho_i \left(Z_{i+1} - Z_i\right) \equiv \overline{\rho h_1}$$

$$\int_z \rho z dz = \sum_{i=1}^{3} \rho_i \left(\frac{Z_{i+1}^2 - Z_i^2}{2}\right) \equiv \overline{\rho h_2}$$

$$\int_z \rho z^2 dz = \sum_{i=1}^{3} \rho_i \left(\frac{Z_{i+1}^3 - Z_i^3}{3}\right) \equiv \overline{\rho h_3}$$

and computing

$$\frac{d}{dt} \left\{ \frac{\partial T}{\partial\left(\dot{u}_p, \dot{v}_p, \dot{w}_p, \frac{\partial \dot{w}_p}{\partial x}, \frac{\partial \dot{w}_p}{\partial y}\right)} \right\}$$

then yields for the TPS mass matrix, per plate node

$$A \begin{bmatrix} \overline{\rho h_1} & 0 & 0 & -\rho h_2 & 0 \\ & \overline{\rho h_1} & 0 & 0 & -\rho h_2 \\ & & \rho h_1 & 0 & 0 \\ & \text{symmetric} & & \rho h_3 & 0 \\ & & & & \rho h_3 \end{bmatrix} \begin{Bmatrix} \ddot{u}_p \\ \ddot{v}_p \\ \ddot{w}_p \\ \frac{\partial \ddot{w}_p}{\partial x} \\ \frac{\partial \ddot{w}_p}{\partial y} \end{Bmatrix} \equiv \left[\bar{M}\right] \left\{\ddot{\delta}_p\right\}$$



Figure 5. TPS Z-Coordinates for Computation of Rigid Mass Matrix

Automatic Grid Generators

To reduce the quantity of input data significantly, two automatic mesh generating schemes were developed. The first procedure generates the primary structure geometry, node and element numbering system, material properties, and boundary conditions; while the second does the exact same thing for the TPS. Each requires a minimum of information, such as overall dimensions stringer pitch, material properties (as a function of temperature) and TPS material temperatures and element properties from which data may be interpolated (see Appendix B for details).

D. APPROXIMATE FREQUENCIES AND MODE SHAPES

This phase employs the primary-structure mass and stiffness matrices (the latter being in lower triangular decomposed form L, where $K = LL^T$) as well as the rigid-tile approximate mass matrix, just described, to obtain approximate mode shapes and frequencies. Since the primary structure idealizations are quite refined, the number of degrees of freedom will be in the thousands with 10,000 as an upper limit. Thus, an efficient and reliable eigenvalue reduction scheme is required.

The reduction procedure employed was suggested by Crandall(5) and is based upon an algorithm for accommodating the full matrix due to Lanczos(6). However, the basic scheme is numerically unstable. The essential improvements necessary to correct this weakness were made by Ojalvo and Newman(7), who were the first to develop a successful reduction scheme for large scale problems. The work was further streamlined by Newman and Pipano(8) through the use of banded matrix packing techniques and the computation of convenient error bounds on frequency squared.

The present program, which is a synthesis of these works, is called ALARM (Automatic LArge Reduction of Matrices). It is designed to operate efficiently through use of the Grumman COmprehensive Matrix Algebra Procedures (COMAP) interface programs developed by C. Wilkie and F. Nolan.

A mathematical statement of the original vibration problem considered is

$$[K]\{\phi\} = \omega^2 [M]\{\phi\} \tag{1}$$

where n x n stiffness matrices [M] and [K], which are generally highly banded and sparse, may be singular but non-negative, with the only restirction being $n \leq 10{,}000$. The associated reduced eigenvalue problem is symmetric, tri-diagonal and of the form[7]

$$\begin{bmatrix} \alpha_1 & \beta_1 & & & \\ & \alpha_2 & \beta_2 & & \\ & & \ddots & \ddots & \\ \text{Symmetric} & & & \ddots & \ddots \\ & & & \alpha_{m-1} & \beta_{m-1} \\ & & & & \alpha_m \end{bmatrix} \left\{ y \right\} = \lambda \left\{ y \right\} \tag{2}$$

where m is typically several orders of magnitude smaller than n, and $\lambda = 1/\omega^2$.

The algorithm used for obtaining the α_i and β_i of Eq. (2), as will be shown, is based upon the power method[9]. Unlike the power method, however, in which each vector is discarded as a new one is generated, the present procedure retains each vector V_i after orthogonalizing and normalizing it to all previous vectors such that $\lfloor V_i \rfloor \{V_j\} = \delta_{ij}$, where δ_{ij} is the Kronecker delta. Thus, the involvement of the original system's lower modes is strengthened. A Rayleigh-Ritz approximation, using the n x m matrix [V] whose columns are the V_i, follows from the substitution of

$$[L]^T \{\phi\} \equiv [V]\{y\} \tag{3}$$

into Eq. (1) where

$$[K] = [L][L]^T \tag{4}$$

Premultiplication of the resulting equation by $\lambda\ [V]\ [L]^{-1}$ then yields Eq. (2). This result is now solved (in core) by Sturm-Sequencing for the λ's and power iterations (as described on page 622 of Reference 9) for the eigenvectors.

Experience has shown[7] that over half the number of modes, $\frac{m}{2}$, obtained by this method are "exact" with a sharp drop-off in accuracy somewhere around $\frac{2}{3}m$; thus, the program usually sets m to 2q+1, where q is the number of desired modes. Newman-Pipano error bounds[8] are useful indicators of where a loss of accuracy occurs. The computational steps for obtaining the approximate frequencies and mode shapes are presented in the Appendix A.

E. FLEXIBLE TILE SOLUTIONS

The tiles are originally treated as nonstructural mass items. However, since their modal stress states are desired, it is necessary to eventaully account for their flexibility. This is achieved by imposing the primary-structure/TPS interface deflections $\{\delta_B\}_i \sin \omega t$, to each tile and computing the associated tile deflections, $\{\delta_A\}_i \sin \omega t$, to obtain tile stresses and reactions, $\{-P_B\} \sin \omega t$. As described earlier, this is repeatedly done in an iterative manner until convergence is obtained.

Referring to Figure 6, the associated steady-state partitioned matrix equations governing each tile are

$$\left[\begin{array}{c|c} K_{AA} - \omega^2 M_{AA} & K_{AB} \\ \hline K_{BA} & K_{BB} - \omega^2 M_{BB} \end{array}\right] \left\{\begin{array}{c} \delta_A \\ \hline \delta_B \end{array}\right\}_i = \left\{\begin{array}{c} 0 \\ \hline P_B \end{array}\right\}_i \tag{5}$$

where use has been made of the fact that the tile mass matrix is diagonal.

This equation is then decomposed into

$$[K_{AA} - \omega^2 M_{AA}]\ \{\delta_A\}_i = -[K_{AB}]\ \{\delta_B\}_i \tag{6}$$

and

$$-[K_{BA}]\ \{\delta_A\}_i - [K_{BB} - \omega^2 M_{BB}]\ \{\delta_B\}_i = \{-P_B\}_i \tag{7}$$



Figure 6. Notation for Flexible Tile Solution Approach

Prior to solution of Eq. (6) for $\{\delta_A\}_i$, it is noted that $[K_{AA} - \omega^2 M_{AA}]$ is not positive definite if any of the eigenvalues, λ_A, of

$$\lambda_A [K_{AA}] \{\delta_A\} = [M_{AA}] \{\delta_A\}$$

satisfy the equation

$$\lambda_A \leq \frac{1}{\omega^2} \tag{8}$$

where ω is the current (approximate) frequency value.

Since the efficient solution routine(9) that is used for large banded symmetric equations, such as Eq. (2), requires positive definiteness, Eq. (6) is premultiplied by $(K_{AA} - \omega^2 M_{AA})$ to insure this property. Thus, the equation treated to obtain $\{\delta_A\}_i$ is

$$[K_{AA} - \omega^2 M_{AA}]^2 \{\delta_A\}_i = [K_{AA} - \omega^2 M_{AA}] \{-K_{AB}\, \delta_B\}_i \tag{9}$$

Following this, Eq. (7) is used to compute $\{-P_B\}_i$. Once convergence of the primary structure deflections has been achieved, the corresponding tile modal stresses are computed from the hexahedron stress recovery equations (3).

F. FREQUENCY UPDATE

Since the modes and frequencies obtained originally ignored the tile stiffness and true displacements, the resulting frequencies are only approximate. To correct these, the frequencies are updated through use of a Rayleigh Quotient calculation in which the latest tile and primary structure deflections are used in the equation

$$\omega_R^2 = \frac{\sum_i \lfloor \delta_T \rfloor_i \left[K_T\right] \left\{\delta_T\right\}_i + \lfloor \delta_{ps} \rfloor \left[K_{ps}\right] \left\{\delta_{ps}\right\}}{\sum_i \lfloor \delta_T \rfloor_i \left[M_T\right] \left\{\delta_T\right\}_i + \lfloor \delta_{ps} \rfloor \left[M_{ps}\right] \left\{\delta_{ps}\right\}_i} \tag{10}$$

where the subscripts "T" and "ps" denote tile and primary structure, respectively. Thus, $\{\delta_{ps}\}$ are the latest primary structure deflections, which

originally are the $\{\phi\}$ of Eq. (1), $[K_{ps}]$ and $[M_{ps}]$ are the banded stiffness and mass matrices, respectively, of the primary structure and tile. Thus, the $[K_T]$ and $[M_T]$ matrices of Eq. (10) are related to the stiffness and mass matrices of Eq. (5) as follows:

$$[K_T] = \begin{bmatrix} K_{AA} & K_{AB} \\ K_{BA} & K_{BB} \end{bmatrix} \qquad [M_T] = \begin{bmatrix} M_{AA} & 0 \\ 0 & M_{BB} \end{bmatrix}$$

G. PRIMARY-STRUCTURE DEFLECTION UPDATE

The original primary-structure modal deflections are approximate, should be checked and, if necessary, corrected. Employing the latest compatible set of tile and primary-structure deflections, the frequencies are recomputed, to give $\omega_{Rayleigh}$, by the method described in the previous subsection. The steady oscillating tile boundary reactions $\{-P_B\}_i \sin \omega_R t$ are collected for all the tiles and applied to the primary-structure, to yield new modal deflections, as follows:

$$[K_{ps} - \omega_R^2 M_{ps}] \quad \{\delta_{ps}\} = \{-P_B\} \tag{11}$$

where $\{-P_B\} \sin \omega_R t$ is the assembled load reaction of all the tiles acting upon the primary-structure.

Once again, since the solution routine[(2)] that is used for large, banded symmetric equations requires the positive-definiteness property, Eq. (11) is premultiplied by $[K_{ps} - \omega_R^2 M_{ps}]$ prior to solution for the $\{\delta_{ps}\}$, i.e., the actual equation solved for $\{\delta_{ps}\}$ is:

$$[K_{ps} - \omega_R^2 M_{ps}]^2 \quad \{\delta_{ps}\} = [K_{ps} - \omega_R^2 M_{ps}] \{-P_{ps}\} \tag{12}$$

For consistency, the deflections $\{\delta_{ps}\}$ are then normalized such that

$$\lfloor \delta_{ps} \rfloor \{\delta_{ps}\} = 1$$

prior to comparison to the previous set, to establish convergence. The convergence test employed consists in satisfying

$$\text{max element of } \left\{ \left| \delta_{\substack{ps \\ present}} - \delta_{\substack{ps \\ previous}} \right| \right\} \leq \epsilon \left| \text{largest element of } \delta_{\substack{ps \\ present}} \right|$$

where ϵ is an empirically determined positive input quantity.

III. NUMERICAL RESULTS

A. TILED CONFIGURATIONS

To demonstrate the numerical convergence properties of the proposed iteration scheme, two examples are presented here. The material properties and loading conditions used, while not precise in a specific design sense, are representative of the problem parameters the method is intended to accommodate.

Figure 7 shows the configuration, finite element idealization, material properties, and boundary conditions considered for Example 1. The fundamental frequency, largest primary-structure normalized deflection and average stress components for certain critical RSI elements are presented as a function of iteration number in Table 1. Besides revealing a rapid convergence rate, the results presented indicate a high level of accuracy for the first iterate in that the maximum frequency, deflection and σ_X errors are less than 2%. The errors in σ_Z were higher for the first iteration (approximately 20%), but these settled down to under 4% in the second iteration.

Similar observations were made for the more realistic shuttle tile configuration of Example 2 shown in Figure 8. This problem consists of three 6 x 6 inch tiles, each of which is two inches thick and has 1 x 1/2 inch edge undercuts. The primary structure is a .041 inch aluminum plate with offset stringers spaced half an inch apart. The two opposite shorter boundaries are clamped while the longer ends are free.

The fundamental frequency and peak normalized deflection, as a function of iteration number, are shown in Table 2. The primary-structure mode-shape is plotted in Figure 9 for iterations 1, 2, and 4. The corresponding stresses for iterations 1 and 4 are shown in Figures 10 through 12. Running time for this realistic type problem on an IBM 370 averaged 1 1/3 CPU minutes per tile plus a fixed time of 13 minutes per iteration. Thus, four iterations of the three tiled configuration required approximately 68 CPU minutes.



Figure 7. Example 1: Sample Problem Used to Demonstrate Numerical Convergence of Iteration Scheme

TABLE 1

FUNDAMENTAL FREQUENCY, MAXIMUM DEFLECTION, AND CRITICAL TILE STRESSES VS. ITERATION NUMBER (Refer to Figure 7)

ITERATION NO.	ω_1 (Hz)	MAXIMUM NORMALIZED DEFLECTION (INCHES)	RSI STRESSES					
			σ_x(psi) ELEMENT NO. 25			σ_z(psi) ELEMENT NO. 21		
			TILE NO. 1	TILE NO. 2	TILE NO. 3	TILE NO. 1	TILE NO. 2	TILE NO. 3
0	510	0.180	-	-	-	-	-	-
1	425	0.181	-43	-88	-46	22	57	35
2	427	0.181	-40	-86	-43	22	49	28
3	425	0.181	-40	-86	-46	21	48	28
4	425	0.181	-40	-86	-46	22	49	28



Figure 8. Example 2: Typical Configuration That Computer Program is Capable of Analyzing

TABLE 2

FUNDAMENTAL FREQUENCY AND MAXIMUM PRIMARY STRUCTURE DEFLECTION AS A FUNCTION OF ITERATION NUMBER FOR EXAMPLE 2

ITERATION NUMBER	FUNDAMENTAL FREQUENCY (Hz)	NORMALIZED MAX PRIM STRUCT DEFLECTION (inches)
0	146	0.111
1	153	0.108
2	153	0.111
3	154	0.110
4	153	0.110





Figure 9. Example 2: Plate Structure Normal Deflections of First Mode



Figure 10. Example 2: Normalized First Mode Direct Stresses for Tiles 1 and 2 in Planer Directions as a Function of Spanwise Coordinate



Figure 11. Example 2: Normalized First Mode Direct Stresses for Tiles 1 and 2 in Planer Directions as a Function of Spanwise Coordinate



Figure 12. Example 2: Normalized First Mode Direct Stresses for Tiles 1 and 2 as a Function of Chordwise Coordinate

B. UNTILED PRIMARY STRUCTURE

Figure 13a is representative of a typical stiffened untiled "shuttle panel" undergoing dynamic testing at the Langley Research Center. Figure 13b shows the finite element idealization that the RESIST computer program generated for this panel. The numerical results obtained (see Table 3) reveal a tendency for the frequencies to occur in groups of 7. The geometric significance of this clustering is that the modes in each group are related to the physical presence of 7 stringers, which subdivide the panel into 6 bays.

The idealized stringers are assumed to be attached at only a single rivet line. However, in the configuration of Figure 13a, each stringer is attached by two rivet lines to form a closed section torque-tube. Thus, the idealization of Figure 13b is inadequate for predicting the higher cross-stringer modes (i.e. $m > 0$) when the stiffened plate-pitch, a, is not small compared to the unstiffened plate-pitch, b. Since a is of the order of b for realistic shuttle panels, the idealization capability within RESIST should be extended to accommodate closed-section stringers with narrow spacing in addition to the present capability which treats widely spaced, or open-section, stringers.



Figure 13. RESIST Idealization of Shuttle Panel for Test at Langley

TABLE 3

NATURAL FREQUENCIES FOR RESIST IDEALIZATION OF SHUTTLE PANEL FOR TEST AT LANGLEY

Mode Shapes		RESIST Finite Element Analysis
n*	m**	
1	0	106
1	1	108
1	2	126
1	3	136
1	4	150
1	5	183
1	6	203
2	0	286
2	1	288
2	2	302
2	3	315
2	4	328
2	5	343
2	6	346

* n = number of 1/2 sine waves between spanwise supports

** m = number of nodes in cross-stringer direction

IV. CONCLUSIONS AND RECOMMENDATIONS

An iterative procedure for the vibration stress analysis of RSI multi-tiled shuttle panels has been developed. The method, which is quite general, is rapidly convergent and highly useful for this application.

A user-oriented computer program based upon this procedure and titled RESIST has been coded. RESIST, which uses finite element methods, obtains three dimensional tile stresses in the isolator, arrestor (if any) and RSI materials. Two dimensional stresses are obtained in the tile coating and the stringer-stiffened primary structure plate. A special feature of the program is that all the usual detailed finite element grid data is generated internally from a minimum of input data.

The program may be used in an iterative mode to obtain detailed results. However, for parametric design studies, reasonably accurate results may be obtained by using only one iteration at a significant savings in running time. This is achieved by having the program analyze certain specific tiles of a multi-tiled panel only once, while ignoring less critically stressed tiles.

At present the program can accommodate tile idealizations with up to 850 nodes (2,550 degrees-of-freedom) and primary structure idealizations with a maximum of 10,000 degrees-of-freedom. In addition, the tile pattern must begin and end at a structural frame and the isolator material must be isotropic. Should such restrictions, or any similar ones, require alteration as the shuttle TPS design changes, it would appear logical to update RESIST.

To enhance the usefulness of the present work, it should be extended to accommodate closely spaced, closed-cell stiffeners (which are more typical of Space Shuttle panel designs) and to perform acoustic response analyses as well.

V. NOMENCLATURE

A	Plate area associated with a given primary-structure node
$[A]$	Matrix used in large eigenvalue algorithm $(= [L]^{-1} [M] [L]^{-T})$
$[G]$	Matrix used in large eigenvalue algorithm
$[K]$	Stiffness matrix used in large eigenvalue algorithm
$[K_T]$	Tile stiffness matrix
$[K_{ps}]$	Primary structure stiffness matrix
$[K_{AA}]$, $[K_{AB}]$, $[K_{BA}]$, $[K_{BB}]$	Matrix partitions of $[K_T]$
$[L]$	Lower triangular decomposition of stiffness matrix
$[M_{ps}]$	Diagonal primary structure mass matrix
$[M_{rt}]$	Mass matrix associated with rigid tile
$[M_T]$	Tile mass matrix
$[\overline{M}]$	Approximate tile mass matrix associated with a typical plate node
$[M]$	Mass matrix used in large eigenvalue algorithm
$[M_{AA}]$, $[M_{BB}]$	Diagonal partition matrices of tile mass matrix
$\{-P_B\}$	Reaction loads caused by all tiles acting upon primary structure
$\{P_B\}_i$	Load acting upon i^{th} tile caused by primary structure
T	Approximate kinetic energy associated with a typical node
$\{\overline{V}_i^{(s)}\}$	Unnormalized and unrefined Lanczos vector
$\{\overline{V}_i\}$	Refined but unnormalized Lanczos vector
$\{V_i\}$	Normalized and refined Lanczos vector

Z_i	Thickness coordinates. Refer to Figure 5.
$\{b_i\}$	Vector used in eigenvalue algorithm
$\{g_i\}$	Vector used in eigenvalue algorithm
m	Order of reduced eigenvalue problem
n	Order of unreduced eigenvalue problem
$\bar{n}$	Number of dynamic degrees of freedom
q	Number of desired approximate system modes
t	Time
u, v, w	Approximate displacement components of arbitrary point within tile
u_p, v_p, w_p	Displacement components of primary structure
x, y, z	Spacial coordinates
$\{y\}, \{y_i\}$	Eigenvectors of reduced eigenvalue problem
y_i^m	Last element of $\{y_i\}$
α_i, β_i	Diagonal and superdiagonal elements of tridiagonal reduced eigenvalue matrix
$\{\delta_{ps}\}$	Primary structure deflections
$\{\delta_A\}_i, \{\delta_B\}_i$	Deflections of i^{th} tile at node points not in contact (A) and in contact (B) with plate
$\{\delta_T\}_i$	Deflections of i^{th} tile
ϵ	Primary structure deflection convergence parameter
λ	Eigenvalue of reduced problem

λ_A	Eigenvalue problem associated with "A" degrees-of-freedom of tile
ρ	Mass density
$\overline{\rho h_i}$	Integrated mass density parameter
$\{\phi_{ps}\}$	Approximate primary structure mode shape
ω	Frequency of large eigenvalue problem
ω_R^2	Rayleigh Quotient
ω_{rt}	Approximate rigid-tile frequency

VI. REFERENCES

1. Ojalvo, I. U., Levy, A. and Austin, F., "Thermal Stress Analysis of Reusable Insulation for Shuttle", NASA CR-132502, 1974.

2. Dwyer, W. J., Emerton, R. K., and Ojalvo, I. U., "An Automated Procedure for the Optimization of Practical Aerospace Structures", Vol. I, AFFDL-TR-70-118, April 1971.

3. Armen, H., Levine, H., Pifko, A. and Levy, A. "Nonlinear Analysis of Structures,"NASA CR-2351, 1974.

4. Levy, A. "A Three-Dimensional "Variable Node" Isoparametric Solid Element", to be published as a GAC Research report.

5. Crandall, S. H.: Engineering Analysis. McGraw-Hill, N. Y., 1956, pp. 106-109.

6. Lanczos, C.: An Iteration Method for the Solution of the Eigenvalue Problem of Linear Differential and Integral Operators., J. Res. Nat. Bur. Stand., Vol. 45, 1950, pp. 225-282.

7. Ojalvo, I. U., and Newman, M., "Vibration Modes of Large Structures by an Automatic Matrix-Reduction Method," AIAA J., Vol. 8, No. 7, 1970, pp. 1234-1239.

8. Newman, M. and Pipano, A., "Fast Modal Extraction in NASTRAN via the FEER Computer Program", NASA TMX-2893, September 1973, pp. 485-506.

9. Wilkinson, J. H., The Algebraic Eigenvalue Problem, Clarendon Press, Oxford, 1965.

10. Ogilvie, P., Levy, A., Austin, F., and Ojalvo, I.U., "Programmer's Manual for RESIST (Static and Dynamic REusable Surface Insulation STress Program)," proposed NASA CR, 1974.

APPENDIX A

LARGE EIGENVALUE SOLUTION ALGORITM

The algorithm employed to initially determine the approximate mode shapes and frequencies of the system(7,8) is outlined below:

1. Initialization: Set $i = 0$ and determine m, the order of the reduced problem as follows:

   For $\bar{n} \le 7$ set $m = \bar{n}$

   For $\bar{n} > 7$ set $m = \bar{n}$ if $2q + 1 \ge \bar{n}$

   $m = 2q + 1$ if $2q + 1 < \bar{n}$ and $q > 3$

   $m = 7$ if $q \le 3$

   "Reverse", transpose, and "reverse" [L] to obtain $[L]^{RTR}$ and save result for repeated use in Step 6 (see discussion in Step 6).

2. Generate $\{V_0\}$: Use a random number generator for each element. Go to 6.

3. Compute $\beta_{i-1} = \lfloor \bar{V}_i \rfloor \{\bar{V}_i\}$

4. Test $i \ge m+1$: if no--continue; if yes--go to 15

5. Compute $\{V_i\} = \frac{1}{\beta_{i-1}} \{\bar{V}_i\}$: This step normalizes the vectors such that

   $$\lfloor V_i \rfloor \{V_i\} = 1$$

6. Solve for $\{g_i\}$ and save it if $i \ge 1$. This is the solution vector of

   $$[L]^T \{g_i\} = \{V_i\}$$

   The usual Grumman routine used for solutions of this type equation is titled QBAC (see Reference 10). However, it is not too efficient when there is only one right-hand side, as is our case.

A more efficient procedure is to manipulate $[L]^T$, which is an upper triangular matrix, into lower triangular form, and then to use QFOR to solve the equation $[L]^{RTR} \{g_i\}^R = \{V_i\}^R$, where $\{g_i\}^R$ and $\{V_i\}^R$ correspond to $\{g_i\}$ and $\{V_i\}$, respectively, each with the order of its elements reversed (e.g., the first element of $\{g_i\}$ is the last element $\{g_i\}^R$ and vice versa). The manipulation of $[L]^T$ into $[L]^{RTR}$ requires two matrix row reversals (COMAP routine REVERS*) and one transpose (TRAN*) operation in the order REVERS-TRAN -REVERS. The most time consuming routine of these three is TRAN, which is even slower than QFOR*. However, since it is only necessary to compute $[L]^{RTR}$ once (see Step 1), each solution for $\{g_i\}$, by the present procedure, requires far less running time than by the direct method (e.g., 1/30th the CPU time for a 3,000 DOF system).

7. Compute $\{b_i\}$ from $\{b_i\} = [M] \{g_i\}$. This is actually accomplished by forming $(\lfloor g_i \rfloor [M])^T$ which is considerably more efficient using the COMAP associated subroutines.

8. Solve for $\{A V_i\}$ from $[L] \{A V_i\} = \{b_i\}$ using QFOR. Note that $[A] = [L]^{-1} [M] [L]^{-T}$. Thus $\{A V_i\}$ is one power iteration of V_i and so accentuates its lower modal content.

9. Test i: if $i = 0$, set $\overline{V}_1 = A V_0$ and return to step 3.
if $i \neq 0$, continue.

----
*See Reference 10 for descriptions of these subroutines.

10. Compute $\alpha_i = \lfloor V_i \rfloor \{A\ V_i\}$ and step up i by 1.

This step computes the Rayleigh Quotient associated with the vector $\{V_i\}$.

11. For i = 2, compute $\left\{\overline{V}_2^{(1)}\right\} = \{A\ V_1\} - \alpha_1 \{V_1\}$

12. For i ≥ 3, compute $\left\{\overline{V}_1^{(1)}\right\} = \left\{A\ V_{i-1}\right\} - \alpha_{i-1} \left\{V_{i-1}\right\} - \beta_{i-2} \left\{V_{i-2}\right\}$

and set s = 1.

This step theoretically[7] orthogonalizes $\{\overline{V}_i\}$.

However, any slight numerical inprecision tends to bias the resulting vestors unfavorably through the present iterative generation scheme. The suggested correction to this numerical stability problem is contained in the following two steps.

13. Test $s > \overline{s}$: if no, continue; if yes, set $\{V_i\} = \left\{\overline{V}_i^{(s)}\right\}$ and return to 3.

14. Replace $\left\{\overline{V}_i^{(s)}\right\}$ by $\left\{\overline{V}_i^{(s)}\right\} - \left(\lfloor V_j \rfloor \left\{\overline{V}_i^{(s)}\right\}\right) \left\{V_j\right\}$ for j = 1

Continue correcting $\left\{V_i^{(s)}\right\}$ by repeating the above step for j = 2, 3, ..., i-1. Step up s by 1 and return to 13.

15. Solve for the lowest 3/4$^{\text{ths}}$ (rounded to an integer) of the frequencies of Eq. 2 using Sturm sequencing[9].

16. Solve for the eigenvectors associated with the highest "q" eigenvalues λ, each normalized such that

$$\lfloor y \rfloor \{y\} = 1$$

17. Compute and print $\omega_i = \lambda_i^{-1/2}$ and $f_i = \frac{\omega_i}{2\pi}$

18. Compute $\frac{\left|\beta_m \, y_i^m\right|}{\lambda_i}$, where y_i^m is the m^{th} (last) component of $\{y_i\}$.

This term is an error bound (9) on

$$\left| \frac{\omega_i^2}{\omega_{i\,\text{exact}}^2} - 1 \right|$$

19. Compute $[G]\{y_i\}$ for i = 1, 2,----, q where the columns of $[G]$ are the vectors $\{g_i\}$. These are the vibration mode shapes $\{\phi_i\}$ associated with the lower q eigenvalues.

These are then normalized such that

$$\lfloor \phi_i \rfloor \{\phi_i\} = 1$$

APPENDIX B

USER'S MANUAL FOR

RE*S*I*ST

(STATIC AND DYNAMIC REUSABLE SURFACE INSULATION STRESS PROGRAM)

A. INTRODUCTION

This Appendix describes the use of a finite element based structural computer program for determining the static response and natural vibrations of TPS protected shuttle panels. The program is titled "RESIST" for static and dynamic REusable Surface Insulation STresses. The logic flor for RESIST is presented in Figure B-1.

The basis for the method is that the TPS is nonstructural but its stress levels, which are critical, must be computed. Thus, it becomes possible to neglect the stiffness of the TPS initially, but not its mass in the vibration, to determine approximate primary structure deflections.

An iterative procedure is then performed where, for each step, the primary structure deflections are imposed individually upon each tile at the tile/primary-structure interface, and the tile deflections and interface boundary loads are obtained. For the vibration option, the frequency is updated by computing a Rayleigh Quotient, using the latest non-rigid tile displacements in addition to the corresponding primary structure displacements. The individual tile boundary loads obtained are then assembled and their reactions are applied to the primary structure. New Primary structure deflections are obtained and compared to the previous set. This process is repeated until convergence is obtained.

B. PROGRAM LIMITATIONS

The usual assumptions for programs based upon the linear elastic finite element method are applicable to RESIST. However, to facilitate the preparation of program input, a number of simplifications regarding the configuration and loadings have been made. Thus, the generation of a voluminous quantity of finite element input data has been greatly reduced by inclusion of a series of data preprocessing subroutines within RESIST. The restrictions upon which these subroutines are based follows:

1. Boundary conditions and edge loadings are assumed uniform along the four rectangular plate edges defined by $x = 0, L_x$ and $y = 0, L_y$.

2. The primary structure plate temperature and properties are all uniform.



* APPLY FOAM/PRIMARY-STRUCTURE BOUNDARY DISPLACEMENT TO EACH TILE SPECIFIED, ONE AT A TIME, AND COMPUTE ALL NON BOUNDARY TILE DISPLACEMENTS AND STEADY STATE BOUNDARY LOADS.

** FOR VB PROBLEMS USE LOADS FROM VI AND FREQUENCY FROM VII. FOR ST PROBLEMS WITH $i = 1$, USE LOADS FROM MODULE X. HOWEVER, IF $i \neq 1$ GET STATIC TILE LOADS FROM VI AND BOUNDARY LOADS FROM X.

Figure B-1 Flow Chart for RSI Stress Analysis Program "Resist"

3. The stringers are equally spaced with temperatures and properties which are all uniform.

4. All tiles are geometrically identical as are their temperature distributions and uniform pressure loadings.

5. The boundary conditions must be selected such that the primary structure is statically stable.

The remaining limitations are primarily concerned with the program's capacity and should be adhered to by the user. These limitations are as follows:

6. Maximum number of nodes in a tile = 850.

7. Maximum number of finite elements running in any one direction in a tile = 20.

8. Maximum number of nodes in primary structure = 2500.

9. Maximum number of primary structure nodes along x or y direction = 1,000.

10. Maximum number of degrees of freedom in primary structure

$$= \begin{cases} 10{,}000 \text{ for vibration option.} \\ 15{,}000 \text{ for statics option.} \end{cases}$$

11. Maximum number of natural mode shapes = 50.

12. Maximum number of stringers = 15.

13. To avoid a singular stiffness matrix, I_z, and $\sin\beta$ must not both be zero for a given stringer.

A violation of restrictions 6-13, inclusive, will cause the program to stop and an appropriate warning message to appear.

To insure symmetry of solutions for panels which are symmetric with regard to stringer locations about $y = L_y/2$, care should be taken wtih the input data to see that the plate nodes associated with the stringers are symmetric about $y = L_y/2$. Thus, the number of primary structure finite elements in the y direction should not be odd if the number of panel stringers is even.

C. INPUT INSTRUCTIONS

A description of the card input for the IBM 370 and CDC 6600 versions of this program is presented in this section.

In addition to the first two input cards which contain literal data, such as special program title and date, in columns 1 through 80, inclusive; there are six groups of input cards containing the following information:

- Group A - Instructions regarding the type of problem being performed, number of iteratious desired, and type of output information.
- Group B - Details of the geometric configuration and finite element mesh of the primary structure and tiles. (Card B.4 is omitted if there are no tiles)
- Group C - Defines the primary structure and RSI temperature dependent material properties. If there is no TPS, cards C.3 through C.11 are omitted.
- Group D - Specifies the primary structure boundary conditions
- Group E - Describes the mechanical loading upon the primary structure as well as its temperature. These cards are omitted when the vibration option is used
- Group F - Defines the RSI temperature distribution. These cards are omitted if there is no TPS.



A. PROGRAM OPTIONS AND CONTROL — Sheet 1 of 2

CARD(S)	COL(S)	FORMAT	SYMBOLS	UNITS	DESCRIPTION
A.1	1-5	I5	-	-	1 in col. 5 denotes that a statics problem is being treated. Skip cols. 6-25 in such cases
					2 in col. 5 denotes that a natural vibration problem is being treated.
	6-10	I5	N_D	-	Number of desired mode shapes (50 is the maximum permitted).
	16-20	I5	$\bar{s}$	-	Number of reorthogonalizations for eigenvalue algorithm. A min of 2 and a max. of 5 is suggested with 3 as an adequate compromise for most problems. The run should be repeated with greater values for $\bar{s}$ or N_D if the frequency error bound of a desired mode is greater than 1%.
	21-25	I5	-	-	Vibration mode number for which tile modes are desired.
	26-30	I5	i_{max}	-	Maximum number of iterations
	31-40	E10.0	ϵ	in. or rad.	Convergence parameter. Maximum primary structure deflection or rotation difference between iterations divided by magnitude of largest element.
	46-50	I5	-	-	0 in col. 50 indicates that primary structure stresses and strains are not required.
					1 in col. 50 indicates that only midplate strains and stresses of primary structure are required.
					2 in col. 50 indicates that only top of plate strains and stresses of primary structure are required.
					3 in col. 50 indicates that only bottom of plate strains and stresses of primary structure are required.
					4 in col. 50 indicates that only mid and top of plate strains and stresses of primary structure are required.
					5 in col. 50 indicates that only mid and bottom of plate strains and stresses of primary structure are required.
					6 in col. 50 indicates that only top and bottom of plate strains and stresses of primary structure are required.
					7 in col. 50 indicates that top, bottom, and mid plate strains and stresses of primary structure are required.
	51-60	E10.0	—	lb-in-sec^2	Overhung rotatory mass inertia associated with each stringer. Used if plate overhange $x = 0$ and $x = L_x$ boundaries.

A. PROGRAM OPTIONS AND CONTROL – Sheet 2 of 2

CARD(S)	COL(S)	FORMAT	SYMBOLS	UNITS	DESCRIPTION
A.2	1-5	I5	-	-	0 in col. 5 indicates that tile stresses are not required. 1 in col. 5 indicates that tile stresses are to be computed after each iteration is performed. 2 in col. 5 indicates that tile stresses are to be computed only after last iteration is performed or only after convergence is obtained.
	6-10	I5	-	-	0 in col. 10 if primary structure stresses and strains were not requested in column 50 of Card A.1. 1 in col. 10 indicates that primary structure stresses and strains are required after each iteration. 2 in col. 10 indicates that primary structure stresses and strains are required only after last iteration or, only after convergence.
	11-15	I5	-	-	0 in col. 15 indicates no tiles on the primary structure. Skip card A.3* 1 in col. 15 indicates that there are tiles on the primary structure.
	16-20	I5	-	-	1 in col. 20 indicates tile node map printout desired. 0 = no node map printout.
	21-25	I5	-	-	1 in col. 25 indicates tile element map printout desired. 0 = no element map printout.
	26-30	I5	-	-	1 in col. 30 indicates tile nodal coordinate, temp. and nodes per element printout. 0 in col. 30 indicates suppression of this printout.
	31-35	I5	-	-	1 in col. 35 indicates printout of element stiffness matrices. 0 = no element stiffness matrices.
	36-40	I5	-	-	1 in col. 40 indicates printout of assembled stiffness matrices and ALARM reorthog. info. 0 in col. 40 indicates suppression of this printout.
	41-45	I5	-	-	1 in col. 45 indicates printout of unit no., file no., and matrix storage info. for program debugging. 0 in col. 45 indicates suppression of this printout.
A.3	1-4, 5-8, 9-12, etc.	I4 I4 I4	- - -	- - -	This card is used to indicate which tile stress states are desired. User may specifically request up to 20 tile stress states (see Figure A.2 for tile numbering scheme). A zero in col. 4 indicates that stress states for all tiles are desired.

* If there are no tiles then $\bar{n}_x$ and $\bar{n}_y$, together with n_{B2} and n_{D2}, are still required since they determine the primary structure finite element grid. In analyzing panels without tiles, leave out cards B.4, C.3 through C.10 and all "F" cards.

B. GEOMETRIC CONFIGURATION – Sheet 1 of 2 (See Figure B-2)

CARD(S)	COL(S)	FORMAT	SYMBOLS	UNITS	DESCRIPTION
B.1	1-10	2E10.0	L_x	inches	Panel dimension
	11-20	↓	L_y	inches	Panel dimension
	21-30	↓	t_p	inches	Panel thickness
B.2	1-10	8E10.0	Y_1	inches	Position of first stringer centroid. If there are no stringers, set $Y_1 > L_y$ and skip to next card.
	11-20	↓	Z_s	inches	Distance of stringer centroid below plate middle surface
	21-30	↓	Y_s	inches	Discrete stiffener spacing
	31-40	↓	A_s	in.^{2}	Stringer cross sectional area
	41-50	↓	$I_{y'}$	in.^{4}	Stiffener principal mom. of inertia about y' axis
	51-60	↓	$I_{z'}$	in.^{4}	Stiffener principal mom. of inertia about z' axis
	61-70	↓	$J_{x'}$	in.^{4}	Stiffener twisting stiffness geometric parameter
	71-80	↓	β_s	Degrees	Angle between z and z' axis measured positive clockwise along x
B.3	1-10	I10	$\bar{n}_x$	-	Integer number of tiles between x = 0 and L_x*
	11-20	I10	$\bar{n}_y$	-	Integer number of tiles between y = 0 and L_y*

* If there are no tiles then $\bar{n}_x$ and $\bar{n}_y$, together with n_{B2} and n_{D2}, are still required since they determine the primary structure finite element grid. In analyzing panels without tiles, leave out cards B.4, C.3 through C.10 and all "F" cards.



Figure B-2 TPS Configuration on Stiffened Primary Structure

B. GEOMETRIC CONFIGURATION — Sheet 2 of 2 (See Figure B-3)

CARD(S)	COL(S)	FORMAT	SYMBOLS	UNITS	DESCRIPTION
B.4	1-10	6E10.0	T	inches	Undercut RSI tile thickness. Leave blank if tile is brick shaped or if there are no tiles.
	11-20	↓	B_1	inches	Tile undercut dimension. Leave blank if tile is brick shaped.
	21-30	↓	T_2	inches	Tile undercut dimension or, height of brick shaped tile.
	31-40	↓	t_A	inches	Strain arrestor plate (SAP) thickness. May replace with layer of isolator, RSI or bond material if no SAP.
	41-50	↓	t_I	inches	Strain isolator thickness (SIP)
	51-60	↓	t_c	inches	Coating thickness. Leave blank if no tile coating.
B.5	1-5	I5	n_{B_1}	-	Number of elements along B_1. Leave blank if tile is brick shaped or if there are no tiles.
	6-10	↓	n_{B_2}	-	Number of elements along B_2.
	11-15	↓	n_{D_2}	-	Number of elements along D_2.
	16-20	↓	n_{T_1}	-	Number of elements along $T\text{-}T_2$. Leave blank if tile is brick shaped.
	21-25	↓	n_{T_2}	-	Number of elements along T_2.



NOTE: SUBSCRIPTED SYMBOLS BEGINNING WITH "n" ARE THE NUMBER OF ELEMENTS WHICH SUBDIVIDE THE INDICATED SPAN. THE OTHER SYMBOLS ARE DIMENSIONS.

Figure B-3 RSI Tile Parameters

C. MATERIAL PROPERTIES — Sheet 1 of 2 (See Figure B-4)

CARD(S)	COL(S)	FORMAT	SYMBOLS	UNITS	DESCRIPTION
C.1	1-10	4E10.0	E_p	psi	Isotropic plate modulus of elasticity
	11-20	↓	ν_p	-	Poisson's ratio for plate
	21-30	↓	γ_p	lb/in^3	Weight density for plate
	31-40	↓	α_p	$°F^{-1}$	Coefficient of thermal expansion for plate
C.2	1-10	4E10.0	E_s	psi	Stringer modulus of elasticity (enter zero if no stringers)
	11-20	↓	ν_s	-	Poisson's ratio for stringer
	21-30	↓	γ_s	lb/in^3	Weight density for stringer
	31-40	↓	α_s	$°F^{-1}$	Coefficient of thermal expansion for stringer
C.3	1-10	6E10.0	E_x	psi	Arrestor x direction orthotropic stiffness
	11-20	↓	E_y	psi	Arrestor y direction orthotropic stiffness
	21-30	↓	E_z	psi	Arrestor z direction orthotropic stiffness
	31-40	↓	ν_{xy}	-	See Figure A.4
	41-50	↓	ν_{yz}	-	See Figure A.4
	51-60	↓	ν_{zx}	-	See Figure A.4
C.4	1-10	7E10.0	G_{xy}	psi	See Figure A.4
	11-20	↓	G_{yz}	psi	See Figure A.4
	21-30	↓	G_{zx}	psi	See Figure A.4
	31-40	↓	γ_A	lb/in^3	Weight density for arrestor
	41-50	↓	α_{AX}	$°F^{-1}$	X coefficient of thermal expansion for arrestor
	51-60	↓	α_{AY}	$°F^{-1}$	Y coefficient of thermal expansion for arrestor
	61-70	↓	α_{AZ}	$°F^{-1}$	Z coefficient of thermal expansion for arrestor

$$\begin{Bmatrix} \epsilon_x \\ \epsilon_y \\ \epsilon_z \\ \gamma_{xy} \\ \gamma_{yz} \\ \gamma_{zx} \end{Bmatrix} = \left[\begin{array}{ccc:ccc} \frac{1}{E_x} & -\frac{\nu_{xy}}{E_y} & -\frac{\nu_{xz}}{E_z} & & & \\ -\frac{\nu_{yx}}{E_x} & \frac{1}{E_y} & -\frac{\nu_{yz}}{E_z} & & \text{NULL} & \\ -\frac{\nu_{zx}}{E_x} & -\frac{\nu_{zy}}{E_y} & \frac{1}{E_z} & & & \\ \hdashline & & & \frac{1}{G_{xy}} & 0 & 0 \\ & \text{NULL} & & 0 & \frac{1}{G_{yz}} & 0 \\ & & & 0 & 0 & \frac{1}{G_{zx}} \end{array}\right] \begin{Bmatrix} \sigma_x \\ \sigma_y \\ \sigma_z \\ \sigma_{xy} \\ \sigma_{yz} \\ \sigma_{zx} \end{Bmatrix}$$

NOTE: This matrix is symmetric; thus, the program insures that

$$\frac{\nu_{xy}}{E_y} = \frac{\nu_{yx}}{E_x}$$

$$\frac{\nu_{xz}}{E_z} = \frac{\nu_{zx}}{E_x}$$

$$\frac{\nu_{zy}}{E_y} = \frac{\nu_{yz}}{E_z}$$

Figure B-4 Orthotropic Stress-Strain Law for 3-Dimensional Elements

C. MATERIAL PROPERTIES — Sheet 2 of 2

CARD(S)	COL(S)	FORMAT	SYMBOLS		UNITS
C.5	1-10	4E10.0	E_I	psi	Isolator modulus of elasticity
	11-20		ν_I	-	Poisson's ratio for isolator (Note:max ν_I=.499)
	21-30		γ_I	lb/in^3	Weight density for isolator
	31-40		α_I	$^oF^{-1}$	Coefficient of thermal expansion for isolator
C.6	1-10	E10.0	γ_R	lb/in^3	Weight density of RSI material
	11-20	E10.0	α_y/α_x	-	RSI coefficient of thermal expansion in y direction ($^oF^{-1}$) divided by coefficient of thermal expansion in x direction (α_x)
	21-30	E10.0	α_z/α_x	-	RSI coeffient of thermal expansion ratio in z vs. x direction

C. TEMPERATURE DEPENDENT MATERIAL PROPERTIES, Sheet 1 of 2

CARD(S)	COL(S)	FORMAT	SYMBOLS	UNITS	DESCRIPTION
C.7.1	1-5	I5	-	-	Number of entry sets in the following table of E_R vs. temperature (^oF)
C.8.1	1-10	E10.0	T_1	^oF	Temperature (absolute, not relative) corresponding to following value of E_R
	11-20	E10.0	$E_R(T_1)$	psi	Value of E_R (RSI modulus - refer to equations below*) associated with previous temp.
	31-30 etc.	E10.0 etc.	T_2 etc.	^oF etc.	Repeat above set of data as often as necessary, 4 sets to a card.
					Program uses closest 3 data pts. for 2nd order Langrangian interpolation of properties if element temp. is within data specified temp. range and at least 3 data-points are input. Program uses closest data-point properties for element temp. outside range. Uniform property value is used for any given property if only one value of that property is specified. Thus, program requires a minimum of 1 or 3 value(s) per property for proper execution.

C. TEMPERATURE DEPENDENT MATERIAL PROPERTIES – Sheet 2 of 2

CARD(S)	COL(S)	FORMAT	SYMBOLS	UNITS	DESCRIPTION
C.7.2 & C.8.2					Repeat above two card sets for E'_R *
C.7.3 & C.8.3 through C.7.6 & C.8.6					Repeat above card sets for remaining RSI properties in following order: G'_R, ν_R, ν'_R* and α_x* where α_x = RSI coefficient of thermal expansion in x direction.
C.9.1 & C.10.1 through C.9.3 & C.10.3					Repeat above card sets for coating properties in following order: E_c, ν_c, α_c

* For RSI
(refer to Figure B-4)

$$E_x = E_y = E_R \qquad G_{xy} = G_{yx} = \frac{E_R}{2(1+\nu_R)}$$

$$E_z = E'_R \qquad G_{yz} = G_{zy} = G_{zx} = G_{xz} = G'_R$$

$$\nu_{xy} = \nu_{yx} = \nu_R \qquad \nu_{xz} = \nu_{yz} = \nu'_R$$

$$\nu_{zx} = \nu_{zy} = \frac{E_R}{E'_R}\ \nu'_R$$

D. BOUNDARY CONDITIONS – Sheet 2 of 3 (See Figure B-5)

CARD(S)	COL(S)	FORMAT	SYMBOLS	UNITS	DESCRIPTION
D.1–D-4, (continued)	31	A1	-	-	0 denotes edge is not held from in-plane deflections 1 denotes edge is held from in-plane deflections 2 denotes edge is not held for y deflection, but is held for x deflection (PARTIALLY HELD) 4 denotes edge is not held for x deflection, but is held for y deflection (PARTIALLY HELD) 3 denotes edge is flexibly held for in-plane deflections NOTE: For non-vibratory heated or cooled primary structure problems, refer to special instructions on bottom of page
	32-40	E9.0	K_{uu}	lb/in^2	In-plane x force per unit length on an edge caused by in-plane x direction unit deflection
	41-49	↓	K_{uv} or K_{vu}	lb/in^2	In-plane x force per unit length on an edge caused by in-plane y direction unit deflection or In-plane y force per unit length on an edge caused by in-plane x direction unit deflection
	50-58	↓	K_{vv}	lb/in^2	In-plane y force per unit length on an edge caused by in-plane y direction unit deflection



Figure B-5 Primary Stucture Boundary Condition Notation

D. BOUNDARY CONDITIONS – Sheet 1 of 3 (See Figure B-5)

CARD(S)	COL(S)	FORMAT	SYMBOLS	UNITS	DESCRIPTION
D.1, D.2, D.3, D.4	1	A1	-	-	A denotes the x=0 edge of the plate (CARD D.1) B denotes the $x=L_x$ edge of the plate (CARD D.2) C denotes the y=0 edge of the plate (CARD D.3) D denotes the $y=L_y$ edge of the plate (CARD D.4)
These are four similar boundary condition cards	2	A1	-	-	0 indicates that the plate edge is free to deflect and rotate out of the z=0 plane (FREE) 1 indicates that the plate edge is not free to deflect or rotate out of the z=0 plane (CLAMPED) 2 indicates that the plate edge is not free to deflect but is free to rotate out of the z=0 plane (PINNED) 3 indicates that the plate edge is flexibly held with regard to out of plane motion
	3-11	E9.0 ↓	K_{ww}	lb/in^2	Out-of-plane force per unit edge-length caused by out-of-plane unit deflection
	12-20		$K_{w\theta}$ or $K_{\theta w}$	lb/in	Out-of-plane force per unit edge-length caused by out-of plane unit rotation or Out-of-plane moment per unit edge-length caused by out-of-plane unit deflection
	21-29		$K_{\theta\theta}$	lb.	Out-of-plane moment per unit edge-length caused by out-of plane unit rotation

D. BOUNDARY CONDITIONS – Sheet 1 of 3 (See Figure B-5)

CARD(S)	COL(S)	FORMAT	SYMBOLS	UNITS	DESCRIPTION
Add'l info. for cards D1 and D2 only.	60	A1		-	0 denotes stringer edge not held for in-plane rotation (θ_z) 1 denotes stringer edge held for in-plane rotation ($\theta_z = 0$) 3 denotes stringer edge flexibly held for in-plane rotation Note θ_z is not a primary structure degree of freedom unless a stringer element is also present at a particular plate node
	61-69	E9.0	$K_{s\theta_z}$	in-lb.	In-plane stringer edge moment produced by unit rotation θ_z
	71	A1	-	-	0 denotes stringer edge free to twist (θ_x) 1 denotes stringer edge not free to twist ($\theta_x = 0$) 3 denotes stringer edge flexibly held against twist
	72-80	E9.0	$K_{s\theta_x}$	in-lb.	Twist moment on end of stringer for a unit twist-rotation

Special Instructions for running a thermal stress problem when the primary structure is at a uniform temperature other than the reference temperature are required to permit free in-plane thermal straining; e.g.:

1. Permit the x=0 boundary to move freely or be elastically held in-plane
2. Permit the $x=L_x$ boundary to move freely in the y direction but not the x direction if free, or be elastically held if elastically held along x=0.
3. Permit the y=0 boundary to move freely or be elastically held in-plane.
4. Permit the $y=L_y$ boundary to move freely in the x direction but not the y direction if free, or be elastically held if elastically held along y=0.

See pages B-53 and B-57 for a typical example of the above instructions.

E. PRIMARY STRUCTURE LOADING (See Figure B-6)

CARD(S)	COL(S)	FORMAT	SYMBOLS	UNITS	DESCRIPTION
E.1	1-10	E10.0	N_x	lb/in	Uniform, direct cover-plate running load in x direction on x = 0 edge (see Figure 7)
	11-20	↓	N_y	lb/in	Uniform, direct cover-plate running load in y direction on y = 0 edge (see Figure 7)
	21-30	↓	N_{xy}	lb/in	Uniform, shearing cover-plate running load on x = 0 edge (see Figure 7)
	31-40	↓	N_{yx}	lb/in	Uniform, shearing cover-plate running load on y = 0 edge (see Figure 7)
	41-50	↓	P_z	psi	Uniform external normal pressure acting upon tiles
	51-60	↓	T	lb	Tension force acting upon centroid of each stiffener at x = 0
	61-70	↓	M	in-lb	Out-of-plane bending moment acting upon each stiffener
	71-80	↓	V	lb	Shear load acting upon each stiffener
					Note, boundary conditions for B and D edges should be selected carefully to produce desired effect, e.g. to produce a uniform primary structure tension in the x direction, $\sigma_x = \bar{\sigma}$ and $\sigma_y = 0$: set $N_x = t_p \bar{\sigma}$, $T = A_s \bar{\sigma}$, and P_z, M and V all equal to zero; then hold plate edge B from in plane x, but not y, motion and also hold the stringers at edge B; next, make edges C and D free for X motion, and only hold one of these edges against y motion.
E.2	1-10	E10.0	ΔT_p	F^o	Temperature difference of plate from T_{Ref}.
	11-20	E10.0	ΔT_s	F^o	Temperature difference of stringers from T_{Ref}.

Note: Leave out cards E.1 and E.2 if vibration option is used



Figure B-6 Possible Static Mechanical Loadings Upon Panel

F. TILE TEMPERATURE DISTRIBUTIONS — Sheet 1 of 2

Each tile is assumed to have the same temperature distribution. There are 3 temperature distribution options, each of which is considered separately below. Tile temperature differences, rather than absolute tile temperatures, are required for each of these options (since thermal strains depend upon temperature differences). However, since temperature-dependent material property data are presented in terms of absolute temperature scales, a reference temperature (which is also input) is added to the differences to obtain absolute temperatures for internally computing material properties.

CARD(S)	COL(S)	FORMAT	SYMBOLS	UNITS	DESCRIPTION
F.1	5	I1	-	-	0 in col.5 of this card indicates no thermal static loading effects will be considered. But material properties used in forming the TPS stiffness properties will be based upon the specified temperature distribution. 1 in col. 5 indicates that thermal static loading will be considered in the analysis. In such cases, refer to bottom of following page for special instructions regarding boundary condition cards (D.1 through D.4).
	10	I1	-	-	1 in col. 10 indicates that each tile is at the same uniform temperature.
					2 in col. 5 indicates that each tile temperature distribution is governed by Lagrangian interpolation formulas.
					3 in col. 5 indicates that each tile temperature distribution is input by consecutive finite element node-temperature differences from the reference temperature.
	11-20	E10.0	T_{Ref}	^oF	Panel reference temperature (added to temp. differences when obtaining mat'l. properties)

F. TILE TEMPERATURE DISTRIBUTIONS – Sheet 2 of 2

CARD(S)	COL(S)	FORMAT	SYMBOLS	UNITS	DESCRIPTION
					UNIFORM TEMPERATURE OPTION (1)
F.2	1-10	E10-1	ΔT_u	F°	Uniform temperature difference from T_{Ref}
					or LAGRANGIAN INTERPOLATION TEMPERATURE OPTION (2)
F.2.1	1-5	2I5	-	-	Number of x coordinates through which temperature differences will be interpolated.
	6-10		-	-	Order of Lagrangian interpolation polynominal in x direction. Must be at lease 1 less than number of coords given in col. 5.
F.3.1	1-10	E10.0	x_i	inches	The local x coordinates used in the x direction temperature difference interpolation. Eight to a card until all are accounted for.
F.2.2– 3.2					Repeat card types F.2.1 and F.3.1 for the y coordinates
F.2.3– 3.3					Repeat card types F.2.1 and F.3.1 for the z coordinates
					or ELEMENT NODE TEMPERATURE OPTION (3)
F.2	1-10 11-20 etc.	E10.0	ΔT_R	F°	Temperature differences above reference temperatures, node by node, in consecutive order. Seven temperature differences to a card until all nodes are accounted for. Cols. 71-80 of each card are reserved for user's card identification.

D. DESCRIPTION OF OUTPUT

Output from a typical run of the RESIST computer program is explained below in outline form. References in parentheses refer to pages in this Appendix.

1. Program title and date indicating latest update of program version which was run.

INPUT INFORMATION

2. Listing of input cards, the first two of which are the title assigned to any given run by the user.

3. User selected input options are listed.

4. Plate, stringer and tile geometry and specification of finite element grids for primary structure and tiles (pp. B.8 - B.11).

5. Plate, stringer, strain isolator and arrestor material properties (p. B.12). Note, if there is no strain arrestor, RSI or isolator material properties may be used for the arrestor. If this is done, the thickness dimension of the usual isolator or RSI should be appropriately reduced to compensate for this addition.

6. Temperature-dependent RSI material property data used for generating curves used internally by program to compute RSI average finite element properties.

7. Plate and stringer boundary conditions (pp. B.16-B.21).

8. Applied primary structure static mechanical and thermal loading if not a vibration problem.

9. RSI temperature distribution input data. Used for property data (item 6 above) and thermal loading if a statics problem.

OUTPUT INFORMATION

10. Map showing typical tiles three dimensional finite element ordering, by layers. Top, or first layer also corresponds to two-dimensional tile coating elements as well.

11. Map showing ordering of a typical tiles finite element nodes by layers.

12. Position and temperatures for a typical tile in a local coordinate system (reference Figures 3.a &.b).

13. Global geometry of primary structure nodes and plate nodal degree-of-freedom numbering . D_x, D_y and D_z refer to nodal deflections, and R_x, R_y and R_z are the nodal rotations. Nodes with no degrees-of-freedom are used to define the stringer centroids and axes.

14.a. Statics Option: Primary structure nodal deflections by iteration number. Nodes with the same x coordinate are grouped together. These groups are separated with dashed lines.

14.b. Vibration Option: Mode numbers, approximate frequencies and corresponding modal error bound (which should be less than 2% to be a reliable approximate mode). This is followed by the primary structure mode shapes with a similar nodal deflection format as for the Statics Option.

15. If requested by the user, the computed convergence parameter is printed out along with the input quantity it was tested against. This is done for each iteration after the first for the Static Option. The primary structure degree-of-freedom with the largest change from the previous iteration is also identified.

16. Tile nodal displacements by tile and iteration number. For a vibration option, this calculation and the subsequent ones are performed only for the user-specified vibration mode.

17. Three dimensional tile stresses and strains for the bottom two layers of elements by element number. These quantities are computed at each element's 8 Gauss integration points. Gauss point stresses are believed to be more accurate than nodal values and provide more detail than simply the element's average stresses.

18. Three dimensional element average stresses and strains (by tile and iteration number).

19. Two-dimensional element average coating stresses. Coating element numbers correspond to three dimensional element numbering directly below them.

20.a. Statics Option: Repeat of items 16-19 for each tile. Repeat of item 14.a and 15 for each iteration.

20.b. Vibrations Option: Computation of Rayleigh Quotient (OMEGA SQUARED) if all tiles have been treated. Repeat of items 16-19 for each iteration. Repeat of items 14.b, 15 and Rayleigh Quotient until convergence or last iteration is performed.

21. Plate element stresses and strains for mid and/or top and/or bottom surfaces. This computation is done after each iteration if requested by the user. Otherwise, it is computed only after convergence or the last iteration is performed.

E. SAMPLE PROBLEMS

Output for three sample problems, one vibration case and two statics cases, are presented in the remaining pages of this report. Only portions of the output for each problem are shown. However, the pages presented are representative of the types of information, and their respective formats, which the RESIST Program can deliver.

S T A T I C   A N D   D Y N A M I C

```
        REUSABLE                      SURFACE          INSULATION            STRESSES

RRRRRRRRR       EEEEEEEEEEE          SSSSSSSSS        IIIIIIIII         SSSSSSSSS   TTTTTTTTTTTT
RRRRRRRRRRR     EEEEEEEEEEE         SSSSSSSSSS        IIIIIIIII        SSSSSSSSSS   TTTTTTTTTTTT
RRR     RRRR    EEE                SSSSS                 III          SSSSS              TTT
RRR       RRR   EEE                SSSS                  III          SSSS               TTT
RRR     RRRR    EEE                 SSSSS                III           SSSSS             TTT
RRRRRRRRRRR     EEEEEEEE     **      SSSSS      **       III     **     SSSSS            TTT
RRRRRRRRRR      EEEEEEEE     **        SSSSS    **       III     **       SSSSS          TTT
RRR   RRR       EEE                     SSSSS            III               SSSSS         TTT
RRR    RRR      EEE                       SSSS           III                SSSS         TTT
RRR     RRR     EEE                      SSSSS           III               SSSSS         TTT
RRR       RRR   EEEEEEEEEEE        SSSSSSSSSS         IIIIIIIII       SSSSSSSSSS         TTT
RRR        RRR  EEEEEEEEEEE        SSSSSSSSS          IIIIIIIII       SSSSSSSSS          TTT

GGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGG
GGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGG
                                      GGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGG
                                        GGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGG
                                         GGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGG
                                          GGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGG
                                            GGGGGGGGGGGGGGGGGGGGGGGGGGGGGGGG
                                           GGGGGGGGGGGGGGGGGGGGGGGGGGGGG
                                         GGGGGGGGGGGGGGGGGGGGGGGGGGG
                                       GGGGGGGGGGGGGGGGGGGGGGGGGGG
                                      GGGGGGGGGGGGGGGGGGGGGGGGG
                                      GGGGGGGGGGGGGGGGGGGGGGG
                                      GGGGGGGGGGGGGGGGGGGGG
                                      GGGGGGGGGGGGGGGGGGG
                                      GGGGGGGGGGGGGGGG
                                      GGGGGGGGGGGG
                                      GGGGGGGGGG
                                      GGGGGGG
                                      GGGGG
                                      GG
```

VERSION DATE

AUGUST 31, 1974

PREPARED BY

I. OJALVO, P. OGILVIE, A. LEVY AND F. AUSTIN

OF GRUMMAN AEROSPACE CORPORATION

FOR

THE LANGLEY RESEARCH CENTER

PROGRAM LISTING OF INPUT DATA CARDS

```
.........1.........2.........3.........4.........5.........6.........7.........8
12345678901234567890123456789012345678901234567890123456789012345678901234567890

SAMPLE PROBLEM I  -  VIBRATION OF THREE (3) SIMPLE TILES
    AUGUST 21, 1974
    2    5         2    1    4      .05          7        0.0
    1    2    1    1    1    1    0    0    0
   0.
       18.    .33333       .75
       1.0
         3         1
                      1.16667    .16667       .05
        10    1         7
     10.E6        .3       .01
         0
     60.E3     60.E3      6.E3        .5        .1       .01
     20.E3     32.E3     32.E3      .005
       90.       .49      .035
      .005
    1
       70.     60.E3
    1
       70.      6.E3
    1
       70.     32.E3
    1
       70.        .5
    1
       70.       .01
    1
       70.        0.
    1
       70.        0.
    1
       70.        0.
    1
       70.        0.
A2                           2
B2                           2
C2                           0
D2                           4
         1       70.
        0.

.........1.........2.........3.........4.........5.........6.........7.........8
12345678901234567890123456789012345678901234567890123456789012345678901234567890
```

O P T I O N S

FREE VIBRATION MODES NO. DESIRED MODES = 5 NO. REORTHOGONALIZATIONS = 2 MODE NO. = 1

MAXIMUM NO. ITERATIONS = 4 CONVERGENCE PARAMETER = 5.0000E-02

OVERHUNG ROTATORY MASS INERTIA ASSOCIATED WITH EACH STRINGER = 0.0

PRIMARY STRUCTURE STRESSES PRESENTED AFTER LAST ITERATION AT PLATE MID, TOP AND BOTTOM SURFACES

TILES ON PRIMARY STRUCTURE

TILE STRESSES PRESENTED AFTER EACH ITERATION

TILE NODE MAP REQUIRED

TILE ELEMENT MAP REQUIRED

TILE NODE COORDINATES REQUIRED

DO NOT PRINT ELEMENT STIFFNESS MATRICES

DO NOT PRINT ASSEMBLED STIFFNESS MATRICES

DO NOT PRINT TILE DEBUGGING INFORMATION

COMPUTE STRESSES FOR ALL TILES

GEOMETRY

PLATE	LX = 1.80000E 01	LY = 3.33330E-01	TP = 7.50000E-01	
STRINGERS	Y1 = 1.00000E 00	ZS = 0.0	YS = 0.0	AS = 0.0
	IY' = 0.0	IZ' = 0.0	JX' = 0.0	BETA S = 0.0
TILES	NXP = 3	NYB = 1		
	T = 0.0	B1 = 0.0	T2 = 1.16667E 00	
	TA = 1.66670E-01	TI = 5.00000E-02	TC = 0.0	
BRICK	NB1 = 0	NB2 = 10	ND2 = 1	
	NT1 = 0	NT2 = 7		

MATERIAL PROPERTIES

PLATE	EP = 1.00000E 07	NU P = 3.00000E-01	GAMMA P = 1.00000E-02	ALPHA P = 0.0
STRINGERS	ES = 0.0	NU S = 0.0	GAMMA S = 0.0	ALPHA P = 0.0
ARRESTOR OR RSI	EX = 6.00000E 04	EY = 6.00000E 04	EZ = 6.00000E 03	
	NU XY = 5.00000E-01	NU YZ = 1.00000E-01	NU ZX = 1.00000E-02	
	GXY = 2.00000E 04	GYZ = 3.20000E 04	GZX = 3.20000E 04	
	GAMMA A = 5.00000E-03			
	ALPHA X = 0.0	ALPHA Y = 0.0	ALPHA Z = 0.0	
ISOLATOR	EI = 9.00000E 01	NU I = 4.90000E-01	GAMMA I = 3.50000E-02	ALPHA I = 0.0
RSI	GAMMA R = 5.00000E-03			
		ALPHA RY / ALPHA RX = 0.0		ALPHA RZ / ALPHA RX = 0.0

TEMPERATURE DEPENDENT MATERIAL PROPERTIES

		TEMPERATURE	PROPERTY	TEMPERATURE	PROPERTY	TEMPERATURE	PROPERTY	TEMPERATURE	PROPERTY
1	ER	ALL	6.000E 04						
1	ER'	ALL	6.000E 03						
1	GR'	ALL	3.200E 04						
1	NU R	ALL	5.000E-01						
1	NU R'	ALL	1.000E-02						
1	ALPHA R	ALL	0.0						
1	EC	ALL	0.0						
1	NU C	ALL	0.0						
1	ALPHA C	ALL	0.0						

BOUNDARY CONDITIONS

EDGE	PLATE OUT OF PLANE	PLATE IN PLANE	STRINGERS	
A	PINNED	FREE	FREE	FREE
B	PINNED	U HELD, V FREE	FREE	FREE
C	FREE	FREE		
D	FREE	V HELD, U FREE		

R S I   T E M P E R A T U R E S

NO STATIC THERMAL LOADING

UNIFORM TEMPERATURE OPTION

T REFERENCE = 7.0000E 01

DEL T U = T - T REF = 0.0

N O D E   M A P

SURFACE 1

200	202	204	206	208	210	212	214	216	218	220
199	201	203	205	207	209	211	213	215	217	219

N O D E   M A P

SURFACE 2

178	180	182	184	186	188	190	192	194	196	198
177	179	181	183	185	187	189	191	193	195	197

E L E M E N T   M A P

LAYER 1
RSI

81 82 83 84 85 86 87 88 89 90


ELEMENT MAP
LAYER 9
ISOLATOR
1 2 3 4 5 6 7 8 9 10

TILE MESH ELEMENT	TILE NODES			
1	1	2	24	23
	3	4	26	25
2	3	4	26	25
	5	6	28	27
3	5	6	28	27
	7	8	30	29
4	7	8	30	29
	9	10	32	31
5	9	10	32	31
	11	12	34	33
6	11	12	34	33
	13	14	36	35
7	13	14	36	35
	15	16	38	37
8	15	16	38	37
	17	18	40	39
9	17	18	40	39
	19	20	42	41
10	19	20	42	41
	21	22	44	43
11	23	24	46	45
	25	26	48	47
12	25	26	48	47
	27	28	50	49
13	27	28	50	49
	29	30	52	51
14	29	30	52	51
	31	32	54	53
15	31	32	54	53
	33	34	56	55
16	33	34	56	55
	35	36	58	57
17	35	36	58	57
	37	38	60	59
18	37	39	60	59
	39	40	62	61
19	39	40	62	61
	41	42	64	63

NODE	LOCAL TILE COORDINATES X	Y	Z	TEMPERATURE
1	0.0	0.0	0.0	0.0
2	0.0	3.33330E-01	0.0	0.0
3	6.00000E-01	0.0	0.0	0.0
4	6.00000E-01	3.33330E-01	0.0	0.0
5	1.20000E 00	0.0	0.0	0.0
6	1.20000E 00	3.33330E-01	0.0	0.0
7	1.80000E 00	0.0	0.0	0.0
8	1.80000E 00	3.33330E-01	0.0	0.0
9	2.40000E 00	0.0	0.0	0.0
10	2.40000E 00	3.33330E-01	0.0	0.0
11	3.00000E 00	0.0	0.0	0.0
12	3.00000E 00	3.33330E-01	0.0	0.0
13	3.60000E 00	0.0	0.0	0.0
14	3.60000E 00	3.33330E-01	0.0	0.0
15	4.20000E 00	0.0	0.0	0.0
16	4.20000E 00	3.33330E-01	0.0	0.0
17	4.80000E 00	0.0	0.0	0.0
18	4.80000E 00	3.33330E-01	0.0	0.0
19	5.40000E 00	0.0	0.0	0.0
20	5.40000E 00	3.33330E-01	0.0	0.0
21	6.00000E 00	0.0	0.0	0.0
22	6.00000E 00	3.33330E-01	0.0	0.0
23	0.0	0.0	5.00000E-02	0.0
24	0.0	3.33330E-01	5.00000E-02	0.0
25	6.00000E-01	0.0	5.00000E-02	0.0
26	6.00000E-01	3.33330E-01	5.00000E-02	0.0
27	1.20000E 00	0.0	5.00000E-02	0.0
28	1.20000E 00	3.33330E-01	5.00000E-02	0.0
29	1.80000E 00	0.0	5.00000E-02	0.0
30	1.80000E 00	3.33330E-01	5.00000E-02	0.0
31	2.40000E 00	0.0	5.00000E-02	0.0
32	2.40000E 00	3.33330E-01	5.00000E-02	0.0
33	3.00000E 00	0.0	5.00000E-02	0.0
34	3.00000E 00	3.33330E-01	5.00000E-02	0.0
35	3.60000E 00	0.0	5.00000E-02	0.0
36	3.60000E 00	3.33330E-01	5.00000E-02	0.0
37	4.20000E 00	0.0	5.00000E-02	0.0
38	4.20000E 00	3.33330E-01	5.00000E-02	0.0
39	4.80000E 00	0.0	5.00000E-02	0.0
40	4.80000E 00	3.33330E-01	5.00000E-02	0.0
41	5.40000E 00	0.0	5.00000E-02	0.0
42	5.40000E 00	3.33330E-01	5.00000E-02	0.0
43	6.00000E 00	0.0	5.00000E-02	0.0
44	6.00000E 00	3.33330E-01	5.00000E-02	0.0
45	0.0	0.0	2.16670E-01	0.0
46	0.0	3.33330E-01	2.16670E-01	0.0
47	6.00000E-01	0.0	2.16670E-01	0.0
48	6.00000E-01	3.33330E-01	2.16670E-01	0.0
49	1.20000E 00	0.0	2.16670E-01	0.0
50	1.20000E 00	3.33330E-01	2.16670E-01	0.0

	PRIMARY STRUCTURE GLOBAL GEOMETRY			DEGREES OF FREEDOM					
NODE	X	Y	Z	DX	DY	DZ	RX	RY	RZ
1	0.0	0.0	0.0	1	2	0	3	4	0
2	0.0	3.333300E-01	0.0	5	0	0	6	7	0
3	6.000000E-01	0.0	0.0	8	9	10	11	12	0
4	6.000000E-01	3.333300E-01	0.0	13	0	14	15	16	0
5	1.200000E 00	0.0	0.0	17	18	19	20	21	0
6	1.200000E 00	3.333300E-01	0.0	22	0	23	24	25	0
7	1.799999E 00	0.0	0.0	26	27	28	29	30	0
8	1.799999E 00	3.333300E-01	0.0	31	0	32	33	34	0
9	2.400000E 00	0.0	0.0	35	36	37	38	39	0
10	2.400000E 00	3.333300E-01	0.0	40	0	41	42	43	0
11	2.999999E 00	0.0	0.0	44	45	46	47	48	0
12	2.999999E 00	3.333300E-01	0.0	49	0	50	51	52	0
13	3.599999E 00	0.0	0.0	53	54	55	56	57	0
14	3.599999E 00	3.333300E-01	0.0	58	0	59	60	61	0
15	4.199999E 00	0.0	0.0	62	63	64	65	66	0
16	4.199999E 00	3.333300E-01	0.0	67	0	68	69	70	0
17	4.799999E 00	0.0	0.0	71	72	73	74	75	0
18	4.799999E 00	3.333300E-01	0.0	76	0	77	78	79	0
19	5.400000E 00	0.0	0.0	80	81	82	83	84	0
20	5.400000E 00	3.333300E-01	0.0	85	0	86	87	88	0
21	5.999999E 00	0.0	0.0	89	90	91	92	93	0
22	5.999999E 00	3.333300E-01	0.0	94	0	95	96	97	0
23	6.599999E 00	0.0	0.0	98	99	100	101	102	0
24	6.599999E 00	3.333300E-01	0.0	103	0	104	105	106	0
25	7.199999E 00	0.0	0.0	107	108	109	110	111	0
26	7.199999E 00	3.333300E-01	0.0	112	0	113	114	115	0
27	7.799999E 00	0.0	0.0	116	117	118	119	120	0
28	7.799999E 00	3.333300E-01	0.0	121	0	122	123	124	0
29	8.399999E 00	0.0	0.0	125	126	127	128	129	0
30	8.399999E 00	3.333300E-01	0.0	130	0	131	132	133	0
31	8.999999E 00	0.0	0.0	134	135	136	137	138	0
32	8.999999E 00	3.333300E-01	0.0	139	0	140	141	142	0
33	9.599999E 00	0.0	0.0	143	144	145	146	147	0
34	9.599999E 00	3.333300E-01	0.0	148	0	149	150	151	0
35	1.020000E 01	0.0	0.0	152	153	154	155	156	0
36	1.020000E 01	3.333300E-01	0.0	157	0	158	159	160	0
37	1.080000E 01	0.0	0.0	161	162	163	164	165	0
38	1.080000E 01	3.333300E-01	0.0	166	0	167	168	169	0
39	1.140000E 01	0.0	0.0	170	171	172	173	174	0
40	1.140000E 01	3.333300E-01	0.0	175	0	176	177	178	0
41	1.200000E 01	0.0	0.0	179	180	181	182	183	0
42	1.200000E 01	3.333300E-01	0.0	184	0	185	186	187	0
43	1.260000E 01	0.0	0.0	188	189	190	191	192	0
44	1.260000E 01	3.333300E-01	0.0	193	0	194	195	196	0
45	1.320000E 01	0.0	0.0	197	198	199	200	201	0
46	1.320000E 01	3.333300E-01	0.0	202	0	203	204	205	0
47	1.380000E 01	0.0	0.0	206	207	208	209	210	0
48	1.380000E 01	3.333300E-01	0.0	211	0	212	213	214	0
49	1.440000E 01	0.0	0.0	215	216	217	218	219	0
50	1.440000E 01	3.333300E-01	0.0	220	0	221	222	223	0
51	1.500000E 01	0.0	0.0	224	225	226	227	228	0

ORDER OF UNREDUCED PROBLEM = 273
NUMBER OF DESIRED MODES = 5
NUMBER OF REORTHOGONALIZATIONS = 2

MODE NUMBER	FREQUENCY (RAD / SEC)	FREQUENCY (HERTZ)	FREQ. SQRD. ERROR BOUND (PERCENT)
1	3.204729E 03	5.100483E 02	7.609798E-14
2	1.096583E 04	1.745266E 03	2.610086E-13
3	2.262648E 04	3.601117E 03	4.191322E-06
4	2.400171E 04	3.819991E 03	9.051610E-06
5	3.946659E 04	6.281301E 03	1.497426E-01
6	4.502263E 04	7.165570E 03	9.145379E-02
7	6.271878E 04	9.982004E 03	4.056820E 00
8	7.672000E 04	1.221037E 04	7.066792E 01

PRIMARY STRUCTURE MODE SHAPE 1 ITERATION NO. 0

NODE	DX	DY	DZ	RX	RY	RZ
1	-2.372677E-07	4.973345E-08		1.429838E-06	-3.161962E-02	
2	-2.371768E-07			-1.400851E-06	-3.162404E-02	
3	-2.104755E-07	4.944270E-08	1.893834E-02	-2.142981E-05	-3.144493E-02	
4	-2.104363E-07		1.894102E-02	3.746948E-05	-3.144924E-02	
5	-1.839400E-07	4.864863E-08	3.766652E-02	-4.241391E-05	-3.092045E-02	
6	-1.838706E-07		3.767179E-02	7.399049E-05	-3.092459E-02	
7	-1.578119E-07	4.731215E-08	5.597616E-02	-6.385770E-05	-3.005014E-02	
8	-1.577289E-07		5.598381E-02	1.099205E-04	-3.005387E-02	
9	-1.323493E-07	4.545071E-08	7.366067E-02	-8.621626E-05	-2.883692E-02	
10	-1.322388E-07		7.367039E-02	1.444587E-04	-2.884041E-02	
11	-1.077374E-07	4.307981E-08	9.051722E-02	-1.059153E-04	-2.729557E-02	
12	-1.076069E-07		9.052908E-02	1.770441E-04	-2.729934E-02	
13	-8.423490E-08	4.024713E-08	1.063567E-01	-1.229580E-04	-2.545035E-02	
14	-8.406460E-08		1.063711E-01	2.091781E-04	-2.545403E-02	
15	-6.193574E-08	3.697092E-08	1.210015E-01	-1.404429E-04	-2.331475E-02	
16	-6.175992E-08		1.210180E-01	2.392771E-04	-2.331808E-02	
17	-4.107149E-08	3.328104E-08	1.342834E-01	-1.547958E-04	-2.091386E-02	
18	-4.085534E-08		1.343020E-01	2.659557E-04	-2.091752E-02	
19	-2.174171E-08	2.925146E-08	1.460547E-01	-1.638929E-04	-1.828836E-02	
20	-2.152723E-08		1.460758E-01	2.906900E-04	-1.829213E-02	
21	-4.124917E-09	2.494605E-08	1.561939E-01	-1.707078E-04	-1.548051E-02	
22	-3.875034E-09		1.562172E-01	3.108683E-04	-1.548352E-02	
23	1.178755E-08	2.042313E-08	1.646020E-01	-1.776280E-04	-1.252230E-02	
24	1.20?399E-08		1.646270E-01	3.271538E-04	-1.252472E-02	
25	[illegible]	1.570584E-08	1.711965E-01	-1.823899E-04	-9.440076E-03	
26	2.615315E-08		1.712228E-01	3.403833E-04	-9.441860E-03	
27	2.814896E-08	1.085576E-08	1.759129E-01	-1.862148E-04	-6.268606E-03	
28	3.?16126E-08		1.759400E-01	3.483910E-04	-6.269876E-03	
29	[illegible]	5.917776E-09	1.767075E-01	-1.877103E-04	-3.038223E-03	
30	4.873820E-08		1.787353E-01	3.546302E-04	-3.039023E-03	
31	5.697272E-08	9.227483E-10	1.795518E-01	-1.892887E-04	2.286215E-04	
32	5.724250E-08		1.795799E-01	3.578272E-04	2.281881E-04	

PRIMARY STRUCTURF NODES ASSOCIATED WITH TILE NO. 1

1	3	5	7	9	11	13	15	17	19	21
2	4	6	8	10	12	14	16	18	20	22

TPS DISPLACEMENTS FOR TILE NO. 1 AND ITERATION NO. 1

NODE	Y COMPONENT(U)	Y COMPONENT(V)	Z COMPONENT(W)
1	-1.1857588E-02	-4.8645558E-07	0.0
2	-1.1859249E-02	5.2531914E-07	0.0
3	-1.1792056E-02	8.0856189E-06	1.8938344E-02
4	-1.1793669E-02	-1.4051055E-05	1.8941015E-02
5	-1.1595350E-02	1.5953861E-05	3.7666518E-02
6	-1.1596903E-02	-2.7746428E-05	3.7671786E-02
7	-1.1268958E-02	2.3993940E-05	5.5976156E-02
8	-1.1270355E-02	-4.1220163E-05	5.5983808E-02
9	-1.0813974E-02	3.2376542E-05	7.3660672E-02
10	-1.0815281E-02	-5.4172007E-05	7.3670387E-02
11	-1.0235939E-02	3.9761304E-05	9.0517223E-02
12	-1.0237359E-02	-6.6391527E-05	9.0529084E-02
13	-9.5439628E-03	4.6149493E-05	1.0635674E-01
14	-9.5453411E-03	-7.8441793E-05	1.0637110E-01
15	-8.7430887E-03	5.2703050E-05	1.2100154E-01
16	-8.7443367E-03	-8.9728899E-05	1.2101799E-01
17	-7.8427382E-03	5.8081714E-05	1.3428342E-01
18	-7.8441054E-03	-9.9733385E-05	1.3430196E-01
19	-6.8581514E-03	6.1489074E-05	1.4605474E-01
20	-6.8595633E-03	-1.0900875E-04	1.4607584E-01
21	-5.8051944E-03	6.4040360E-05	1.5619385E-01
22	-5.8063194E-03	-1.1657560E-04	1.5621716E-01
23	1.4547564E-02	-6.3910964E-04	1.2398793E-03
24	1.4194820E-02	-8.7081082E-04	1.4891145E-03
25	1.4519908E-02	-5.0962073E-05	1.9550174E-02
26	1.4168963E-02	-1.9416506E-04	1.9783165E-02
27	1.4426317E-02	4.8901746E-04	3.8002007E-02
28	1.4112670E-02	4.4811238E-04	3.9206004E-02
29	1.4063966E-02	9.4013475E-04	5.6169845E-02
30	1.3832748E-02	1.0023813E-03	5.6362256E-02
31	1.3425775E-02	1.2302890E-03	7.3761225E-02
32	1.3346210E-02	1.3694626E-03	7.3977292E-02
33	1.2545496E-02	1.2185425E-03	9.0547383E-02
34	1.2709964E-02	1.4096978E-03	9.0835929E-02
35	1.1494334E-02	7.3654414E-04	1.0633683E-01
36	1.1997625E-02	9.4610523E-04	1.0675156E-01
37	1.0387622E-02	-3.6612875E-04	1.2097675E-01
38	1.1290297E-02	-1.8315547E-04	1.2157196E-01
39	9.3781725E-03	-2.1629541E-03	1.3437933E-01
40	1.0673009E-02	-2.0691841E-03	1.3517231E-01
41	8.6540468E-03	-4.5677647E-03	1.4652973E-01
42	1.0241371E-02	-4.6531880E-03	1.4751375E-01
43	8.3580683E-03	-7.3943338E-03	1.5772128E-01
44	1.0027479E-02	-7.7313706E-03	1.5879726E-01
45	9.5742457E-03	-8.5340976E-04	2.1167265E-03
46	9.2171617E-03	-9.4800652E-04	2.4439321E-03
47	9.5377430E-03	-2.2878307E-04	2.0108391E-02
48	9.1875307E-03	-2.8696839E-04	2.0416472E-02
49	9.4466731E-03	3.5078474E-04	3.8306460E-02
50	9.1335960E-03	3.4779799E-04	3.8583938E-02

STRESSES FOR ISOLATOR AND ARRESTOR FOR TILE NO. 1 AND ITERATION NO. 1

	LOCAL COORDINATES X	Y	Z	STRESSES XX	YY	ZZ	XY	YZ	ZX
			ELEMENT NUMBER	1					
1	4.7320E-01	2.6289E-01	3.9434E-02	2.6906E 01	2.6883E 01	2.8029E 01	8.8016E-04	-1.6162E-01	1.6666E 01
2	4.7320E-01	7.0441E-02	3.9434E-02	2.2899E 01	2.2876E 01	2.3860E 01	-1.0059E-03	-1.1118E-01	1.6789E 01
3	1.2679E-01	2.6289E-01	3.9434E-02	3.7726E 01	3.7696E 01	3.9298E 01	8.0522E-04	-3.9381E-01	1.6698E 01
4	1.2679E-01	7.0441E-02	3.9434E-02	3.3534E 01	3.3504E 01	3.4934E 01	-1.0808E-03	-3.2088E-01	1.6821E 01
5	4.7320E-01	2.6289E-01	1.0566E-02	2.7413E 01	2.7399E 01	2.8531E 01	-2.2875E-04	-1.7388E-01	1.6685E 01
6	4.7320E-01	7.0441E-02	1.0566E-02	2.3408E 01	2.3395E 01	2.4363E 01	-2.4156E-04	-1.2343E-01	1.6807E 01
7	1.2679E-01	2.6289E-01	1.0566E-02	3.8398E 01	3.8385E 01	3.9965E 01	-2.5049E-04	-4.0664E-01	1.6717E 01
8	1.2679E-01	7.0441E-02	1.0566E-02	3.4207E 01	3.4194E 01	3.5603E 01	-2.6328E-04	-3.3371E-01	1.6839E 01
			ELEMENT NUMBER	2					
1	1.0732E 00	2.6289E-01	3.9434E-02	1.6174E 01	1.6165E 01	1.6847E 01	1.5363E-03	2.2179E-01	1.6533E 01
2	1.0732E 00	7.0441E-02	3.9434E-02	1.2621E 01	1.2613E 01	1.3152E 01	-6.7633E-04	2.2994E-01	1.6645E 01
3	7.2679E-01	2.6289E-01	3.9434E-02	2.1127E 01	2.1109E 01	2.2009E 01	-3.2834E-06	3.3251E-03	1.6624E 01
4	7.2679E-01	7.0441E-02	3.9434E-02	1.7262E 01	1.7246E 01	1.7990E 01	-2.2154E-03	3.6417E-02	1.6744E 01
5	1.0732E 00	2.6289E-01	1.0566E-02	1.6671E 01	1.6599E 01	1.7278E 01	-2.8976E-05	2.1105E-01	1.6542E 01
6	1.0732E 00	7.0441E-02	1.0566E-02	1.3099E 01	1.3077E 01	1.3614E 01	-1.6293E-04	2.1920E-01	1.6654E 01
7	7.2679E-01	2.6289E-01	1.0566E-02	2.1757E 01	2.1734E 01	2.2624E 01	-4.4361E-04	-8.3737E-03	1.6633E 01
8	7.2679E-01	7.0441E-02	1.0565E-02	1.7924E 01	1.7901E 01	1.8635E 01	-5.7781E-04	2.4718E-02	1.6752E 01
			ELEMENT NUMBER	3					
1	1.6732E 00	2.6289E-01	3.9434E-02	1.0661E 01	1.0681E 01	1.1127E 01	3.2492E-03	5.5905E-01	1.6188E 01
2	1.6732E 00	7.0441E-02	3.9434E-02	7.3571E 00	7.3810E 00	7.6956E 00	1.0171E-03	5.2378E-01	1.6274E 01
3	1.3268E 00	2.6289E-01	3.9434E-02	1.3076E 01	1.3088E 01	1.3648E 01	-1.5320E-04	3.7069E-01	1.6405E 01
4	1.3268E 00	7.0441E-02	3.9434E-02	9.6336E 00	9.6495E 00	1.0073E 01	-2.3954E-03	3.6053E-01	1.6508E 01
5	1.6732E 00	2.6289E-01	1.0566E-02	1.1327E 01	1.1300E 01	1.1756E 01	4.4718E-04	5.4923E-01	1.6192E 01
6	1.6732E 00	7.0441E-02	1.0566E-02	8.0929E 00	8.0672E 00	8.3925E 00	3.0674E-04	5.1397E-01	1.6278E 01
7	1.3268E 00	2.6289E-01	1.0566E-02	1.3925E 01	1.3898E 01	1.4461E 01	-4.7055E-04	3.6045E-01	1.6410E 01
8	1.3268E 00	7.0441E-02	1.0566E-02	1.0554E 01	1.0528E 01	1.0954E 01	-6.1104E-04	3.5029E-01	1.6512E 01
			ELEMENT NUMBER	4					
1	2.2732E 00	2.6289E-01	3.9434E-02	7.8198E 00	7.8658E 00	8.1889E 00	5.8366E-03	8.0050E-01	1.5616E 01
2	2.2732E 00	7.0441E-02	3.9434E-02	4.1944E 00	4.2473E 00	4.4296E 00	4.2046E-03	7.2903E-01	1.5654E 01
3	1.9268E 00	2.6289E-01	3.9434E-02	8.9758E 00	9.0158E 00	9.3979E 00	-4.2068E-04	6.7421E-01	1.5955E 01
4	1.9268E 00	7.0441E-02	3.9434E-02	5.5634E 00	5.6104E 00	5.8604E 00	-2.0530E-03	6.2252E-01	1.6024E 01
5	2.2732E 00	2.6289E-01	1.0566E-02	8.7375E 00	8.7054E 00	9.0500E 00	1.1650E-03	7.8995E-01	1.5618E 01
6	2.2732E 00	7.0441E-02	1.0566E-02	5.2418E 00	5.2115E 00	5.4154E 00	1.1814E-03	7.1847E-01	1.5656E 01
7	1.9268E 00	2.6289E-01	1.0566E-02	1.0039E 01	1.0007E 01	1.0404E 01	-5.1494E-04	6.6431E-01	1.5957E 01
8	1.9268E 00	7.0441E-02	1.0566E-02	6.7561E 00	6.7260E 00	6.9915E 00	-4.9875E-04	6.1262E-01	1.6026E 01
			ELEMENT NUMBER	5					
1	2.8732E 00	2.6289E-01	3.9434E-02	6.9006E 00	6.9647E 00	7.2467E 00	9.1163E-03	8.6963E-01	1.4849E 01
2	2.8732E 00	7.0441E-02	3.9434E-02	2.1431E 00	2.2185E 00	2.3179E 00	8.0453E-03	7.7022E-01	1.4808E 01
3	2.5268E 00	2.6289E-01	3.9434E-02	7.0614E 00	7.1217E 00	7.4180E 00	-9.5026E-04	8.5259E-01	1.5291E 01
4	2.5268E 00	7.0441E-02	3.9434E-02	2.9963E 00	3.0677E 00	3.2098E 00	-2.0213E-03	7.6860E-01	1.5298E 01
5	2.3732E 00	2.6289E-01	1.0566E-02	8.0533E 00	8.0143E 00	8.3259E 00	2.0526E-03	8.5493E-01	1.4850E 01
6	2.3732E 00	7.0441E-02	1.0566E-02	3.5047E 00	3.4688E 00	3.5978E 00	2.1828E-03	7.5652E-01	1.4809E 01
7	2.5268E 00	2.6289E-01	1.0566E-02	8.3200E 00	8.2815E 00	8.6030E 00	-6.4047E-04	8.4102E-01	1.5291E 01
8	2.5268E 00	7.0441E-02	1.0566E-02	4.4538E 00	4.4283E 00	4.5955E 00	-5.1022E-04	7.5703E-01	1.5300E 01

STRESSES AND DIRECT STRAINS FOR TILE NO. 1 AND ITERATION NO. 1

MEM	TEMP	LOCAL COORDINATES X	Y	Z	* STRAINS XX	YY	ZZ	* STRESSES XX	YY	ZZ	XY	YZ	ZX *
1	0.	0.30	0.17	0.02	3.234E-05	-2.970E-04	2.091E-02	3.056E 01	3.054E 01	3.182E 01	-1.733E-04	-2.531E-01	1.675E 01
2	0.	0.90	0.17	0.02	1.015E-04	-1.875E-04	1.162E-02	1.707E 01	1.706E 01	1.777E 01	-3.217E-04	1.173E-01	1.664E 01
3	0.	1.50	0.17	0.02	4.441E-06	-6.568E-05	7.209E-03	1.058E 01	1.057E 01	1.101E 01	1.742E-04	4.485E-01	1.635E 01
4	0.	2.10	0.17	0.02	-8.944E-05	3.724E-05	4.898E-03	7.166E 00	7.173E 00	7.467E 00	1.112E-03	7.014E-01	1.581E 01
5	0.	2.70	0.17	0.02	-1.502E-04	1.032E-04	3.722E-03	5.430E 00	5.445E 00	5.664E 00	2.159E-03	8.087E-01	1.506E 01
6	0.	3.30	0.17	0.02	-1.579E-04	1.275E-04	3.488E-03	5.107E 00	5.124E 00	5.327E 00	3.080E-03	6.764E-01	1.413E 01
7	0.	3.90	0.17	0.02	-8.861E-05	9.413E-05	4.449E-03	6.587E 00	6.598E 00	6.861E 00	3.630E-03	2.052E-01	1.308E 01
8	0.	4.50	0.17	0.02	7.243E-05	-1.763E-05	7.477E-03	1.115E 01	1.115E 01	1.160E 01	3.314E-03	-6.779E-01	1.199E 01
9	0.	5.10	0.17	0.02	3.389E-04	-2.475E-04	1.440E-02	2.146E 01	2.143E 01	2.231E 01	2.243E-03	-1.978E 00	1.093E 01
10	0.	5.70	0.17	0.02	6.651E-04	-5.952E-04	3.010E-02	4.469E 01	4.462E 01	4.647E 01	-4.048E-04	-3.614E 00	9.993E 00
11	0.	0.30	0.17	0.13	-4.985E-05	-3.958E-04	4.535E-03	-1.098E 00	3.234E 00	2.753E 01	8.851E-02	-1.630E-01	1.170E 01
12	0.	0.90	0.17	0.13	-1.229E-04	-1.840E-04	2.811E-03	-5.491E 00	3.418E 00	1.720E 01	5.288E-02	1.013E-01	2.029E 01
13	0.	1.50	0.17	0.13	-4.461E-04	6.061E-05	1.627E-03	-2.664E 01	5.855E-02	9.742E 00	5.416E-01	3.229E-01	1.916E 01
14	0.	2.10	0.17	0.13	-7.918E-04	2.861E-04	9.667E-04	-4.807E 01	-1.244E 00	5.628E 00	1.432E 00	4.998E-01	1.798E 01
15	0.	2.70	0.17	0.13	-1.072E-03	4.517E-04	6.049E-04	-6.545E 01	-2.283E 00	3.336E 00	2.375E 00	5.264E-01	1.622E 01
16	0.	3.30	0.17	0.13	-1.241E-03	5.412E-04	4.851E-04	-7.593E 01	-2.955E 00	2.539E 00	3.089E 00	3.452E-01	1.390E 01
17	0.	3.90	0.17	0.13	-1.259E-03	5.281E-04	6.761E-04	-7.714E 01	-3.226E 00	3.657E 00	3.282E 00	-8.202E-02	1.107E 01
18	0.	4.50	0.17	0.13	-1.095E-03	3.783E-04	1.402E-03	-6.698E 01	-2.716E 00	8.073E 00	2.644E 00	-7.877E-01	7.748E 00
19	0.	5.10	0.17	0.13	-7.355E-04	3.815E-05	3.189E-03	-4.440E 01	-9.126E-01	1.900E 01	1.313E 00	-1.602E 00	3.380E 00
20	0.	5.70	0.17	0.13	-3.018E-04	-4.679E-04	6.799E-03	-1.473E 01	5.936E 00	4.137E 01	-1.089E 00	-2.552E 00	-1.602E-01
21	0.	0.30	0.17	0.30	-6.129E-05	-1.187E-04	3.741E-03	-5.188E 00	-7.484E 00	2.232E 01	2.389E-01	-1.448E-01	1.003E 01
22	0.	0.90	0.17	0.30	-1.123E-04	-2.359E-05	2.563E-03	-7.267E 00	-4.119E 00	1.530E 01	4.555E-01	5.484E-02	2.092E 01
23	0.	1.50	0.17	0.30	-2.869E-04	9.123E-05	1.546E-03	-1.749E 01	-2.363E 00	9.080E 00	7.577E-01	1.650E-01	2.282E 01
24	0.	2.10	0.17	0.30	-5.154E-04	2.263E-04	8.677E-04	-3.120E 01	-1.536E 00	4.879E 00	1.205E 00	2.657E-01	2.101E 01
25	0.	2.70	0.17	0.30	-7.053E-04	3.332E-04	4.927E-04	-4.259E 01	-1.054E 00	2.520E 00	1.556E 00	2.460E-01	1.784E 01
26	0.	3.30	0.17	0.30	-8.065E-04	3.879E-04	3.527E-04	-4.868E 01	-9.017E-01	1.620E 00	1.566E 00	7.629E-02	1.338E 01
27	0.	3.90	0.17	0.30	-7.854E-04	3.714E-04	5.143E-04	-4.745E 01	-1.180E 00	2.599E 00	1.068E 00	-2.480E-01	7.850E 00
28	0.	4.50	0.17	0.30	-6.249E-04	2.682E-04	1.226E-03	-3.787E 01	-2.148E 00	6.957E 00	9.900E-02	-7.801E-01	1.354E 00
29	0.	5.10	0.17	0.30	-3.538E-04	7.557E-05	2.958E-03	-2.179E 01	-4.611E 00	1.748E 01	-1.123E 00	-1.099E 00	-5.193E 00
30	0.	5.70	0.17	0.30	-1.143E-04	-1.549E-04	6.226E-03	-7.900E 00	-9.526E 00	3.718E 01	-1.904E 00	-1.987E 00	-6.264E 00
31	0.	0.30	0.17	0.47	-6.970E-05	-5.609E-05	2.903E-03	-2.321E 00	2.425E-01	1.740E 01	2.789E-01	-1.721E-01	8.899E 00
32	0.	0.90	0.17	0.47	-8.925E-05	1.626E-05	2.139E-03	-3.850E 00	3.306E-01	1.280E 01	6.089E-01	-6.557E-03	2.024E 01
33	0.	1.50	0.17	0.47	-1.549E-04	6.190E-05	1.349E-03	-8.314E 00	3.578E-01	8.010E 00	8.797E-01	5.269E-02	2.392E 01
34	0.	2.10	0.17	0.47	-2.669E-04	1.241E-04	7.430E-04	-1.552E 01	1.140E-01	4.304E 00	1.169E 00	1.141E-01	2.244E 01
35	0.	2.70	0.17	0.47	-3.679E-04	1.781E-04	3.320E-04	-2.190E 01	-5.709E-02	2.073E 00	1.297E 00	8.583E-02	1.824E 01
36	0.	3.30	0.17	0.47	-4.109E-04	2.009E-04	2.453E-04	-2.459E 01	-1.222E-01	1.224E 00	1.055E 00	-4.768E-02	1.212E 01
37	0.	3.90	0.17	0.47	-3.719E-04	1.797E-04	4.017E-04	-2.206E 01	-2.472E-02	2.190E 00	3.277E-01	-2.899E-01	4.505E 00
38	0.	4.50	0.17	0.47	-2.492E-04	1.123E-04	1.094E-03	-1.417E 01	2.926E-01	6.365E 00	-8.144E-01	-6.771E-01	-3.944E 00
39	0.	5.10	0.17	0.47	-9.591E-05	2.014E-05	2.634E-03	-3.712E 00	9.227E-01	1.577E 01	-1.895E 00	-7.515E-01	-1.077E 01
40	0.	5.70	0.17	0.47	-1.614E-05	-5.794E-05	5.228E-03	2.673E 00	1.001E 00	3.141E 01	-1.967E 00	-1.633E 00	-8.722E 00
41	0.	0.30	0.17	0.63	-6.777E-05	1.395E-07	2.143E-03	-2.850E 00	-1.335E-01	1.283E 01	3.006E-01	-2.072E-01	7.679E 00
42	0.	0.90	0.17	0.63	-5.229E-05	1.809E-07	1.673E-03	-2.171E 00	-7.304E-02	1.002E 01	6.591E-01	-7.188E-02	1.868E 01
43	0.	1.50	0.17	0.63	-3.368E-05	2.188E-06	1.109E-03	-1.279E 00	1.559E-01	6.641E 00	9.287E-01	-3.529E-02	2.317E 01
44	0.	2.10	0.17	0.63	-4.072E-05	1.219E-05	6.309E-04	-2.016E 00	1.001E-01	3.766E 00	1.156E 00	-1.788E-03	2.220E 01
45	0.	2.70	0.17	0.63	-5.501E-05	2.296E-05	3.249E-04	-3.098E 00	2.031E-02	1.919E 00	1.160E 00	-3.242E-02	1.754E 01
46	0.	3.30	0.17	0.63	-4.325E-05	2.097E-05	2.136E-04	-2.770E 00	-1.445E-03	1.254E 00	8.102E-01	-1.240E-01	1.037E 01
47	0.	3.90	0.17	0.63	-7.965E-06	-7.970E-08	3.722E-04	-1.939E-01	1.216E-01	2.232E 00	6.924E-03	-2.995E-01	1.529E 00
48	0.	4.50	0.17	0.63	5.175E-05	-3.639E-05	9.840E-04	3.873E 00	3.480E-01	5.946E 00	-1.195E 00	-5.589E-01	-7.619E 00
49	0.	5.10	0.17	0.63	8.224E-05	-6.734E-05	2.249E-03	6.599E 00	6.158E-01	1.357E 01	-2.105E 00	-4.902E-01	-1.357E 01
50	0.	5.70	0.17	0.63	4.201E-05	-2.479E-05	4.129E-03	4.932E 00	-1.396E-01	2.481E 01	-1.973E 00	-1.329E 00	-9.161E 00

```
SUM TILE DEN =    2.18633D-06

P.S. DEN =    1.37988D-06

SUM DEN =    4.06620D-06

OMEGA SQUARED =     7.12655E 06
OMEGA =     2.66956E 03
```

PRIMARY STRUCTURE DEFLECTIONS FOR ITERATION NO. 1

NODE	DX	DY	DZ	RX	RY	RZ
33	6.681679E-05	-1.673227E-06	1.785551E-01	-5.587914E-05	3.189787E-03	
34	6.680365E-05		1.786259E-01	4.809038E-04	3.191435E-03	
35	5.671559E-05	-1.613901E-06	1.756771E-01	-5.725912E-05	6.399900E-03	
36	5.670004E-05		1.757467E-01	4.751717E-04	6.402336E-03	
37	4.701459E-05	-1.536437E-06	1.708824E-01	-5.781297E-05	9.573631E-03	
38	4.699403E-05		1.709508E-01	4.673784E-04	9.576578E-03	
39	3.779292E-05	-1.429681E-06	1.642013E-01	-5.394027E-05	1.267944E-02	
40	3.776843E-05		1.642683E-01	4.556030E-04	1.268287E-02	
41	2.907454E-05	-1.320172E-06	1.556897E-01	-4.895801E-05	1.566771E-02	
42	2.905251E-05		1.557546E-01	4.377079E-04	1.567218E-02	
43	2.120507E-05	-1.232098E-06	1.454340E-01	-3.918960E-05	1.847837E-02	
44	2.116353E-05		1.454960E-01	4.109822E-04	1.848471E-02	
45	1.428868E-05	-1.067070E-06	1.335610E-01	-3.102203E-05	2.105218E-02	
46	1.423488E-05		1.336186E-01	3.767714E-04	2.106069E-02	
47	8.377575E-06	-8.915556E-07	1.202210E-01	-2.576198E-05	2.336588E-02	
48	8.321329E-06		1.202730E-01	3.377073E-04	2.337612E-02	
49	2.536151E-06	-7.026549E-07	1.055738E-01	-2.197572E-05	2.540788E-02	
50	2.477969E-06		1.056194E-01	2.953170E-04	2.541899E-02	
51	-1.711983E-07	-5.027475E-07	8.978516E-02	-1.980127E-05	2.716987E-02	
52	-2.311028E-07		8.982366E-02	2.503702E-04	2.718170E-02	
53	-2.642518E-06	-2.934773E-07	7.302600E-02	-1.593972E-05	2.863894E-02	
54	-2.743862E-06		7.305735E-02	2.037658E-04	2.865112E-02	
55	-3.945375E-06	-7.611419E-08	5.547747E-02	-1.253435E-05	2.979947E-02	
56	-4.007697E-06		5.550126E-02	1.549640E-04	2.981209E-02	
57	-2.914061E-06	1.474601E-07	3.732768E-02	-8.897214E-06	3.064273E-02	
58	-2.986332E-06		3.734367E-02	1.049516E-04	3.065582E-02	
59	-2.587715E-06	3.967929E-07	1.876834E-02	-5.443265E-06	3.116091E-02	
60	-2.664435E-06		1.877641E-02	5.384142E-05	3.117428E-02	
61		5.462543E-07		1.710423E-06	3.133634E-02	
62				-1.713168E-06	3.134975E-02	

MAXIMUM DEFLECTION = 1.79574E-01 FOR DOF 140

MAXIMUM DEFLECTION DIFFERENCE = 7.54654E-04 FOR DOF 194

MID-POINT PLATE MEMBER STRAINS AND STRESSES FOR ITERATION NO. 1

MEMBER	COORDINATES X	Y	STRAINS EPS X	EPS Y	EPS XY	STRESSES SIG X	SIG Y	SIG XY
1	3.0000E-01	1.6666E-01	-1.1270E-06	2.8437E-07	7.6610E-09	-1.1447E 01	-5.9034E-01	5.4721E-02
2	9.0000E-01	1.6666E-01	-3.0212E-06	8.1109E-07	-1.0723E-08	-3.0526E 01	-1.0468E 00	-7.6596E-02
3	1.5000E 00	1.6666E-01	-4.9522E-06	1.4223E-06	5.0875E-10	-4.9731E 01	-6.9658E-01	3.6339E-03
4	2.1000E 00	1.6666E-01	-6.8412E-06	1.9951E-06	-4.9761E-10	-6.8601E 01	-6.2947E-01	-3.5543E-03
5	2.7000E 00	1.6666E-01	-8.6617E-06	2.5449E-06	9.8254E-10	-8.6794E 01	-5.8923E-01	7.0181E-03
6	3.3000E 00	1.6666E-01	-1.0390E-05	3.0682E-06	2.7056E-09	-1.0406E 02	-5.3562E-01	1.9326E-02
7	3.9000E 00	1.6666E-01	-1.2010E-05	3.5613E-06	4.5449E-09	-1.2024E 02	-4.5776E-01	3.2463E-02
8	4.5000E 00	1.6666E-01	-1.3517E-05	4.0194E-06	6.7660E-09	-1.3529E 02	-3.9400E-01	4.8329E-02
9	5.1000E 00	1.6666E-01	-1.4923E-05	4.4374E-06	3.0466E-09	-1.4936E 02	-4.3319E-01	2.1761E-02
10	5.7000E 00	1.6666E-01	-1.6246E-05	4.7443E-06	1.6097E-08	-1.6289E 02	-1.4233E 00	1.1498E-01
11	6.3000E 00	1.6666E-01	-1.7193E-05	4.9652E-06	-4.2749E-09	-1.7257E 02	-2.1183E 00	-3.0535E-02
12	6.9000E 00	1.6666E-01	-1.7465E-05	5.1359E-06	-1.0357E-08	-1.7499E 02	-1.1392E 00	-7.3980E-02
13	7.5000E 00	1.6666E-01	-1.7671E-05	5.2154E-06	-9.4432E-09	-1.7699E 02	-9.4382E-01	-6.7451E-02
14	8.1000E 00	1.6666E-01	-1.7738E-05	5.2276E-06	-7.2482E-09	-1.7769E 02	-1.0326E 00	-5.1773E-02
15	8.7000E 00	1.6666E-01	-1.7630E-05	5.1821E-06	-4.0846E-09	-1.7666E 02	-1.1764E 00	-2.9176E-02
16	9.3000E 00	1.6666E-01	-1.7330E-05	5.0826E-06	-4.9312E-10	-1.7368E 02	-1.2776E 00	-3.5223E-03
17	9.9000E 00	1.6666E-01	-1.6337E-05	4.9307E-06	3.1968E-09	-1.6877E 02	-1.3237E 00	2.2834E-02
18	1.0500E 01	1.6666E-01	-1.6173E-05	4.7256E-06	5.1882E-09	-1.6214E 02	-1.3868E 00	3.7058E-02
19	1.1100E 01	1.6666E-01	-1.5373E-05	4.4492E-06	1.0692E-08	-1.5426E 02	-1.7868E 00	7.6369E-02
20	1.1700E 01	1.6666E-01	-1.4520E-05	4.1243E-06	1.0737E-09	-1.4606E 02	-2.5689E 00	7.6691E-02
21	1.2300E 01	1.6666E-01	-1.3132E-05	3.8284E-06	-1.0975E-08	-1.3169E 02	-1.2216E 00	-7.8394E-02
22	1.2900E 01	1.6666E-01	-1.1538E-05	3.4488E-06	-2.7438E-09	-1.1542E 02	-1.3707E-01	-1.9598E-02
23	1.3500E 01	1.6666E-01	-9.8535E-06	2.9330E-06	-9.0353E-09	-9.8594E 01	-1.9858E-01	-6.4538E-02
24	1.4100E 01	1.6666E-01	-8.0711E-06	2.3913E-06	-6.7381E-09	-8.0809E 01	-3.2947E-01	-4.8129E-02
25	1.4700E 01	1.6666E-01	-6.1804E-06	1.8081E-06	-5.2718E-09	-6.1955E 01	-5.0534E-01	-3.7656E-02

PROGRAM LISTING OF INPUT DATA CARDS

```
.........1.........2.........3.........4.........5.........6.........7.........8
12345678901234567890123456789012345678901234567890123456789012345678901234567890

SAMPLE PROBLEM II   -  STATICS COLD SOAK
    AUGUST 21, 1974
    1                        3        0.         7
    2    1    1         1    1    0    0    0
   0
  6.66667    .33333     .75
       .4
         1         1
                    1.16667    .16667      .05
        10    1         7
     10.E6        .3            13.1E-6
         0
     60.E3     60.E3      6.E3        .5        .1       .01
     20.E3     32.E3     32.E3               1.E-6     1.E-6     1.E-6
       90.       .49            271.E-6
                  1.        1.
    1
       70.     60.E3
    1
       70.      6.E3
    1
       70.     32.E3
    1
       70.        .5
    1
       70.       .01
    1
       70.   .347E-6
    1
       70.        0.
    1
       70.        0.
    1
       70.        0.
A2                           0                           0         0
B2                           2                           0         0
C1                           0
D1                           4
        0.        0.        0.        0.        0.        0.        0.        0.
     -325.
    1    1        70.
     -325.

.........1.........2.........3.........4.........5.........6.........7.........8
12345678901234567890123456789012345678901234567890123456789012345678901234567890
```

OPTIONS

STATICS PROBLEM

MAXIMUM NO. ITERATIONS = 3 CONVERGENCE PARAMETER = 0.0

PRIMARY STRUCTURE STRESSES PRESENTED AFTER EACH ITERATION AT PLATE MID, TOP AND BOTTOM SURFACES

TILES ON PRIMARY STRUCTURE

TILE STRESSES PRESENTED AFTER LAST ITERATION

TILE NODE MAP NOT REQUIRED

TILE ELEMENT MAP REQUIRED

TILE NODE COORDINATES REQUIRED

DO NOT PRINT ELEMENT STIFFNESS MATRICES

DO NOT PRINT ASSEMBLED STIFFNESS MATRICES

DO NOT PRINT TILE DEBUGGING INFORMATION

COMPUTE STRESSES FOR ALL TILES

GEOMETRY

PLATE	LX = 6.66667E 00	LY = 3.33330E-01	TP = 7.50000E-01	
STRINGERS	YI = 4.00000E-01	ZS = 0.0	YS = 0.0	AS = 0.0
	IY' = 0.0	IZ' = 0.0	JX' = 0.0	BETA S = 0.0
TILES	NXB = 1	NYB = 1		
	T = 0.0	B1 = 0.0	T2 = 1.16667E 00	
	TA = 1.66670E-01	TI = 5.00000E-02	TC = 0.0	
BRICK	NB1 = 0	NB2 = 10	ND2 = 1	
	NT1 = 0	NT2 = 7		

MATERIAL PROPERTIES

PLATE	EP = 1.00000E 07	NU P = 3.00000E-01	GAMMA P = 0.0	ALPHA P = 1.31000E-05
STRINGERS	ES = 0.0	NU S = 0.0	GAMMA S = 0.0	ALPHA P = 0.0
ARRESTOR OR RSI	EX = 6.00000E 04	EY = 6.00000E 04	EZ = 6.00000E 03	
	NU XY = 5.00000E-01	NU YZ = 1.00000E-01	NU ZX = 1.00000E-02	
	GXY = 2.20000E 04	GYZ = 3.20000E 04	GZX = 3.20000E 04	
	GAMMA A = 0.0			
	ALPHA X = 9.99999E-07	ALPHA Y = 9.99999E-07	ALPHA Z = 9.99999E-07	
ISOLATOR	EI = 9.00000E 01	NU I = 4.90000E-01	GAMMA I = 0.0	ALPHA I = 2.71000E-04
RSI	GAMMA R = 0.0			
		ALPHA RY / ALPHA RX = 1.00000E 00		ALPHA RZ / ALPHA RX = 1.00000E 00

TEMPERATURE DEPENDENT MATERIAL PROPERTIES

		TEMPERATURE	PROPERTY	TEMPERATURE	PROPERTY	TEMPERATURE	PROPERTY	TEMPERATURE	PROPERTY
1	ER	ALL	6.000E 04						
1	ER'	ALL	6.000E 03						
1	GR'	ALL	3.200E 04						
1	NU R	ALL	5.000E-01						
1	NU R'	ALL	1.000E-02						
1	ALPHA R	ALL	3.470E-07						
1	EC	ALL	0.0						
1	NU C	ALL	0.0						
1	ALPHA C	ALL	0.0						

B O U N D A R Y   C O N D I T I O N S

EDGE	PLATE OUT OF PLANE	PLATE IN PLANE	STRINGERS	
A	PINNED	FREE	FREE	FREE
B	PINNED	U HELD, V FREE	FREE	FREE
C	FREE	FREE		
D	FREE	V HELD, U FREE		

S T A T I C   L O A D I N G

NX = 0.0	NY = 0.0	NXY = 0.0	NYX = 0.0
PZ = 0.0	T = 0.0	M = 0.0	V = 0.0

DEL TEMP P = -2.25000E 02   DEL TEMP S = 0.0

R S I   T E M P E R A T U R E S

STATIC THERMAL LOADING

UNIFORM TEMPERATURE OPTION

T REFERENCE = 7.0000E 01

DEL T U = T - T REF = -3.2500E 02

E L E M E N T   M A P

LAYER 1
RST

81 82 83 84 85 86 87 88 89 90

TILE MESH ELEMENT	T I L E	N O D E S		
1	1	2	24	23
	3	4	26	25
2	3	4	26	25
	5	6	28	27
3	5	6	28	27
	7	8	30	29
4	7	8	30	29
	9	10	32	31
5	9	10	32	31
	11	12	34	33
6	11	12	34	33
	13	14	36	35
7	13	14	36	35
	15	16	38	37
8	15	16	38	37
	17	18	40	39
9	17	18	40	39
	19	20	42	41
10	19	20	42	41
	21	22	44	43
11	23	24	46	45
	25	26	48	47
12	25	26	48	47
	27	28	50	49
13	27	28	50	49
	29	30	52	51
14	29	30	52	51
	31	32	54	53
15	31	32	54	53
	33	34	56	55
16	33	34	56	55
	35	36	58	57
17	35	36	59	57
	37	38	60	59
18	37	38	60	59
	39	40	62	61
19	39	40	62	61
	41	42	64	63

NODE	LOCAL TILE COORDINATES X	Y	Z	TEMPERATURE
1	0.0	0.0	0.0	-3.25000E 02
2	0.0	3.33330E-01	0.0	-3.25000E 02
3	6.66667E-01	0.0	0.0	-3.25000E 02
4	6.66667E-01	3.33330E-01	0.0	-3.25000E 02
5	1.33333E 00	0.0	0.0	-3.25000E 02
6	1.33333E 00	3.33330E-01	0.0	-3.25000E 02
7	2.00000E 00	0.0	0.0	-3.25000E 02
8	2.00000E 00	3.33330E-01	0.0	-3.25000E 02
9	2.66667E 00	0.0	0.0	-3.25000E 02
10	2.66667E 00	3.33330E-01	0.0	-3.25000E 02
11	3.33333E 00	0.0	0.0	-3.25000E 02
12	3.33333E 00	3.33330E-01	0.0	-3.25000E 02
13	4.00000E 00	0.0	0.0	-3.25000E 02
14	4.00000E 00	3.33330E-01	0.0	-3.25000E 02
15	4.66667E 00	0.0	0.0	-3.25000E 02
16	4.66667E 00	3.33330E-01	0.0	-3.25000E 02
17	5.33334E 00	0.0	0.0	-3.25000E 02
18	5.33334E 00	3.33330E-01	0.0	-3.25000E 02
19	6.00000E 00	0.0	0.0	-3.25000E 02
20	6.00000E 00	3.33330E-01	0.0	-3.25000E 02
21	6.66667E 00	0.0	0.0	-3.25000E 02
22	6.66667E 00	3.33330E-01	0.0	-3.25000E 02
23	0.0	0.0	5.00000E-02	-3.25000E 02
24	0.0	3.33330E-01	5.00000E-02	-3.25000E 02
25	6.66667E-01	0.0	5.00000E-02	-3.25000E 02
26	6.66667E-01	3.33330E-01	5.00000E-02	-3.25000E 02
27	1.33333E 00	0.0	5.00000E-02	-3.25000E 02
28	1.33333E 00	3.33330E-01	5.00000E-02	-3.25000E 02
29	2.00000E 00	0.0	5.00000E-02	-3.25000E 02
30	2.00000E 00	3.33330E-01	5.00000E-02	-3.25000E 02
31	2.66667E 00	0.0	5.00000E-02	-3.25000E 02
32	2.66667E 00	3.33330E-01	5.00000E-02	-3.25000E 02
33	3.33333E 00	0.0	5.00000E-02	-3.25000E 02
34	3.33333E 00	3.33330E-01	5.00000E-02	-3.25000E 02
35	4.00000E 00	0.0	5.00000E-02	-3.25000E 02
36	4.00000E 00	3.33330E-01	5.00000E-02	-3.25000E 02
37	4.66667E 00	0.0	5.00000E-02	-3.25000E 02
38	4.66667E 00	3.33330E-01	5.00000E-02	-3.25000E 02
39	5.33334E 00	0.0	5.00000E-02	-3.25000E 02
40	5.33334E 00	3.33330E-01	5.00000E-02	-3.25000E 02
41	6.00000E 00	0.0	5.00000E-02	-3.25000E 02
42	6.00000E 00	3.33330E-01	5.00000E-02	-3.25000E 02
43	6.66667E 00	0.0	5.00000E-02	-3.25000E 02
44	6.66667E 00	3.33330E-01	5.00000E-02	-3.25000E 02
45	0.0	0.0	2.16670E-01	-3.25000E 02
46	0.0	3.33330E-01	2.16670E-01	-3.25000E 02
47	6.66667E-01	0.0	2.16670E-01	-3.25000E 02
48	6.66667E-01	3.33330E-01	2.16670E-01	-3.25000E 02
49	1.33333E 00	0.0	2.16670E-01	-3.25000E 02
50	1.33333E 00	3.33330E-01	2.16670E-01	-3.25000E 02

PRIMARY STRUCTURE — GLOBAL GEOMETRY — DEGREES OF FREEDOM

NODE	X	Y	Z	DX	DY	DZ	RX	RY	RZ
1	0.0	0.0	0.0	1	2	0	3	4	0
2	0.0	3.333300E-01	0.0	5	0	0	6	7	0
3	6.666670E-01	0.0	0.0	8	9	10	11	12	0
4	6.666670E-01	3.333300E-01	0.0	13	0	14	15	16	0
5	1.333334E 00	0.0	0.0	17	18	19	20	21	0
6	1.333334E 00	3.333300E-01	0.0	22	0	23	24	25	0
7	2.000001E 00	0.0	0.0	26	27	28	29	30	0
8	2.000001E 00	3.333300E-01	0.0	31	0	32	33	34	0
9	2.666668E 00	0.0	0.0	35	36	37	38	39	0
10	2.666668E 00	3.333300E-01	0.0	40	0	41	42	43	0
11	3.333335E 00	0.0	0.0	44	45	46	47	48	0
12	3.333335E 00	3.333300E-01	0.0	49	0	50	51	52	0
13	4.000002E 00	0.0	0.0	53	54	55	56	57	0
14	4.000002E 00	3.333300E-01	0.0	58	0	59	60	61	0
15	4.666669E 00	0.0	0.0	62	63	64	65	66	0
16	4.666669E 00	3.333300E-01	0.0	67	0	68	69	70	0
17	5.333336E 00	0.0	0.0	71	72	73	74	75	0
18	5.333336E 00	3.333300E-01	0.0	76	0	77	78	79	0
19	6.000003E 00	0.0	0.0	80	81	82	83	84	0
20	6.000003E 00	3.333300E-01	0.0	85	0	86	87	88	0
21	6.666670E 00	0.0	0.0	0	89	0	90	91	0
22	6.666670E 00	3.333300E-01	0.0	0	0	0	92	93	0

PRIMARY STRUCTURE DEFLECTIONS FOR ITERATION NO. 1

NODE	DX	DY	DZ	RX	RY	RZ
1	2.838170E-02	1.419157E-03		0.0	0.0	
2	2.838172E-02			0.0	0.0	
3	2.554341E-02	1.419158E-03	0.0	0.0	0.0	
4	2.554342E-02		0.0	0.0	0.0	
5	2.270516E-02	1.419166E-03	0.0	0.0	0.0	
6	2.270516E-02		0.0	0.0	0.0	
7	1.986694E-02	1.419171E-03	0.0	0.0	0.0	
8	1.986694E-02		0.0	0.0	0.0	
9	1.702876E-02	1.419175E-03	0.0	0.0	0.0	
10	1.702876E-02		0.0	0.0	0.0	
11	1.419059E-02	1.419178E-03	0.0	0.0	0.0	
12	1.419060E-02		0.0	0.0	0.0	
13	1.135245E-02	1.419182E-03	0.0	0.0	0.0	
14	1.135246E-02		0.0	0.0	0.0	
15	8.514332E-03	1.419182E-03	0.0	0.0	0.0	
16	8.514334E-03		0.0	0.0	0.0	
17	5.676214E-03	1.419185E-03	0.0	0.0	0.0	
18	5.676214E-03		0.0	0.0	0.0	
19	2.838105E-03	1.419186E-03	0.0	0.0	0.0	
20	2.838105E-03		0.0	0.0	0.0	
21		1.419186E-03		0.0	0.0	
22				0.0	0.0	

PRIMARY STRUCTURE NODES ASSOCIATED WITH TILE NO. 1

1	3	5	7	9	11	13	15	17	19	21
2	4	6	8	10	12	14	16	18	20	22

MID-POINT PLATE MEMBER STRAINS AND STRESSES FOR ITERATION NO. 1

MEMBER	COORDINATES X	Y	STRAINS EPS X	EPS Y	EPS XY	STRESSES SIG X	SIG Y	SIG XY
1	3.3333E-01	1.6666E-01	-4.2574E-03	-4.2575E-03	2.5495E-08	6.5625E-01	8.2031E-02	1.8211E-01
2	1.0000E 00	1.6666E-01	-4.2574E-03	-4.2575E-03	1.4232E-08	1.3516E 00	1.6406E-01	1.0166E-01
3	1.6667E 00	1.6666E-01	-4.2573E-03	-4.2575E-03	1.8335E-09	1.8008E 00	8.2031E-02	1.3097E-02
4	2.3333E 00	1.6666E-01	-4.2573E-03	-4.2576E-03	7.0723E-09	2.3750E 00	1.2500E-01	5.0516E-02
5	3.0000E 00	1.6666E-01	-4.2572E-03	-4.2576E-03	1.2049E-08	2.6211E 00	1.2500E-01	8.6065E-02
6	3.6667E 00	1.6666E-01	-4.2572E-03	-4.2575E-03	1.5629E-08	2.9063E 00	8.2031E-02	1.1163E-01
7	4.3333E 00	1.6666E-01	-4.2572E-03	-4.2576E-03	1.6939E-08	3.2344E 00	1.2500E-01	1.2099E-01
8	5.0000E 00	1.6666E-01	-4.2572E-03	-4.2576E-03	9.5170E-09	3.3555E 00	1.2500E-01	6.7979E-02
9	5.6667E 00	1.6666E-01	-4.2572E-03	-4.2576E-03	1.7462E-10	3.5195E 00	8.2031E-02	1.2473E-03
10	6.3333E 00	1.6666E-01	-4.2572E-03	-4.2576E-03	8.7311E-11	3.5195E 00	8.2031E-02	6.2365E-04

PRIMARY STRUCTURE DEFLECTIONS FOR ITERATION NO. 2

NODE	DX	DY	DZ	RX	RY	RZ
1	2.837436E-02	1.419182E-03		1.110410E-08	-4.857246E-05	
2	2.837437E-02			-1.107075E-08	-4.856790E-05	
3	2.553628E-02	1.419224E-03	3.204057E-05	-2.494943E-07	-4.696766E-05	
4	2.553628E-02		3.203745E-05	2.304330E-07	-4.696350E-05	
5	2.269858E-02	1.419286E-03	6.173004E-05	-6.444173E-07	-4.118166E-05	
6	2.269857E-02		6.172433E-05	6.098011E-07	-4.117824E-05	
7	1.986120E-02	1.419325E-03	8.592271E-05	-9.869391E-07	-3.059379E-05	
8	1.986119E-02		8.591506E-05	9.408456E-07	-3.059104E-05	
9	1.702403E-02	1.419350E-03	1.017259E-04	-1.215332E-06	-1.628358E-05	
10	1.702403E-02		1.017165E-04	1.158402E-06	-1.628164E-05	
11	1.418696E-02	1.419358E-03	1.072070E-04	-1.294960E-06	2.458277E-08	
12	1.418696E-02		1.071968E-04	1.233488E-06	2.492761E-08	
13	1.134991E-02	1.419356E-03	1.016948E-04	-1.215301E-06	1.632443E-05	
14	1.134991E-02		1.016850E-04	1.155909E-06	1.632320E-05	
15	8.512773E-03	1.419335E-03	8.587058E-05	-9.875703E-07	3.061576E-05	
16	8.512788E-03		8.586222E-05	9.369464E-07	3.061310E-05	
17	5.675480E-03	1.419303E-03	6.167241E-05	-6.426225E-07	4.117301E-05	
18	5.675491E-03		6.166630E-05	6.055278E-07	4.116938E-05	
19	2.837912E-03	1.419243E-03	3.200154E-05	-2.472392E-07	4.692137E-05	
20	2.837926E-03		3.199324E-05	2.270913E-07	4.691687E-05	
21		1.419209E-03		1.092928E-08	4.850829E-05	
22				-1.089510E-08	4.850344E-05	

MAXIMUM DEFLECTION = 2.83744E-02 FOR DOF 5

MAXIMUM DEFLECTION DIFFERENCE = 1.07207E-04 FOR DOF 46

MAXIMUM CONVERGENCE PARAMETER = 3.77830E-03

SOLUTION HAS NOT CONVERGED

TPS DISPLACEMENTS FOR TILE NO. 1 AND ITERATION NO. 3

NODE	X COMPONENT(U)	Y COMPONENT(V)	Z COMPONENT(W)
1	2.8356735E-02	1.4191780E-03	0.0
2	2.8356742E-02	4.0737547E-09	0.0
3	2.5519237E-02	1.4193156E-03	3.1108400E-05
4	2.5519237E-02	-8.4500016E-08	3.1105301E-05
5	2.2683658E-02	1.4195214E-03	5.9920829E-05
6	2.2683650E-02	-2.2263924E-07	5.9915212E-05
7	1.9850120E-02	1.4196830E-03	8.3383013E-05
8	1.9850120E-02	-3.4235200E-07	8.3375431E-05
9	1.7018143E-02	1.4197913E-03	9.8699835E-05
10	1.7018139E-02	-4.2083934E-07	9.8690522E-05
11	1.4186997E-02	1.4198280E-03	1.0401016E-04
12	1.4186997E-02	-4.4781825E-07	1.0400009E-04
13	1.1355862E-02	1.4197964E-03	9.8668752E-05
14	1.1355866E-02	-4.1985641E-07	9.8659031E-05
15	8.5239187E-03	1.4196937E-03	8.3330786E-05
16	8.5239336E-03	-3.4091357E-07	8.3322491E-05
17	5.6904666E-03	1.4195368E-03	5.9863130E-05
18	5.6904778E-03	-2.2099863E-07	5.9857077E-05
19	2.8549971E-03	1.4193379E-03	3.1069256E-05
20	2.8550087E-03	-8.3249513E-08	3.1065982E-05
21	1.7662009E-05	1.4192052E-03	0.0
22	1.7660204E-05	4.0019721E-09	0.0
23	1.5587583E-02	7.6064793E-04	-1.2956962E-02
24	1.5587766E-02	6.7323772E-04	-1.2960125E-02
25	1.5338384E-02	7.7265571E-04	-1.2648195E-02
26	1.5338622E-02	6.6036545E-04	-1.2651250E-02
27	1.5057739E-02	7.7850767E-04	-1.2551006E-02
28	1.5057940E-02	6.5354165E-04	-1.2553982E-02
29	1.4790334E-02	7.3239455E-04	-1.2500148E-02
30	1.4790516E-02	6.4387037E-04	-1.2503054E-02
31	1.4522307E-02	7.8311702E-04	-1.2469962E-02
32	1.4522433E-02	6.4758677E-04	-1.2472779E-02
33	1.4252145E-02	7.8328699E-04	-1.2460098E-02
34	1.4252219E-02	6.4697629E-04	-1.2462813E-02
35	1.3981856E-02	7.8261830E-04	-1.2470119E-02
36	1.3981912E-02	6.4715929E-04	-1.2472767E-02
37	1.3713460E-02	7.8135147E-04	-1.2500532E-02
38	1.3713501E-02	6.4793133E-04	-1.2503073E-02
39	1.3445422E-02	7.7666598E-04	-1.2551751E-02
40	1.3445560E-02	6.5199099E-04	-1.2554195E-02
41	1.3163764E-02	7.6972460E-04	-1.2649776E-02
42	1.3164302E-02	6.5793312E-04	-1.2652103E-02
43	1.2913782E-02	7.5655939E-04	-1.2960803E-02
44	1.2914129E-02	6.6179486E-04	-1.2963068E-02
45	1.5435152E-02	7.4291974E-04	-1.3182126E-02
46	1.5435338E-02	6.9463029E-04	-1.3186198E-02
47	1.5249137E-02	7.4337330E-04	-1.2763843E-02
48	1.5249330E-02	6.9318260E-04	-1.2767731E-02
49	1.5013330E-02	7.4224360E-04	-1.2597803E-02
50	1.5012553E-02	6.9324533E-04	-1.2601636E-02

STRESSES FOR ISOLATOR AND ARRESTOR FOR TILE NO. 1 AND ITERATION NO. 3

	LOCAL COORDINATES			STRESSES					
	X	Y	Z	XX	YY	ZZ	XY	YZ	ZX
			ELEMENT NUMBER	1					
1	5.2578E-01	2.6289E-01	3.9434E-02	1.5710E 01	1.5712E 01	3.9111E-01	-2.5630E-04	2.3283E-01	-6.4684E 00
2	5.2578E-01	7.0441E-02	3.9434E-02	1.5762E 01	1.5765E 01	4.4556E-01	2.5833E-04	-2.2482E-01	-6.4685E 00
3	1.4088E-01	2.6289E-01	3.9434E-02	1.1014E 01	1.1019E 01	-4.4983E 00	-2.5844E-04	2.3546E-01	-7.3711E 00
4	1.4088E-01	7.0441E-02	3.9434E-02	1.1068E 01	1.1073E 01	-4.4426E 00	2.5608E-04	-2.2715E-01	-7.3712E 00
5	5.2578E-01	2.6289E-01	1.0566E-02	8.8938E 00	8.8943E 00	-6.2898E 00	-7.0354E-05	2.3299E-01	-6.4757E 00
6	5.2578E-01	7.0441E-02	1.0566E-02	8.9462E 00	8.9467E 00	-6.2353E 00	7.1774E-05	-2.2466E-01	-6.4758E 00
7	1.4088E-01	2.6289E-01	1.0566E-02	4.1617E 00	4.1628E 00	-1.1216E 01	-7.0902E-05	2.3563E-01	-7.3784E 00
8	1.4088E-01	7.0441E-02	1.0566E-02	4.2153E 00	4.2165E 00	-1.1160E 01	7.1195E-05	-2.2699E-01	-7.3784E 00
			ELEMENT NUMBER	2					
1	1.1925E 00	2.6289E-01	3.9434E-02	1.8934E 01	1.8937E 01	3.7536E 00	-1.3370E-04	2.2992E-01	-4.9285E 00
2	1.1925E 00	7.0441E-02	3.9434E-02	1.8986E 01	1.8988E 01	3.8067E 00	1.2957E-04	-2.2252E-01	-4.9286E 00
3	8.0755E-01	2.6289E-01	3.9434E-02	1.7791E 01	1.7795E 01	2.5626E 00	-1.3235E-04	2.3134E-01	-5.8195E 00
4	8.0755E-01	7.0441E-02	3.9434E-02	1.7843E 01	1.7846E 01	2.6164E 00	1.3126E-04	-2.2358E-01	-5.8196E 00
5	1.1925E 00	2.6289E-01	1.0566E-02	1.2201E 01	1.2201E 01	-2.8461E 00	-3.8826E-05	2.3008E-01	-4.9303E 00
6	1.1925E 00	7.0441E-02	1.0566E-02	1.2252E 01	1.2253E 01	-2.7928E 00	3.8103E-05	-2.2236E-01	-4.9304E 00
7	8.0755E-01	2.6289E-01	1.0566E-02	1.1039E 01	1.1040E 01	-4.0554E 00	-3.8010E-05	2.3150E-01	-5.8213E 00
8	8.0755E-01	7.0441E-02	1.0566E-02	1.1091E 01	1.1092E 01	-4.0015E 00	3.8951E-05	-2.2342E-01	-5.8214E 00
			ELEMENT NUMBER	3					
1	1.8591E 00	2.6289E-01	3.9434E-02	1.9995E 01	1.9995E 01	4.8571E 00	-8.9503E-05	2.2807E-01	-3.3817E 00
2	1.8591E 00	7.0441E-02	3.9434E-02	2.0045E 01	2.0045E 01	4.9088E 00	8.8453E-05	-2.2118E-01	-3.3817E 00
3	1.4742E 00	2.6289E-01	3.9434E-02	1.9544E 01	1.9545E 01	4.3857E 00	-8.8828E-05	2.2905E-01	-4.2765E 00
4	1.4742E 00	7.0441E-02	3.9434E-02	1.9594E 01	1.9595E 01	4.4392E 00	8.9128E-05	-2.2188E-01	-4.2766E 00
5	1.8591E 00	2.6289E-01	1.0566E-02	1.3270E 01	1.3270E 01	-1.7334E 00	-2.6462E-05	2.2823E-01	-3.3824E 00
6	1.8591E 00	7.0441E-02	1.0566E-02	1.3320E 01	1.3320E 01	-1.6818E 00	2.6609E-05	-2.2103E-01	-3.3824E 00
7	1.4742E 00	2.6289E-01	1.0566E-02	1.2807E 01	1.2807E 01	-2.2163E 00	-2.6672E-05	2.2920E-01	-4.2773E 00
8	1.4742E 00	7.0441E-02	1.0566E-02	1.2857E 01	1.2857E 01	-2.1638E 00	2.6465E-05	-2.2172E-01	-4.2773E 00
			ELEMENT NUMBER	4					
1	2.5258E 00	2.6289E-01	3.9434E-02	2.0503E 01	2.0503E 01	5.3864E 00	-2.1043E-05	2.2733E-01	-1.8335E 00
2	2.5258E 00	7.0441E-02	3.9434E-02	2.0551E 01	2.0551E 01	5.4366E 00	2.1278E-05	-2.2082E-01	-1.8336E 00
3	2.1409E 00	2.6289E-01	3.9434E-02	2.0252E 01	2.0252E 01	5.1250E 00	-1.8680E-05	2.2761E-01	-2.7276E 00
4	2.1409E 00	7.0441E-02	3.9434E-02	2.0301E 01	2.0301E 01	5.1761E 00	2.3528E-05	-2.2090E-01	-2.7277E 00
5	2.5258E 00	2.6289E-01	1.0566E-02	1.3789E 01	1.3789E 01	-1.1932E 00	-7.4484E-06	2.2748E-01	-1.8339E 00
6	2.5258E 00	7.0441E-02	1.0566E-02	1.3838E 01	1.3837E 01	-1.1431E 00	7.4247E-06	-2.2067E-01	-1.8340E 00
7	2.1409E 00	2.6289E-01	1.0566E-02	1.3536E 01	1.3535E 01	-1.4574E 00	-6.8578E-06	2.2776E-01	-2.7280E 00
8	2.1409E 00	7.0441E-02	1.0566E-02	1.3585E 01	1.3584E 01	-1.4063E 00	8.2584E-06	-2.2075E-01	-2.7281E 00
			ELEMENT NUMBER	5					
1	3.1924E 00	2.6289E-01	3.9434E-02	2.0698E 01	2.0697E 01	5.5891E 00	-9.6340E-06	2.2703E-01	-2.8710E-01
2	3.1924E 00	7.0441E-02	3.9434E-02	2.0744E 01	2.0744E 01	5.6376E 00	6.6029E-06	-2.2079E-01	-2.8712E-01
3	2.8075E 00	2.6289E-01	3.9434E-02	2.0620E 01	2.0620E 01	5.5086E 00	-7.8339E-06	2.2717E-01	-1.1802E 00
4	2.8075E 00	7.0441E-02	3.9434E-02	2.0668E 01	2.0667E 01	5.5532E 00	8.7405E-06	-2.2079E-01	-1.1802E 00
5	3.1924E 00	2.6289E-01	1.0566E-02	1.3990E 01	1.3989E 01	-9.8430E-01	-3.5045E-06	2.2717E-01	-2.8722E-01
6	3.1924E 00	7.0441E-02	1.0566E-02	1.4037E 01	1.4036E 01	-9.3584E-01	2.1825E-06	-2.2065E-01	-2.8724E-01
7	2.8075E 00	2.6289E-01	1.0566E-02	1.3912E 01	1.3911E 01	-1.0660E 00	-2.9841E-06	2.2732E-01	-1.1803E 00
8	2.8075E 00	7.0441E-02	1.0566E-02	1.3959E 01	1.3959E 01	-1.0164E 00	2.7203E-06	-2.2064E-01	-1.1803E 00

STRESSES AND DIRECT STRAINS FOR TILE NO. 1 AND ITERATION NO. 3

MEM	TEMP	LOCAL COORDINATES X	Y	Z	* STRAINS XX	YY	ZZ	* STRESSES XX	YY	ZZ	XY	YZ	ZX *
1	-325.	0.33	0.17	0.02	-2.315E-03	-2.279E-03	-2.564E-01	9.971E 00	9.973E 00	-5.376E 00	4.430E-07	4.162E-03	-6.923E 00
2	-325.	1.00	0.17	0.02	-2.337E-03	-2.307E-03	-2.529E-01	1.502E 01	1.502E 01	-1.196E-01	-5.625E-07	3.872E-03	-5.375E 00
3	-325.	1.67	0.17	0.02	-2.326E-03	-2.324E-03	-2.520E-01	1.643E 01	1.643E 01	1.349E 00	-7.735E-08	3.593E-03	-3.830E 00
4	-325.	2.33	0.17	0.02	-2.325E-03	-2.332E-03	-2.516E-01	1.704E 01	1.704E 01	1.990E 00	7.876E-07	3.383E-03	-2.281E 00
5	-325.	3.00	0.17	0.02	-2.326E-03	-2.334E-03	-2.514E-01	1.733E 01	1.733E 01	2.286E 00	-6.610E-07	3.229E-03	-7.337E-01
6	-325.	3.67	0.17	0.02	-2.326E-03	-2.334E-03	-2.514E-01	1.733E 01	1.733E 01	2.286E 00	-2.496E-06	3.092E-03	8.124E-01
7	-325.	4.33	0.17	0.02	-2.325E-03	-2.332E-03	-2.516E-01	1.704E 01	1.704E 01	1.987E 00	-2.890E-06	2.960E-03	2.359E 00
8	-325.	5.00	0.17	0.02	-2.326E-03	-2.323E-03	-2.520E-01	1.642E 01	1.642E 01	1.341E 00	-3.417E-06	2.805E-03	3.908E 00
9	-325.	5.67	0.17	0.02	-2.338E-03	-2.307E-03	-2.529E-01	1.499E 01	1.500E 01	-1.440E-01	-3.052E-06	2.572E-03	5.453E 00
10	-325.	6.33	0.17	0.02	-2.315E-03	-2.278E-03	-2.564E-01	9.904E 00	9.907E 00	-5.445E 00	-2.173E-06	2.244E-03	7.001E 00
11	-325.	0.33	0.17	0.13	-3.264E-04	-2.236E-04	-1.025E-03	1.280E 00	2.803E 00	-3.919E 00	-1.090E-03	4.053E-03	-5.748E 00
12	-325.	1.00	0.17	0.13	-3.874E-04	-2.523E-04	-4.899E-04	-2.601E 00	2.297E 00	-7.626E-01	-1.588E-03	3.457E-03	-6.509E 00
13	-325.	1.67	0.17	0.13	-3.888E-04	-2.692E-04	-2.060E-04	-2.163E 00	3.311E 00	1.043E 00	-6.566E-04	3.457E-03	-3.888E 00
14	-325.	2.33	0.17	0.13	-3.913E-04	-2.793E-04	-9.189E-05	-2.304E 00	3.315E 00	1.728E 00	-2.841E-04	3.576E-03	-2.252E 00
15	-325.	3.00	0.17	0.13	-3.948E-04	-2.820E-04	-4.342E-05	-2.485E 00	3.364E 00	2.023E 00	-1.690E-03	3.695E-03	-7.064E-01
16	-325.	3.67	0.17	0.13	-3.950E-04	-2.819E-04	-4.357E-05	-2.495E 00	3.363E 00	2.022E 00	-3.353E-03	3.338E-03	8.361E-01
17	-325.	4.33	0.17	0.13	-3.918E-04	-2.790E-04	-9.254E-05	-2.335E 00	3.314E 00	1.724E 00	-3.544E-03	2.980E-03	2.380E 00
18	-325.	5.00	0.17	0.13	-3.896E-04	-2.686E-04	-2.078E-04	-2.213E 00	3.310E 00	1.032E 00	-3.818E-03	2.742E-03	4.013E 00
19	-325.	5.67	0.17	0.13	-3.885E-04	-2.514E-04	-4.947E-04	-2.676E 00	2.287E 00	-7.920E-01	-2.240E-03	1.907E-03	6.642E 00
20	-325.	6.33	0.17	0.13	-3.272E-04	-2.224E-04	-1.034E-03	1.213E 00	2.787E 00	-3.977E 00	-1.364E-03	2.980E-03	5.857E 00
21	-325.	0.33	0.17	0.30	-2.380E-04	-1.005E-04	-4.711E-04	-9.988E 00	-4.439E 00	-2.295E 00	-2.071E-03	2.980E-03	-3.986E 00
22	-325.	1.00	0.17	0.30	-3.212E-04	-8.401E-05	-2.611E-04	-1.575E 01	-6.259E 00	-1.110E 00	-1.639E-03	3.219E-03	-5.603E 00
23	-325.	1.67	0.17	0.30	-3.582E-04	-7.308E-05	1.225E-05	-1.795E 01	-6.541E 00	5.053E-01	-7.451E-04	2.980E-03	-3.971E 00
24	-325.	2.33	0.17	0.30	-3.681E-04	-7.187E-05	1.521E-04	-1.853E 01	-6.675E 00	1.337E 00	-1.495E-03	3.099E-03	-2.166E 00
25	-325.	3.00	0.17	0.30	-3.725E-04	-7.136E-05	2.035E-04	-1.879E 01	-6.748E 00	1.642E 00	-1.937E-03	3.219E-03	-6.657E-01
26	-325.	3.67	0.17	0.30	-3.727E-04	-7.129E-05	2.034E-04	-1.881E 01	-6.750E 00	1.641E 00	-2.231E-03	3.099E-03	8.199E-01
27	-325.	4.33	0.17	0.30	-3.685E-04	-7.165E-05	1.516E-04	-1.855E 01	-6.674E 00	1.334E 00	-2.305E-03	2.503E-03	2.324E 00
28	-325.	5.00	0.17	0.30	-3.569E-04	-7.270E-05	1.052E-05	-1.799E 01	-6.540E 00	4.945E-01	-2.361E-03	2.623E-03	4.129E 00
29	-325.	5.67	0.17	0.30	-3.219E-04	-8.349E-05	-2.651E-04	-1.579E 01	-6.250E 00	-1.134E 00	-5.588E-04	1.550E-03	5.754E 00
30	-325.	6.33	0.17	0.30	-2.397E-04	-1.000E-04	-4.770E-04	-1.003E 01	-4.483E 00	-2.330E 00	-8.428E-04	3.576E-03	4.108E 00
31	-325.	0.33	0.17	0.47	-1.777E-04	-6.794E-05	-2.998E-04	-3.628E 00	7.613E-01	-1.151E 00	-2.151E-03	2.861E-03	-1.843E 00
32	-325.	1.00	0.17	0.47	-2.614E-04	-3.473E-05	-2.810E-04	-8.990E 00	7.757E-02	-1.093E 00	-1.942E-03	2.384E-03	-4.232E 00
33	-325.	1.67	0.17	0.47	-3.192E-04	-2.676E-06	-7.657E-05	-1.233E 01	9.059E-02	9.486E-02	-6.193E-04	2.861E-03	-3.621E 00
34	-325.	2.33	0.17	0.47	-3.405E-04	1.122E-06	6.578E-05	-1.351E 01	1.740E-01	9.390E-01	-1.653E-03	2.861E-03	-2.110E 00
35	-325.	3.00	0.17	0.47	-3.478E-04	4.116E-06	1.230E-04	-1.387E 01	2.067E-01	1.278E 00	-1.527E-03	2.623E-03	-6.378E-01
36	-325.	3.67	0.17	0.47	-3.479E-04	4.163E-06	1.228E-04	-1.388E 01	2.046E-01	1.277E 00	-8.801E-04	2.623E-03	7.788E-01
37	-325.	4.33	0.17	0.47	-3.412E-04	1.269E-06	6.515E-05	-1.352E 01	1.736E-01	9.340E-01	-1.830E-03	2.146E-03	2.254E 00
38	-325.	5.00	0.17	0.47	-3.164E-04	-2.469E-06	-7.826E-05	-1.236E 01	8.846E-02	9.433E-02	-2.710E-03	2.027E-03	3.772E 00
39	-325.	5.67	0.17	0.47	-2.613E-04	-3.443E-05	-2.540E-04	-9.013E 00	7.962E-02	-1.117E 00	2.313E-06	1.311E-03	4.374E 00
40	-325.	6.33	0.17	0.47	-1.732E-04	-6.778E-05	-3.034E-04	-3.665E 00	7.495E-01	-1.173E 00	-1.537E-03	3.457E-03	1.953E 00
41	-325.	0.33	0.17	0.63	-1.483E-04	-8.901E-05	-1.901E-04	-1.991E 00	3.824E-01	-4.803E-01	-2.105E-03	2.623E-03	-8.664E-01
42	-325.	1.00	0.17	0.63	-2.146E-04	-5.971E-05	-2.423E-04	-6.194E 00	2.433E-03	-8.448E-01	-1.621E-03	1.669E-03	-2.751E 00
43	-325.	1.67	0.17	0.63	-2.779E-04	-3.150E-05	-1.197E-04	-9.936E 00	-1.306E-01	-1.425E-01	-1.262E-03	2.027E-03	-2.969E 00
44	-325.	2.33	0.17	0.63	-3.166E-04	-1.692E-05	4.422E-06	-1.130E 01	-4.924E-02	5.843E-01	-1.886E-03	2.027E-03	-1.930E 00
45	-325.	3.00	0.17	0.63	-3.295E-04	-1.185E-05	6.278E-05	-1.240E 01	-5.117E-02	9.288E-01	-1.448E-03	1.907E-03	-6.021E-01
46	-325.	3.67	0.17	0.63	-3.294E-04	-1.183E-05	6.261E-05	-1.241E 01	-5.335E-02	9.277E-01	-2.360E-04	2.027E-03	7.418E-01
47	-325.	4.33	0.17	0.63	-3.097E-04	-1.687E-05	3.785E-06	-1.180E 01	-8.835E-02	5.905E-01	-2.473E-03	1.788E-03	2.073E 00
48	-325.	5.00	0.17	0.63	-2.780E-04	-3.143E-05	-1.211E-04	-9.995E 00	-1.320E-01	-1.511E-01	-3.404E-03	1.311E-03	3.108E 00
49	-325.	5.67	0.17	0.63	-2.147E-04	-5.961E-05	-2.454E-04	-6.291E 00	3.664E-03	-8.590E-01	-1.225E-03	8.345E-04	2.875E 00
50	-325.	6.33	0.17	0.63	[illegible]	[illegible]	-1.921E-04	-2.017E 00	3.711E-01	-4.925E-01	-1.462E-03	3.099E-03	9.724E-01

BOTTOM-POINT PLATE MEMBER STRAINS AND STRESSES FOR ITERATION NO. 3

MEMBER	COORDINATES X	Y	EPS X	STRAINS EPS Y	EPS XY	SIG X	STRESSES SIG Y	SIG XY
1	3.3333E-01	1.6665E-01	-4.2580E-03	-4.2574E-03	1.6214E-08	-5.2813E 00	-5.3125E-01	1.1581E-01
2	1.0000E 00	1.6666E-01	-4.2597E-03	-4.2569E-03	1.3421E-08	-2.2148E 01	-1.6406E-01	9.5864E-02
3	1.6667E 00	1.6666E-01	-4.2619E-03	-4.2562E-03	5.1156E-09	-4.3762E 01	-2.8516E-01	3.6540E-02
4	2.3333E 00	1.6666E-01	-4.2636E-03	-4.2557E-03	4.1084E-09	-6.0832E 01	-2.4609E-01	2.9345E-02
5	3.0000E 00	1.6666E-01	-4.2645E-03	-4.2554E-03	-9.7114E-10	-7.0004E 01	-2.4609E-01	-6.9367E-03
6	3.6667E 00	1.6666E-01	-4.2645E-03	-4.2554E-03	2.2289E-09	-6.9676E 01	-2.4609E-01	1.5920E-02
7	4.3333E 00	1.6666E-01	-4.2635E-03	-4.2557E-03	8.6426E-09	-6.0016E 01	-2.0313E-01	6.1733E-02
8	5.0000E 00	1.6666E-01	-4.2617E-03	-4.2563E-03	1.1266E-08	-4.2246E 01	-2.4609E-01	8.0474E-02
9	5.6667E 00	1.6666E-01	-4.2595E-03	-4.2569E-03	2.4381E-09	-2.0192E 01	-1.6406E-01	1.7415E-02
10	6.3333E 00	1.6666E-01	-4.2577E-03	-4.2575E-03	1.1365E-09	-2.6602E 00	-5.3125E-01	8.1179E-03

PROGRAM LISTING OF INPUT DATA CARDS

```
.........1.........2.........3.........4.........5.........6.........7.........8
12345678901234567890123456789012345678901234567890123456789012345678901234567890

SAMPLE PROBLEM III  -  NORMAL PRESSURE
    AUGUST 21, 1974
    1                        3        .05         6
    2    2    1    1    0    0    0    0    0
   0
   6.66667    .33333      .75
        .5
         1         1
                       1.16667   .16667       .05
        10    1             7
     10.E6        .3
         0
     60.E3     60.E3      6.E3       .5        .1        .01
     20.E3     32.E3     32.E3
       90.       .49
        0.
    1
        0.     60.E3
    1
        0.      6.E3
    1
        0.     32.E3
    1
        0.        .5
    1
        0.       .01
    1
        0.        0.
    1
        0.        0.
    1
        0.        0.
    1
        0.        0.
A2                            C                            0         0
B2                            2                            0         0
C0                            4
D0                            0
        0.        0.        0.        0.      100.        0.        0.        0.
        0.        0.
    0    1        0.
        0.

.........1.........2.........3.........4.........5.........6.........7.........8
12345678901234567890123456789012345678901234567890123456789012345678901234567890
```

O P T I O N S
- - - - - - -

STATICS PROBLEM

MAXIMUM NO. ITERATIONS = 3 CONVERGENCE PARAMETER = 5.0000E-02

PRIMARY STRUCTURE STRESSES PRESENTED AFTER LAST ITERATION AT PLATE TOP AND BOTTOM SURFACES

TILES ON PRIMARY STRUCTURE

TILE STRESSES PRESENTED AFTER LAST ITERATION

TILE NODE MAP REQUIRED

TILE ELEMENT MAP NOT REQUIRED

TILE NODE COORDINATES NOT REQUIRED

DO NOT PRINT ELEMENT STIFFNESS MATRICES

DO NOT PRINT ASSEMBLED STIFFNESS MATRICES

DO NOT PRINT FILE DEBUGGING INFORMATION

COMPUTE STRESSES FOR ALL TILES

G E O M E T R Y

PLATE	LX = 6.66667E 00	LY = 3.33330E-01	TP = 7.50000E-01	
STRINGERS	Y1 = 5.00000E-01	ZS = 0.0	YS = 0.0	AS = 0.0
	IY' = 0.0	IZ' = 0.0	JX' = 0.0	BETA S = 0.0
TILES	NXB = 1	NYB = 1		
	T = 0.0	B1 = 0.0	T2 = 1.16667E 00	
	TA = 1.66670E-01	TI = 5.00000E-02	TC = 0.0	
BRICK	NB1 = 0	NB2 = 10	ND2 = 1	
	NT1 = 0	NT2 = 7		

M A T E R I A L   P R O P E R T I E S

PLATE	EP = 1.00000E 07	NU P = 3.00000E-01	GAMMA P = 0.0	ALPHA P = 0.0
STRINGERS	ES = 0.0	NU S = 0.0	GAMMA S = 0.0	ALPHA P = 0.0
ARRESTOR OR RSI	EX = 6.00000E 04	EY = 6.00000E 04	EZ = 6.00000E 03	
	NU XY = 5.00000E-01	NU YZ = 1.00000E-01	NU ZX = 1.00000E-02	
	GXY = 2.00000E 04	GYZ = 3.20000E 04	GZX = 3.20000E 04	
	GAMMA A = 0.0			
	ALPHA X = 0.0	ALPHA Y = 0.0	ALPHA Z = 0.0	
ISOLATOR	EI = 9.00000E 01	NU I = 4.90000E-01	GAMMA I = 0.0	ALPHA I = 0.0
RSI	GAMMA R = 0.0			
		ALPHA RY / ALPHA RX = 0.0		ALPHA RZ / ALPHA RX = 0.0

TEMPERATURE DEPENDENT MATERIAL PROPERTIES

		TEMPERATURE	PROPERTY	TEMPERATURE	PROPERTY	TEMPERATURE	PROPERTY	TEMPERATURE	PROPERTY
1	ER	ALL	6.000E 04						
1	ER'	ALL	6.000E 03						
1	GR'	ALL	3.200E 04						
1	NU R	ALL	5.000E-01						
1	NU R'	ALL	1.000E-02						
1	ALPHA R	ALL	0.0						
1	EC	ALL	0.0						
1	NU C	ALL	0.0						
1	ALPHA C	ALL	0.0						

B O U N D A R Y   C O N D I T I O N S

EDGE	PLATE OUT OF PLANE	PLATE IN PLANE	STRINGERS	
A	PINNED	FREE	FREE	FREE
B	PINNED	U HELD, V FREE	FREE	FREE
C	FREE	V HELD, U FREE		
D	FREE	FREE		

S T A T I C   L O A D I N G

NX = C.0	NY = 0.0	NXY = 0.0	NYX = 0.0
PZ = 1.00000E 02	T = C.C	M = 0.0	V = 0.0

DEL TEMP P = C.0   DEL TEMP S = C.0

R S I   T E M P E R A T U R E S

NO STATIC THERMAL LOADING

UNIFORM TEMPERATURE OPTION

T REFERENCE = 0.0

DEL T U = T - T REF = 0.0

NODE MAP

SURFACE 1

200	202	204	206	208	210	212	214	216	218	220
199	201	203	205	207	209	211	213	215	217	219

NODE MAP

SURFACE 2

178	180	182	184	186	188	190	192	194	196	198
177	179	181	183	185	187	189	191	193	195	197

PRIMARY STRUCTURE

GLOBAL GEOMETRY

DEGREES OF FREEDOM

NODE	X	Y	Z	DX	DY	DZ	RX	RY	RZ
1	0.0	0.0	0.0	1	0	0	2	3	0
2	0.0	3.333300E-01	0.0	4	5	0	6	7	0
3	6.666670E-01	0.0	0.0	8	0	9	10	11	0
4	6.666670E-01	3.333300E-01	0.0	12	13	14	15	16	0
5	1.333334E 00	0.0	0.0	17	0	18	19	20	0
6	1.333334E 00	3.333300E-01	0.0	21	22	23	24	25	0
7	2.000001E 00	0.0	0.0	26	0	27	28	29	0
8	2.000001E 00	3.333300E-01	0.0	30	31	32	33	34	0
9	2.666668E 00	0.0	0.0	35	0	36	37	38	0
10	2.666668E 00	3.333300E-01	0.0	39	40	41	42	43	0
11	3.333335E 00	0.0	0.0	44	0	45	46	47	0
12	3.333335E 00	3.333300E-01	0.0	48	49	50	51	52	0
13	4.000002E 00	0.0	0.0	53	0	54	55	56	0
14	4.000002E 00	3.333300E-01	0.0	57	58	59	60	61	0
15	4.666669E 00	0.0	0.0	62	0	63	64	65	0
16	4.666669E 00	3.333300E-01	0.0	66	67	68	69	70	0
17	5.333336E 00	0.0	0.0	71	0	72	73	74	0
18	5.333336E 00	3.333300E-01	0.0	75	76	77	78	79	0
19	6.000003E 00	0.0	0.0	80	0	81	82	83	0
20	6.000003E 00	3.333300E-01	0.0	84	85	86	87	88	0
21	6.666670E 00	0.0	0.0	0	0	0	89	90	0
22	6.666670E 00	3.333300E-01	0.0	0	91	0	92	93	0

PRIMARY STRUCTURE DEFLECTIONS FOR ITERATION NO. 1

NODE	DX	DY	DZ	RX	RY	RZ
1	0.0			-1.473518E-06	3.456739E-03	
2	0.0	0.0		1.470131E-06	3.456733E-03	
3	0.0		-2.264617E-03	2.863919E-05	3.268892E-03	
4	0.0	0.0	-2.264618E-03	-2.864301E-05	3.268868E-03	
5	0.0		-4.286710E-03	5.041329E-05	2.744951E-03	
6	0.0	0.0	-4.286692E-03	-5.027156E-05	2.744913E-03	
7	0.0		-5.870827E-03	6.620480E-05	1.969881E-03	
8	0.0	0.0	-5.870786E-03	-6.595705E-05	1.969814E-03	
9	0.0		-6.877355E-03	7.583386E-05	1.027109E-03	
10	0.0	0.0	-6.877262E-03	-7.522025E-05	1.027037E-03	
11	0.0		-7.222328E-03	7.908084E-05	2.700736E-07	
12	0.0	0.0	-7.222202E-03	-7.829435E-05	2.323126E-07	
13	0.0		-6.877705E-03	7.592475E-05	-1.026573E-03	
14	0.0	0.0	-6.877575E-03	-7.511086E-05	-1.026564E-03	
15	0.0		-5.871460E-03	6.644083E-05	-1.969688E-03	
16	0.0	0.0	-5.871363E-03	-6.583716E-05	-1.969655E-03	
17	0.0		-4.287299E-03	5.057774E-05	-2.745199E-03	
18	0.0	0.0	-4.287232E-03	-5.013507E-05	-2.745150E-03	
19	0.0		-2.264980E-03	2.877529E-05	-3.269351E-03	
20	0.0	0.0	-2.264944E-03	-2.853607E-05	-3.269293E-03	
21				-1.470409E-06	-3.457324E-03	
22		0.0		1.468549E-06	-3.457266E-03	

PRIMARY STRUCTURE NODES ASSCCIATED WITH TILE NO. 1

1	3	5	7	9	11.	13	15	17	19	21
2	4	6	8	10	12	14	16	18	20	22

PRIMARY STRUCTURE DEFLECTIONS FOR ITERATION NO. 2

NODE	DX	DY	DZ	RX	RY	RZ
1	-3.901913E-06			-1.457974E-06	3.361257E-03	
2	-3.897959E-06	7.973046E-08		1.453203E-06	3.361257E-03	
3	-3.676207E-06		-2.201482E-03	2.826525E-05	3.175853E-03	
4	-3.671434E-06	6.345107E-08	-2.201487E-03	-2.829292E-05	3.175835E-03	
5	-3.351139E-06		-4.164275E-03	4.925889E-05	2.661913E-03	
6	-3.346494E-06	4.207058E-08	-4.164264E-03	-4.916536E-05	2.661876E-03	
7	-2.938193E-06		-5.699161E-03	6.429966E-05	1.907061E-03	
8	-2.935175E-06	2.713396E-08	-5.699124E-03	-6.406714E-05	1.906994E-03	
9	-2.460804E-06		-6.673034E-03	7.339950E-05	9.932443E-04	
10	-2.459236E-06	1.782072E-08	-6.672934E-03	-7.276067E-05	9.931689E-04	
11	-1.949114E-06		-7.006560E-03	7.645463E-05	2.626637E-07	
12	-1.949119E-06	1.465368E-08	-7.006425E-03	-7.562677E-05	2.205044E-07	
13	-1.437492E-06		-6.673370E-03	7.350260E-05	-9.927261E-04	
14	-1.439067E-06	1.783919E-08	-6.673235E-03	-7.263929E-05	-9.927156E-04	
15	-9.603064E-07		-5.699780E-03	6.455116E-05	-1.906876E-03	
16	-9.633204E-07	2.717687E-08	-5.699676E-03	-6.391277E-05	-1.906838E-03	
17	-5.476637E-07		-4.164848E-03	4.944927E-05	-2.662152E-03	
18	-5.523403E-07	4.207477E-08	-4.164778E-03	-4.899905E-05	-2.662102E-03	
19	-2.230393E-07		-2.201836E-03	2.841215E-05	-3.176297E-03	
20	-2.290736E-07	6.385153E-08	-2.201798E-03	-2.817533E-05	-3.176240E-03	
21				-1.454991E-06	-3.361825E-03	
22		7.931072E-08		1.452934E-06	-3.361768E-03	

MAXIMUM DEFLECTION = -3.36177E-03 FOR DOF 93

MAXIMUM DEFLECTION DIFFERENCE = 2.15776E-04 FOR DOF 50

MAXIMUM CONVERGENCE PARAMETER = 6.41853E-02

SOLUTION HAS NOT CONVERGED

PRIMARY STRUCTURE DEFLECTIONS FOR ITERATION NO. 3

NODE	DX	DY	DZ	RX	RY	RZ
1	-3.838843E-06			-1.455582E-06	3.364080E-03	
2	-3.834992E-06	7.958687E-08		1.455494E-06	3.364078E-03	
3	-3.615079E-06		-2.203349E-03	2.828105E-05	3.178601E-03	
4	-3.610429E-06	6.373557E-08	-2.203352E-03	-2.829883E-05	3.178587E-03	
5	-3.294500E-06		-4.167896E-03	4.928574E-05	2.664377E-03	
6	-3.289982E-06	4.291585E-08	-4.167885E-03	-4.920547E-05	2.664342E-03	
7	-2.898414E-06		-5.704246E-03	6.433637E-05	1.908939E-03	
8	-2.885486E-06	2.840901E-08	-5.704213E-03	-6.412840E-05	1.908872E-03	
9	-2.419676E-06		-6.679095E-03	7.343816E-05	9.942634E-04	
10	-2.418157E-06	1.937944E-08	-6.679010E-03	-7.286872E-05	9.941910E-04	
11	-1.917612E-06		-7.012971E-03	7.650600E-05	2.646018E-07	
12	-1.917616E-06	1.631173E-08	-7.012848E-03	-7.574550E-05	2.219912E-07	
13	-1.415613E-06		-6.679438E-03	7.356293E-05	-9.937447E-04	
14	-1.417140E-06	1.939791E-08	-6.679308E-03	-7.272129E-05	-9.937328E-04	
15	-9.470772E-07		-5.704869E-03	6.458355E-05	-1.908754E-03	
16	-9.500015E-07	2.845171E-08	-5.704772E-03	-6.399328E-05	-1.908718E-03	
17	-5.412911E-07		-4.168469E-03	4.946388E-05	-2.664619E-03	
18	-5.458402E-07	4.292060E-08	-4.168406E-03	-4.905126E-05	-2.664571E-03	
19	-2.211529E-07		-2.203700E-03	2.842055E-05	-3.179051E-03	
20	-2.260555E-07	6.412620E-08	-2.203666E-03	-2.818723E-05	-3.178995E-03	
21				-1.455612E-06	-3.364645E-03	
22		7.917902E-08		1.453408E-06	-3.364590E-03	

MAXIMUM DEFLECT ION = -3.36459E-03 FOR DOF 93

MAXIMUM DEFLECTION DIFFERENCE = 6.42240E-06 FOR DOF 50

MAXIMUM CONVERGENCE PARAMETER = 1.90PP2E-03

SOLUTION HAS CONVERGED

TPS DISPLACEMENTS FOR TILE NO. 1 AND ITERATION NO. 3

NODE	X COMPONENT(U)	Y COMPONENT(V)	Z COMPONENT(W)
1	1.2576911E-03	5.4584314E-07	0.0
2	1.2576941E-03	-4.6622353E-07	0.0
3	1.1883602E-03	-1.0605394E-05	-2.2033486E-03
4	1.1883595E-03	1.0675798E-05	-2.2033518E-03
5	9.9584647E-04	-1.8482140E-05	-4.1678958E-03
6	9.9583808E-04	1.8494960E-05	-4.1678846E-03
7	7.1296352E-04	-2.4126130E-05	-5.7042465E-03
8	7.1294140E-04	2.4076551E-05	-5.7042129E-03
9	3.7042890E-04	-2.7539310E-05	-6.6790953E-03
10	3.7040329E-04	2.7345130E-05	-6.6790096E-03
11	-1.8183864E-06	-2.8689741E-05	-7.0129707E-03
12	-1.8343690E-06	2.8420851E-05	-7.0128478E-03
13	-3.7406967E-04	-2.7586095E-05	-6.6794381E-03
14	-3.7406664E-04	2.7289876E-05	-6.6793077E-03
15	-7.1672956E-04	-2.4218825E-05	-5.7048686E-03
16	-7.1671931E-04	2.4025925E-05	-5.7047717E-03
17	-9.9977315E-04	-1.8548948E-05	-4.1684695E-03
18	-9.9975988E-04	1.8437131E-05	-4.1684061E-03
19	-1.1923651E-03	-1.0657704E-05	-2.2036997E-03
20	-1.1923490E-03	1.0634339E-05	-2.2036657E-03
21	-1.2617419E-03	5.4585439E-07	0.0
22	-1.2617209E-03	-4.6584898E-07	0.0
23	-1.9288564E-03	-3.6905985E-04	-3.7478809E-03
24	-1.9288959E-03	3.6939513E-04	-3.7476560E-03
25	-1.7317173E-03	-3.4020585E-04	-5.6907944E-03
26	-1.7317629E-03	3.4074089E-04	-5.6905597E-03
27	-1.4811209E-03	-3.0802726E-04	-7.4508972E-03
28	-1.4811754E-03	3.0878210E-04	-7.4506365E-03
29	-1.0883159E-03	-2.7959980E-04	-8.8769421E-03
30	-1.0883401E-03	2.8061983E-04	-8.8766739E-03
31	-5.7616225E-04	-2.6274496E-04	-9.7944960E-03
32	-5.7614408E-04	2.6372983E-04	-9.7941980E-03
33	-1.3282192E-07	-2.5708741E-04	-1.0110635E-02
34	-1.1892917E-07	2.5797938E-04	-1.0110315E-02
35	5.7595852E-04	-2.6276428E-04	-9.7948052E-03
36	5.7593780E-04	2.6369118E-04	-9.7944811E-03
37	1.0882213E-03	-2.7955766E-04	-8.8774636E-03
38	1.0881955E-03	2.8062542E-04	-8.8771619E-03
39	1.4811466E-03	-3.0784123E-04	-7.4514151E-03
40	1.4810888E-03	3.0894089E-04	-7.4511021E-03
41	1.7317953E-03	-3.3979258E-04	-5.6911409E-03
42	1.7316977E-03	3.4115440E-04	-5.6909099E-03
43	1.9289383E-03	-3.6838348E-04	-3.7480451E-03
44	1.9288501E-03	3.7009967E-04	-3.7478020E-03
45	-1.4385977E-03	-1.6514414E-04	-6.8438686E-03
46	-1.4386380E-03	1.6520663E-04	-6.8435557E-03
47	-1.3081105E-03	-1.4886331E-04	-8.5816644E-03
48	-1.3081587E-03	1.4912240E-04	-8.5813478E-03
49	-1.1065099E-03	-1.2930391E-04	-1.0192931E-02
50	-1.1065663E-03	1.2975477E-04	-1.0192588E-02

STRESSES FOR ISOLATOR AND ARRESTOR FOR TILE NO. 1 AND ITERATION NO. 3

	LOCAL COORDINATES X	Y	Z	STRESSES XX	YY	ZZ	XY	YZ	ZX
			ELEMENT NUMBER	1					
1	5.2578E-01	2.6289E-01	3.9434E-02	-1.0207E 02	-1.0199E 02	-1.0637E 02	-5.3123E-04	1.1811E-01	-1.8883E 00
2	5.2578E-01	7.0441E-02	3.9434E-02	-1.0208E 02	-1.0199E 02	-1.0637E 02	5.3182E-04	-1.1782E-01	-1.8883E 00
3	1.4088E-01	2.6289E-01	3.9434E-02	-1.0642E 02	-1.0633E 02	-1.1089E 02	-5.3092E-04	1.2610E-01	-1.9813E 00
4	1.4088E-01	7.0441E-02	3.9434E-02	-1.0642E 02	-1.0633E 02	-1.1090E 02	5.3209E-04	-1.2589E-01	-1.9813E 00
5	5.2578E-01	2.6289E-01	1.0566E-02	-1.0416E 02	-1.0413E 02	-1.0844E 02	7.0903E-05	1.1810E-01	-1.8952E 00
6	5.2578E-01	7.0441E-02	1.0566E-02	-1.0417E 02	-1.0414E 02	-1.0845E 02	-7.1102E-05	-1.1783E-01	-1.8951E 00
7	1.4088E-01	2.6289E-01	1.0566E-02	-1.0863E 02	-1.0860E 02	-1.1309E 02	7.1124E-05	1.2609E-01	-1.9881E 00
8	1.4088E-01	7.0441E-02	1.0566E-02	-1.0863E 02	-1.0860E 02	-1.1309E 02	-7.0886E-05	-1.2590E-01	-1.9881E 00
			ELEMENT NUMBER	2					
1	1.1925E 00	2.6289E-01	3.9434E-02	-9.5839E 01	-9.5761E 01	-9.9871E 01	-6.1842E-04	1.0427E-01	-1.6344E 00
2	1.1925E 00	7.0441E-02	3.9434E-02	-9.5843E 01	-9.5766E 01	-9.9875E 01	6.1785E-04	-1.0382E-01	-1.6344E 00
3	8.0755E-01	2.6289E-01	3.9434E-02	-9.9211E 01	-9.9129E 01	-1.0339E 02	-6.1797E-04	1.1226E-01	-1.7890E 00
4	8.0755E-01	7.0441E-02	3.9434E-02	-9.9215E 01	-9.9133E 01	-1.0339E 02	6.1828E-04	-1.1191E-01	-1.7889E 00
5	1.1925E 00	2.6289E-01	1.0566E-02	-9.7959E 01	-9.7921E 01	-1.0197E 02	-1.6868E-05	1.0426E-01	-1.6398E 00
6	1.1925E 00	7.0441E-02	1.0566E-02	-9.7963E 01	-9.7925E 01	-1.0197E 02	1.3852E-05	-1.0383E-01	-1.6398E 00
7	8.0755E-01	2.6289E-01	1.0566E-02	-1.0145E 02	-1.0141E 02	-1.0560E 02	-1.6456E-05	1.1224E-01	-1.7943E 00
8	8.0755E-01	7.0441E-02	1.0566E-02	-1.0145E 02	-1.0142E 02	-1.0561E 02	1.4265E-05	-1.1192E-01	-1.7943E 00
			ELEMENT NUMBER	3					
1	1.8591E 00	2.6289E-01	3.9434E-02	-9.1963E 01	-9.1902E 01	-9.5846E 01	-5.5080E-04	9.2099E-02	-1.2399E 00
2	1.8591E 00	7.0441E-02	3.9434E-02	-9.1967E 01	-9.1906E 01	-9.5850E 01	5.5449E-04	-9.1456E-02	-1.2399E 00
3	1.4742E 00	2.6289E-01	3.9434E-02	-9.3739E 01	-9.3674E 01	-9.7699E 01	-5.5190E-04	9.8869E-02	-1.4756E 00
4	1.4742E 00	7.0441E-02	3.9434E-02	-9.3743E 01	-9.3678E 01	-9.7704E 01	5.5337E-04	-9.8341E-02	-1.4756E 00
5	1.8591E 00	2.6289E-01	1.0566E-02	-9.4213E 01	-9.4172E 01	-9.8061E 01	-4.2444E-05	9.2087E-02	-1.2428E 00
6	1.8591E 00	7.0441E-02	1.0566E-02	-9.4217E 01	-9.4176E 01	-9.8065E 01	3.8778E-05	-9.1469E-02	-1.2428E 00
7	1.4742E 00	2.6289E-01	1.0566E-02	-9.6090E 01	-9.6048E 01	-1.0001E 02	-4.2228E-05	9.8850E-02	-1.4785E 00
8	1.4742E 00	7.0441E-02	1.0566E-02	-9.6094E 01	-9.6052E 01	-1.0002E 02	3.9002E-05	-9.8354E-02	-1.4785E 00
			ELEMENT NUMBER	4					
1	2.5258E 00	2.6289E-01	3.9434E-02	-8.9875E 01	-8.9827E 01	-9.3683E 01	-3.3072E-04	8.4091E-02	-7.2296E-01
2	2.5258E 00	7.0441E-02	3.9434E-02	-8.9879E 01	-8.9831E 01	-9.3687E 01	3.2842E-04	-8.3348E-02	-7.2297E-01
3	2.1409E 00	2.6289E-01	3.9434E-02	-9.0789E 01	-9.0738E 01	-9.4637E 01	-3.3245E-04	8.8140E-02	-1.0210E 00
4	2.1409E 00	7.0441E-02	3.9434E-02	-9.0793E 01	-9.0742E 01	-9.4642E 01	3.2670E-04	-8.7439E-02	-1.0210E 00
5	2.5258E 00	2.6289E-01	1.0566E-02	-9.2246E 01	-9.2203E 01	-9.6009E 01	-2.8702E-05	8.4080E-02	-7.2446E-01
6	2.5258E 00	7.0441E-02	1.0566E-02	-9.2250E 01	-9.2207E 01	-9.6013E 01	1.9976E-05	-8.3359E-02	-7.2447E-01
7	2.1409E 00	2.6289E-01	1.0566E-02	-9.3220E 01	-9.3177E 01	-9.7023E 01	-2.9040E-05	8.8128E-02	-1.0225E 00
8	2.1409E 00	7.0441E-02	1.0566E-02	-9.3224E 01	-9.3181E 01	-9.7027E 01	1.9641E-05	-8.7451E-02	-1.0225E 00
			ELEMENT NUMBER	5					
1	3.1924E 00	2.6289E-01	3.9434E-02	-8.9055E 01	-8.9013E 01	-9.2836E 01	-1.1282E-04	8.0732E-02	-1.3450E-01
2	3.1924E 00	7.0441E-02	3.9434E-02	-8.9058E 01	-8.9016E 01	-9.2839E 01	1.1020E-04	-7.9979E-02	-1.3451E-01
3	2.8075E 00	2.6289E-01	3.9434E-02	-8.9336E 01	-8.9293E 01	-9.3129E 01	-1.1276E-04	8.2106E-02	-4.6519E-01
4	2.8075E 00	7.0441E-02	3.9434E-02	-8.9340E 01	-8.9297E 01	-9.3133E 01	1.1025E-04	-8.1349E-02	-4.6521E-01
5	3.1924E 00	2.6289E-01	1.0566E-02	-9.1501E 01	-9.1458E 01	-9.5232E 01	-1.1352E-05	8.0721E-02	-1.3496E-01
6	3.1924E 00	7.0441E-02	1.0566E-02	-9.1505E 01	-9.1461E 01	-9.5236E 01	5.7775E-06	-7.9989E-02	-1.3498E-01
7	2.8075E 00	2.6289E-01	1.0566E-02	-9.1802E 01	-9.1759E 01	-9.5546E 01	-1.1707E-05	8.2095E-02	-4.6566E-01
8	2.8075E 00	7.0441E-02	1.0566E-02	-9.1806E 01	-9.1762E 01	-9.5549E 01	5.4171E-06	-8.1360E-02	-4.6567E-01

STRESSES AND DIRECT STRAINS FOR TILE NO. 1 AND ITERATION NO. 3

MEM	TEMP	LOCAL COORDINATES X	Y	Z	* STRAINS XX	STRAINS YY	STRAINS ZZ *	STRESSES XX	STRESSES YY	STRESSES ZZ	STRESSES XY	STRESSES YZ	STRESSES ZX *
1	0.	0.33	0.17	0.02	9.585E-05	1.080E-03	-7.235E-02	-1.053E 02	-1.053E 02	-1.097E 02	2.936E-07	1.191E-04	-1.938E 00
2	0.	1.00	0.17	0.02	4.356E-05	1.017E-03	-6.770E-02	-9.862E 01	-9.856E 01	-1.027E 02	-5.192E-07	1.937E-04	-1.714E 00
3	0.	1.67	0.17	0.02	8.245E-05	9.467E-04	-6.455E-02	-9.400E 01	-9.395E 01	-9.791E 01	-1.578E-07	2.868E-04	-1.359E 00
4	0.	2.33	0.17	0.02	1.272E-04	8.923E-04	-6.288E-02	-9.153E 01	-9.149E 01	-9.534E 01	-3.234E-06	3.552E-04	-8.728E-01
5	0.	3.00	0.17	0.02	1.528E-04	8.652E-04	-6.213E-02	-9.043E 01	-9.038E 01	-9.419E 01	-2.106E-06	3.723E-04	-3.001E-01
6	0.	3.67	0.17	0.02	1.529E-04	8.651E-04	-6.213E-02	-9.042E 01	-9.038E 01	-9.419E 01	-3.797E-07	3.805E-04	3.021E-01
7	0.	4.33	0.17	0.02	1.272E-04	8.923E-04	-6.288E-02	-9.153E 01	-9.149E 01	-9.534E 01	1.979E-06	3.943E-04	8.749E-01
8	0.	5.00	0.17	0.02	8.240E-05	9.467E-04	-6.455E-02	-9.400E 01	-9.395E 01	-9.791E 01	-1.086E-07	3.910E-04	1.361E 00
9	0.	5.67	0.17	0.02	4.353E-05	1.017E-03	-6.770E-02	-9.862E 01	-9.856E 01	-1.027E 02	1.093E-06	4.068E-04	1.717E 00
10	0.	6.33	0.17	0.02	9.583E-05	1.080E-03	-7.235E-02	-1.053E 02	-1.053E 02	-1.097E 02	1.797E-06	4.678E-04	1.941E 00
11	0.	0.33	0.17	0.13	2.457E-04	1.536E-03	-1.796E-02	6.900E 00	-1.350E 01	-1.091E 02	3.719E-04	0.0	-6.084E-01
12	0.	1.00	0.17	0.13	3.391E-04	1.391E-03	-1.690E-02	1.298E 01	-1.269E 01	-1.026E 02	1.630E-05	0.0	-4.286E 00
13	0.	1.67	0.17	0.13	5.160E-04	1.245E-03	-1.617E-02	2.434E 01	-1.127E 01	-9.814E 01	1.440E-03	1.192E-04	-3.681E 00
14	0.	2.33	0.17	0.13	6.702E-04	1.134E-03	-1.575E-02	3.398E 01	-1.055E 01	-9.555E 01	-9.354E-04	3.576E-04	-2.308E 00
15	0.	3.00	0.17	0.13	7.545E-04	1.076E-03	-1.557E-02	3.921E 01	-1.022E 01	-9.441E 01	-6.228E-04	1.192E-04	-7.972E-01
16	0.	3.67	0.17	0.13	7.546E-04	1.076E-03	-1.557E-02	3.922E 01	-1.022E 01	-9.441E 01	2.296E-04	-2.384E-04	7.973E-01
17	0.	4.33	0.17	0.13	6.703E-04	1.133E-03	-1.575E-02	3.399E 01	-1.055E 01	-9.555E 01	9.764E-04	0.0	2.309E 00
18	0.	5.00	0.17	0.13	5.161E-04	1.245E-03	-1.617E-02	2.435E 01	-1.127E 01	-9.814E 01	-2.149E-03	0.0	3.683E 00
19	0.	5.67	0.17	0.13	3.392E-04	1.391E-03	-1.690E-02	1.298E 01	-1.269E 01	-1.026E 02	6.519E-05	-4.768E-04	4.289E 00
20	0.	6.33	0.17	0.13	2.457E-04	1.536E-03	-1.796E-02	6.899E 00	-1.351E 01	-1.091E 02	-3.591E-04	3.576E-04	6.114E-01
21	0.	0.33	0.17	0.30	1.795E-04	5.480E-04	-1.809E-02	1.466E 01	2.940E 01	-1.081E 02	8.804E-06	9.537E-04	-3.354E 00
22	0.	1.00	0.17	0.30	2.667E-04	4.739E-04	-1.712E-02	1.985E 01	2.813E 01	-1.022E 02	-1.496E-04	4.768E-04	-6.014E 00
23	0.	1.67	0.17	0.30	3.802E-04	3.934E-04	-1.650E-02	2.645E 01	2.698E 01	-9.849E 01	5.023E-04	1.192E-03	-5.991E 00
24	0.	2.33	0.17	0.30	4.846E-04	3.278E-04	-1.611E-02	3.267E 01	2.640E 01	-9.606E 01	-7.947E-04	1.550E-03	-3.981E 00
25	0.	3.00	0.17	0.30	5.452E-04	2.917E-04	-1.593E-02	3.629E 01	2.615E 01	-9.497E 01	-9.113E-04	9.537E-04	-1.382E 00
26	0.	3.67	0.17	0.30	5.452E-04	2.916E-04	-1.593E-02	3.629E 01	2.615E 01	-9.497E 01	-3.716E-04	5.960E-04	1.381E 00
27	0.	4.33	0.17	0.30	4.847E-04	3.278E-04	-1.611E-02	3.268E 01	2.640E 01	-9.606E 01	5.352E-04	1.669E-03	3.982E 00
28	0.	5.00	0.17	0.30	3.802E-04	3.934E-04	-1.650E-02	2.646E 01	2.698E 01	-9.849E 01	-2.003E-03	1.073E-03	5.992E 00
29	0.	5.67	0.17	0.30	2.667E-04	4.739E-04	-1.712E-02	1.985E 01	2.814E 01	-1.022E 02	1.150E-03	2.384E-04	6.016E 00
30	0.	6.33	0.17	0.30	1.796E-04	5.480E-04	-1.809E-02	1.466E 01	2.940E 01	-1.081E 02	-1.303E-03	1.073E-03	3.353E 00
31	0.	0.33	0.17	0.47	1.630E-04	1.687E-04	-1.776E-02	-1.525E 00	-1.298E 00	-1.066E 02	-9.051E-05	1.073E-03	-4.480E 00
32	0.	1.00	0.17	0.47	2.020E-04	1.397E-04	-1.700E-02	1.345E 00	-1.144E 00	-1.020E 02	-4.547E-06	5.960E-04	-7.424E 00
33	0.	1.67	0.17	0.47	2.617E-04	1.036E-04	-1.647E-02	5.318E 00	-1.006E 00	-9.879E 01	-1.585E-04	9.537E-04	-7.283E 00
34	0.	2.33	0.17	0.47	3.185E-04	7.112E-05	-1.614E-02	8.972E 00	-9.214E-01	-9.675E 01	-4.950E-04	-1.192E-03	-5.087E 00
35	0.	3.00	0.17	0.47	3.537E-04	5.197E-05	-1.598E-02	1.122E 01	-8.512E-01	-9.578E 01	-8.814E-04	-5.125E-03	-1.790E 00
36	0.	3.67	0.17	0.47	3.537E-04	5.197E-05	-1.598E-02	1.122E 01	-8.499E-01	-9.578E 01	-5.726E-04	-6.437E-03	1.784E 00
37	0.	4.33	0.17	0.47	3.185E-04	7.112E-05	-1.614E-02	8.973E 00	-9.205E-01	-9.674E 01	2.467E-04	-2.503E-03	5.085E 00
38	0.	5.00	0.17	0.47	2.617E-04	1.036E-04	-1.647E-02	5.319E 00	-1.005E 00	-9.879E 01	-1.462E-03	2.384E-04	7.280E 00
39	0.	5.67	0.17	0.47	2.020E-04	1.397E-04	-1.700E-02	1.347E 00	-1.143E 00	-1.020E 02	9.932E-04	7.153E-04	7.429E 00
40	0.	6.33	0.17	0.47	1.631E-04	1.687E-04	-1.776E-02	-1.523E 00	-1.297E 00	-1.066E 02	-1.930E-03	9.537E-04	4.479E 00
41	0.	0.33	0.17	0.63	1.591E-04	1.841E-04	-1.748E-02	-8.900E-01	1.132E-01	-1.049E 02	3.851E-04	6.345E-04	-4.093E 00
42	0.	1.00	0.17	0.63	1.495E-04	1.784E-04	-1.695E-02	-1.240E 00	-8.444E-02	-1.017E 02	-4.912E-04	-1.431E-03	-7.991E 00
43	0.	1.67	0.17	0.63	1.549E-04	1.700E-04	-1.652E-02	-6.298E-01	-2.678E-02	-9.913E 01	-6.954E-05	-6.557E-03	-7.885E 00
44	0.	2.33	0.17	0.63	1.669E-04	1.603E-04	-1.625E-02	2.548E-01	-1.831E-03	-9.750E 01	-4.433E-04	-6.914E-03	-5.598E 00
45	0.	3.00	0.17	0.63	1.760E-04	1.541E-04	-1.612E-02	9.046E-01	2.884E-02	-9.671E 01	-8.515E-04	-6.199E-03	-2.003E 00
46	0.	3.67	0.17	0.63	1.760E-04	1.541E-04	-1.612E-02	9.059E-01	2.921E-02	-9.672E 01	-1.047E-03	-7.510E-03	1.997E 00
47	0.	4.33	0.17	0.63	1.668E-04	1.603E-04	-1.625E-02	2.546E-01	-2.365E-03	-9.750E 01	4.299E-04	-6.795E-03	5.593E 00
48	0.	5.00	0.17	0.63	1.549E-04	1.700E-04	-1.652E-02	-6.299E-01	-2.676E-02	-9.913E 01	-1.312E-03	-7.272E-03	7.880E 00
49	0.	5.67	0.17	0.63	1.496E-04	1.784E-04	-1.695E-02	-1.238E 00	-8.260E-02	-1.017E 02	8.567E-04	-2.861E-03	7.993E 00
50	0.	6.33	0.17	0.63	1.591E-04	1.841E-04	-1.748E-02	-8.856E-01	1.147E-01	-1.049E 02	-1.027E-03	2.742E-03	4.090E 00

TOP-POINT PLATE MEMBER STRAINS AND STRESSES FOR ITERATION NO. 3

MEMBER	COORDINATES X	COORDINATES Y	STRAINS EPS X	STRAINS EPS Y	STRAINS EPS XY	STRESSES SIG X	STRESSES SIG Y	STRESSES SIG XY
1	3.3333E-01	1.6666E-01	-1.0400E-04	3.0404E-05	-1.7294E-09	-1.0426E 03	-8.7436E 00	-1.2353E-02
2	1.0000E 00	1.6666E-01	-2.8878E-04	8.7388E-05	-2.8538E-08	-2.8853E 03	8.3048E 00	-2.0384E-01
3	1.6667E 00	1.6666E-01	-4.2433E-04	1.2777E-04	-4.6300E-08	-4.2418E 03	5.1730E 00	-3.3071E-01
4	2.3333E 00	1.6666E-01	-5.1380E-04	1.5463E-04	-9.0042E-08	-5.1364E 03	5.3959E 00	-6.4315E-01
5	3.0000E 00	1.6666E-01	-5.5836E-04	1.6799E-04	-5.9231E-08	-5.5820E 03	5.3321E 00	-4.2308E-01
6	3.6667E 00	1.6666E-01	-5.5836E-04	1.6798E-04	-2.0045E-08	-5.5821E 03	5.1957E 00	-1.4318E-01
7	4.3333E 00	1.6666E-01	-5.1398E-04	1.5468E-04	4.8764E-08	-5.1382E 03	5.3562E 00	3.4832E-01
8	5.0000E 00	1.6666E-01	-4.2456E-04	1.2785E-04	4.8311E-08	-4.2440E 03	5.2606E 00	3.4508E-01
9	5.6667E 00	1.6666E-01	-2.8889E-04	8.7418E-05	5.5284E-08	-2.8864E 03	8.2066E 00	3.9489E-01
10	6.3333E 00	1.6666E-01	-1.0406E-04	3.0421E-05	6.6454E-08	-1.0432E 03	-8.7649E 00	4.7467E-01

BOTTOM-POINT PLATE MEMBER STRAINS AND STRESSES FOR ITERATION NO. 3

MEMBER	COORDINATES X	Y	STRAINS EPS X	EPS Y	EPS XY	STRESSES SIG X	SIG Y	SIG XY
1	3.3333E-01	1.6666E-01	1.0467E-04	-2.9974E-05	2.5926E-09	1.0514E 03	1.5686E 01	1.8519E-02
2	1.0000E 00	1.6666E-01	2.8974E-04	-8.7068E-05	2.6673E-08	2.8969E 03	-1.6196E 00	1.9052E-01
3	1.6667E 00	1.6666E-01	4.2555E-04	-1.2756E-04	4.6589E-08	4.2559E 03	1.1875E 00	3.3278E-01
4	2.3333E 00	1.6666E-01	5.1521E-04	-1.5449E-04	8.9941E-08	5.1523E 03	8.0867E-01	6.4243E-01
5	3.0000E 00	1.6666E-01	5.5987E-04	-1.6789E-04	5.9203E-08	5.5989E 03	8.0227E-01	4.2288E-01
6	3.6667E 00	1.6666E-01	5.5987E-04	-1.6787E-04	2.0064E-08	5.5989E 03	9.3916E-01	1.4331E-01
7	4.3333E 00	1.6666E-01	5.1539E-04	-1.5454E-04	-4.8651E-08	5.1541E 03	8.4817E-01	-3.4751E-01
8	5.0000E 00	1.6666E-01	4.2578E-04	-1.2763E-04	-4.8670E-08	4.2581E 03	1.0976E 00	-3.4764E-01
9	5.6667E 00	1.6666E-01	2.8985E-04	-8.7097E-05	-5.3558E-08	2.8980E 03	-1.5727E 00	-3.8256E-01
10	6.3333E 00	1.6666E-01	1.0473E-04	-2.9991E-05	-6.2518E-08	1.0520E 03	1.5701E 01	-4.4656E-01

APPENDIX C

FINITE ELEMENT TYPES USED IN RE*S*I*ST

The active degrees-of-freedom (dof) for an element are defined as the dof for which there is at least one nonzero term in the corresponding row of the element stiffness matrix. The nodes and active dof per node, for each type element included in the RESIST computer program, are defined in (Figures C-1 through C-4).



- BENDING AND MEMBRANE STIFFNESS
- FOUR NODES AT PLATE MIDDLE SURFACE
- ACTIVE DOF PER NODE ARE x, y AND z DEFLECTIONS AND x AND y ROTATIONS
- LUMPED MASSES AT NODES

Figure C-1 Primary Structure Isotropic Plate Element



- ARBITRARY CROSS SECTION BENDING, TWISTING AND AXIAL STIFFNESS
- TWO CENTROIDAL NODES AND TWO ATTACHMENT NODES
- ACTIVE DOF ARE x, y AND z DEFLECTIONS AND ROTATIONS AT ATTACHMENT NODES ONLY. NO ACTIVE DOF AT CENTROIDAL NODES
- LUMPED MASSES AT CENTROIDAL NODES

Figure C-2 Primary Structure Uniform Stiffener Element



- THREE DIMENSIONAL STIFFNESS ELEMENT
- EIGHT CORNER NODES
- ACTIVE DOF PER NODE ARE x, y AND z DEFLECTIONS
- LUMPED MASSES AT CORNER NODES

Figure C-3 Three Dimensional Orthotropic TPS Element



- TWO DIMENSIONAL MEMBRANE ELEMENT
- FOUR CORNER NODES
- ACTIVE DOF PER NODE ARE x AND y DEFLECTIONS ONLY
- INERTIA EFFECTS NEGLECTED FOR THESE ELEMENTS

Figure C-4 TPS Thin Membrane Coating Element

GRUMMAN AEROSPACE CORPORATION
BETHPAGE, NEW YORK 11714

2008-74